

JOINT SEALANTS AND EXPANSION JOINTS

OUR JOINT SEALANTS AND EXPANSION JOINTS WILL PROTECT YOUR POOL DECK FROM CONCRETE MOVEMENT AND WATER INTRUSION, WHILE ALSO MAINTAINING THE AESTHETIC LOOK OF YOUR DECK



Seal all cracks and joints with DECK-O-SEAL two-part, elastomeric, polysulfide-based joint sealant. It is ideal for sealing joints in and around swimming pools, and is applicable for both interior and exterior applications under compression or elongation.

DECK-O-SEAL is available in a variety of formulations to meet every need in pool deck construction.

DECK-O-SEAL



DECK-O-SEAL two-part, polysulfide-based joint sealant is a premium-grade, pourable, self-leveling sealant.

DECK-O-SEAL 125



DECK-O-SEAL 125 two-part, pourable joint sealant is a self-leveling, polysulfide-based sealing compound. It is a non-staining sealant that cures to a firm, flexible, tear-resistant rubber. DECK-O-SEAL 125 is a self-leveling product that is engineered for submerged applications and heavy traffic areas.

DECK-O-SEAL GUN GRADE



is a two-component, non-sag, non-flowing, polysulfide-based sealing compound. It is designed for vertical applications as well as submerged applications.

PRODUCT COVERAGE

THIS CHART SHOWS THE APPROXIMATE NUMBER OF LINEAL FEET WHICH CAN BE SEALED WITH A 96 OUNCE DECK-O-SEAL KIT.

WIDTH OF JOINT

	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/4"	231	154	106	92	77	66	58
3/8"		102	77	62	51	44	38
1/2"			58	46	38	33	29
5/8"				37	31	26	23
3/4"					26	22	19
7/8"						19	17
1"							14

