



PROTECTO TRIPLE GUARD ENERGY SILL SEALER®

A cold applied self-adhering membrane composed of a 3/8" closed cell foam gasket laminated with two peel and stick flaps that seal to the foundation and to the exterior framed wall assembly. The bottom flap incorporates our proprietary high temperature asphalt blend adhesive and the top flap incorporates our Super Stick adhesive technology to provide an aggressive bond to the exterior framing and/or sheathing once the wall is set into place.

- Helps lower energy costs by reducing heating and air conditioning loss at the foundation to sill plate interface
- Virtually eliminates air, moisture and insect/rodent infiltration between the sill plate and foundation
- Helps eliminate costly call backs due to leaks
- Roll sizes available: 3.5", 5.5" x 25' • High temperature: 240°F



PROTECTO DUAL GUARD THRESHOLD TAPE™

Protecto Premium Dual Guard Threshold Tape with its unique flange acts like a gasket, sealing off the sub-floor and preventing air and moisture infiltration under the threshold. Helps keep the door frame from racking and the sub-floor from swelling and warping.

- Waterproofing and energy savings in one step
- Exceeds all building codes and manufacturers installation specifications
- Reduces energy costs
- Prevents air, moisture and insect infiltration under the threshold
- Adheres to concrete, wood and metal surfaces
- Helps prevent subfloors from swelling and structural framing from warping
- Roll sizes available: 5.5" x 6.5' and 5.5" x 25' • High temperature: 240°F



PROTECTO ENERGY PLATE LINER®

Designed specifically for conforming and sealing off the air gaps between the floor deck and the exterior wall plates. The unique peel and stick adhesive bottom allows for easy and precise placement. The 1/4" closed cell foam forms a gasket seal beneath the exterior wall plate virtually eliminating any air drafts resulting in a large amount of heating and air conditioning energy savings.

- The only peel and stick 1/4" closed cell foam plate liner that totally stops air and moisture infiltration between the wood floor and wall plate
- Helps reduce energy costs by stopping air conditioning and heating loss between the wood floor and the wall plate
- Conforms and seals off irregularities between substrates (i.e. warped wood to wood, metal frame to concrete, etc.)
- Roll sizes available: 3.5", 5.5" x 25' • High temperature: 240°F



PROTECTO PREMIUM ENERGY SILL SEALER®

A full 3/8" closed cell polyethylene foam with an aggressive self adhesive waterproofing membrane that conforms and seals off the voids and irregularities between the top of the foundation and sill plate. This unique and patented design combines the peel and stick waterproofing characteristics of Protecto Wrap's waterproofing membrane with a 3/8" thick foam sill sealer forming a gasket seal virtually eliminating any air, moisture and insect/rodent infiltration beneath the sill plate.

- The adhesive bottom conforms and seals to the uneven top of the foundation wall
- Helps lower energy costs by stopping hot and cold air loss at the foundation to sill plate interface
- Mildew and water resistant – will help prevent sill plate rot
- A full 3/8" closed cell foam provides 1-1/2 times more protection from energy loss over standard 1/4" sill sealers used by builders today
- Roll sizes available: 3.5", 5.5" x 25' • High temperature: 240°F