

## COLPHENE® LIQUID MEMBRANE

COLPHENE® Liquid Membrane is a two component, elastomeric, solvent-free, cold applied material used in conjunction with a variety of waterproofing membranes. COLPHENE® Liquid Membrane is designed to be used as an adhesive to seal end-laps and/or reinforcement at penetrations and membrane terminations.

### INSTALLATION

COLPHENE Liquid Membrane is packaged in cartridges. It is applied via pneumatic cartridge applicator.

### COLPHENE LIQUID MEMBRANE

PRODUCT CODE

A191

Scan QR code with the SOPREMA toolbox app for more information.



## COLPLY® EF ADHESIVE

COLPLY EF Adhesive is a high performance, single-component polymeric adhesive for use with SBS-modified bitumen membrane systems. Due to its polymer composition, once cured, COLPLY EF Adhesive provides an additional layer of elastomeric waterproofing protection beneath or between membrane plies. COLPLY EF (environmentally friendly) Adhesive is unique in that it is a solvent-free and ultra-low VOC material allowing for application flexibility on job sites where exposure to VOC's or odor may be a concern.

### INSTALLATION

COLPLY EF Adhesive is applied to approved, compatible substrates using ¼ inch notched neoprene squeegees or trowels. Apply COLPLY EF Adhesive at 1.5 to 2 gallons per 100 square feet for sand-surfaced interply applications. When the ambient temperature is below 50°F (10°C), material should be warmed to a temperature of 70°F (24°C) at the time of application.

### COLPLY EF ADHESIVE

PRODUCT CODE

A216

Scan QR code with the SOPREMA toolbox app for more information.

