

L&M™ JOINT TITE 750™

Refer to Data Sheet 176.5
7-40-752-1474/7-40-752-1475/7-40-752-1472



L&M™ JOINT TITE 750™ is a self-leveling, 100% solids, two component, rapid curing, polyurea control joint and crack filler. L&M JOINT TITE 750 is designed to fill interior random cracks, damaged control joints, saw cut control joints, and construction joints in industrial concrete floors. L&M JOINT TITE 750 is designed specifically for commercial, retail, and manufacturing floor applications which receive high volume vehicle traffic, such as fork lift or hard rubber wheel carts.

FEATURES/BENEFITS:

- Rapid cure
- Accepts dye
- Excellent shore hardness
- Versatile material used in concrete cracks, joints, and spalls

PACKAGING

The L&M JOINT TITE 750 system consists of two component units packaged as follows: 10 gal (37.9 L) Unit: 5 gal (18.9 L) of "A" side and 5 gal. (18.9 L) of "B" side. Also available in a 20 oz (600 ml) dual cartridges with static mixing nozzle.

APPROXIMATE COVERAGE
Linear Feet (Meters) per Gallon (3.8 L)

JOINT DEPTH	JOINT OPENING/WIDTH			
	1/8" (3 mm)	3/16" (4.7 mm)	1/4" (6.3 mm)	3/8" (9.5 mm)
3/4" (19 mm)	200 ft (60.9 m)	135 ft (41.1 m)	100 ft (30.5 m)	70 ft (21.3 m)
1" (25 mm)	150 ft (45.7 m)	100 ft (30.5 m)	80 ft (24.4 m)	50 ft (15.2 m)
1-1/2" (38 mm)	100 ft (30.5 m)	70 ft (21.3 m)	50 ft (15.2 m)	34 ft (10.4 m)
2" (51 mm)	75 ft (22.9 m)	50 ft (15.2 m)	40 ft (12.2 m)	25 ft (7.6 m)

Note: Does not figure in waste for overfill.

APPROXIMATE COVERAGE Linear Feet (Meters) per 600 ml Cartridge

JOINT DEPTH	JOINT OPENING/WIDTH					
	1/8" (3 mm)	1/4" (6.3 mm)	3/8" (9.5 mm)	1/2" (12 mm)	3/4" (19 mm)	1" (25.4 mm)
1/2" (12 mm)	48 ft (14.6 m)	24 ft (7.3 m)	16 ft (4.8 m)	12 ft (3.6 m)	8 ft (2.4 m)	6 ft (1.8 m)
3/4" (19 mm)	32 ft (9.7 m)	16 ft (4.8 m)	10.7 ft (3.2 m)	8 ft (2.4 m)	5.3 ft (1.6 m)	4 ft (1.2 m)
1" (25 mm)	24 ft (7.3 m)	12 ft (3.6 m)	8 ft (2.4 m)	6 ft (1.8 m)	4 ft (1.2 m)	3 ft (0.9 m)
1-1/4" (32 mm)	19 ft (5.8 m)	9.6 ft (3.0 m)	6.4 ft (2 m)	4.8 ft (1.4 m)	3.2 ft (0.9 m)	2.4 ft (0.7 m)
1-1/2" (38 mm)	16 ft (4.8 m)	8 ft (2.4 m)	5.3 ft (1.6 m)	4 ft (1.2 m)	2.7 ft (0.8 m)	2 ft (0.6 m)
1-3/4" (44 mm)	13.7 ft (4.1 m)	6.9 ft (2.1 m)	4.6 ft (1.4 m)	3.4 ft (1.0 m)	2.3 ft (0.7 m)	1.7 ft (0.5 m)
2" (51 mm)	12 ft (3.6 m)	6 ft (1.8 m)	4 ft (1.2 m)	3 ft (0.9 m)	2 ft (0.6 m)	1.5 ft (0.4 m)

Note: Does not figure in waste for overfill.

LATASIL™ sealants are available in all 40 colors:

Note: Grout color availability subject to change. Visit www.laticrete.com for the most current color selections. See page 78 for color chart.

LATASIL™

Refer to Data Sheet 6200.1
62XX

See page 77 for further details



LATASIL 9118 PRIMER

Refer to Data Sheet 6528.1
9118-0601-2

See page 77 for further details



A 100% silicone sealant for use in covers, corners, changes in plane, and expansion joints in exterior and interior applications of tile and stone. LATASIL™ silicone sealant is now available in 40 colors, plus clear.

A single component, primer adhesive designed to increase the adhesion of porous stone or permanently wet/underwater applications.