

■ Sure-Seal, Sure-White, and Sure-Tough EPDM

■ Sure-Weld TPO

■ Sure-Flex PVC

■ FleeceBACK

■ Multiple-Ply Systems

■ Low-VOC Product

## Sure-Weld TPO Bonding Adhesive



A high-strength, solvent-based contact adhesive that allows bonding of Sure-Weld membrane to various porous and non-porous substrates.

**Coverage Rate:** 60 square feet per gallon of finished surface.

**Packaging:** 5-gallon pail

**Product Number:** 302099

**Shelf Life:** 12 months



## TPO Primer



A high-solids, clear polymer-based primer used to prepare TPO membrane prior to the application of Pressure-Sensitive (PS) products.

**Coverage Rate:** 200 – 250 square feet (one surface) per gallon.

**Packaging:** (6) 1-gallon cans

**Product Number:** 310471

**Shelf Life:** 12 months unopened can



## Universal Single-Ply Sealant



A 100%-solids, solvent-free, one-part, polyether sealant that provides a weathertight seal to a variety of building substrates.

**Coverage Rate:** 25' per tube or 600' per carton using a 1/4" bead.

**Packaging:** 24 Tubes/carton

**Product Number:** 310131

**Shelf Life:** 12 months unopened container (@ <90°F)



## X-Tenda Coat Classic Acrylic Coating

A 100% acrylic, single-component, water-based, premium quality elastomeric coating for spray, brush, or roller application. This product is designed to provide protection for a wide range of building surfaces such as roofs, vertical walls, and masonry. It is excellent for waterproofing and restoring existing roof systems. Available in White, Light Gray, Dark Gray and Tan.

**Packaging:** 5-gallon pail/55-gallon drum

## X-Tenda Coat XTRA Silicone Coating

A single-component, moisture-cured, fluid-applied silicone coating that is specially formulated to meet low-VOC requirements. Once cured, the silicone coating membrane offers excellent resistance to water intrusion, UV exposure, and natural weathering. It is excellent for waterproofing and restoring existing roof systems. Available in White, Light Gray, Dark Gray, Tan, Santa Fe Tan, and Terra Cotta.

**Packaging:** 5-gallon pail/50-gallon drum

## Water Cut-Off Mastic



A one-component, low-viscosity, self-wetting, butyl-blend mastic used in conjunction with roofing and waterproofing systems. It is used as a sealing agent between various membranes and substrates for compression-type terminations.

**Coverage Rate:** 10' per tube, using a 7/16" bead.

**Packaging:** 25 Tubes/carton

**Product Number:** 319621

**Shelf Life:** 12 months unopened container



## Weathered Membrane Cleaner



Used to clean both new and in-service EPDM and TPO membranes prior to seaming or application of Pressure-Sensitive (PS) products. Helps to loosen and remove dirt and other contaminants from the surface of the membranes and leaves a suitable surface for application of adhesive or primer. Please refer to the Product Data Sheets for specific instructions for EPDM and TPO applications.

**Coverage Rate:** 400 square feet (one surface) per gallon.

**Packaging:**

(2) 1-gallon closed-top cans,

5-gallon closed-top pail

1-gallon cans

**Product Number:** 304066 5-gallon pail

**Product Number:** 302074



## Low-VOC Membrane Cleaner



Use to clean both new and in-service, PVC, KEE HP, TPO, and EPDM membranes prior to the seaming process. Low-VOC Membrane Cleaner contains 100% EPA-exempted solvents and can be used in a wide variety of temperatures.

**Packaging:** 1-gallon can (2) & 5-gallon can

**Product Number:**

326160 1-gallon can (2)

326860 5-gallon can



\*\* Certain restrictions apply, see Product Data Sheet.

\* Not compliant in all CA counties