

SOPRASEAL®

LM 202 VP

SOPRASEAL LM 202 VP is a one-component liquid applied vapor-permeable air barrier membrane used in wall construction. SOPRASEAL LM 202 VP is a water-based, ultra low VOC liquid product composed of a modified rubber formulation. This non-flammable vapor permeable air barrier provides moisture protection behind wall claddings such as brick, siding, metal panels, EIFS, and stucco. Utilization of a slipsheet is required for stucco cladding.


INSTALLATION

To apply SOPRASEAL LM 202 VP mix the product until thoroughly blended. To apply SOPRASEAL LM 202 VP at temperatures below 40°F (4°C) but above 25°F (-4°C), blend with one quart container of SOPRASEAL LT Additive. Use a ¾" (19 mm) nap roller, paint brush or spray equipment to apply.

PRODUCT PROPERTIES

COLOR	Red-Brown
SOLIDS	74%
VOLUME	5 gal (19 L)

APPLICATION



LIQUID APPLIED



BRUSH



ROLLER

RELATED PRODUCTS

SOPRASEAL STICK 1100T
SOPRASOLIN HD
SOPRASEAL MESH

AIR & VAPOR BARRIERS
SOPRASEAL®



SOPRASEAL LM 202 VP

PRODUCT CODE

A501

Scan QR code with the SOPREMA toolbox app for more information.

