





Commercial Building Submittal Package-US



Submitted to:

Submitted by:

Date:

Job Reference:

Job Name:


Address:

Commercial Wall Insulation Products

Product Description	R-value	Thickness	L	W	Location
<p>CAVITYROCK® Exterior Cavity and Rainscreen Walls Semi-rigid, non-combustible stone wool insulation board designed for exterior cavity wall and rainscreen applications. Its high permeability enables it to maintain its R-value and its mineral fiber structure allows for effective drainage of water which penetrates the exterior cladding.</p> <p>Thicknesses of 1-2" are made of a mono-density structure that maintains a consistent density throughout the product.</p> <p>Thicknesses 2.5" and greater, utilizes dual-density technology to provide increased performance. The higher density outer layer provides a rigid outer surface for durability and enhanced strength, while the lower density inner layer allows for easier installation in the wall structure.</p>	4.3	1"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"	
			<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
	6.5	1.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"	
			<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
	8.6	2"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"	
			<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
	10.8	2.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"	
				<input type="checkbox"/> 24"	
	12.9	3"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"	
				<input type="checkbox"/> 24"	
				<input type="checkbox"/> 32"	
	15.1	3.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"	
				<input type="checkbox"/> 24"	
	17.2	4"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"	
<input type="checkbox"/> 24"					
19.4	4.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"		
			<input type="checkbox"/> 24"		
21.5	5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"		
			<input type="checkbox"/> 24"		
			<input type="checkbox"/> 32"		
25.8	6"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"		
			<input type="checkbox"/> 24"		
<p>COMFORTBOARD™ 110 Exterior Insulated Sheathing Rigid stone wool, non-structural insulated sheathing board used as continuous insulation in commercial applications.</p> <p>This product is thermally efficient, moisture resistant and vapor permeable. It takes the place of other external sheathing insulations to create high-performance wall assemblies that are effective against fire, moisture and thermal bridging while allowing for superior drying potential.</p>	4	1"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
			<input type="checkbox"/> 72"	<input type="checkbox"/> 48"	
	5	1.25"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
			<input type="checkbox"/> 72"	<input type="checkbox"/> 48"	
	8	2"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
			<input type="checkbox"/> 72"	<input type="checkbox"/> 48"	
	10	2.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
	12	3"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
			<input type="checkbox"/> 72"	<input type="checkbox"/> 48"	


Product Description	R-value	Thickness	L	W	Location
CURTAINROCK® 40 Curtain Wall Semi rigid, mineral wool insulation board designed for fire rated curtain wall applications.	8.6	□ 2"	□ 48"	□ 24"	
			□ 60"	□ 36"	
			□ 72"	□ 48"	
	12.9	□ 3"	□ 48"	□ 24"	
			□ 60"	□ 36"	
			□ 72"	□ 48"	
	15.1	□ 3.5"	□ 72"	□ 48"	
	17.2	□ 4"	□ 48"	□ 24"	
			□ 60"	□ 24"	
			□ 60"	□ 36"	
			□ 72"	□ 80"	
	21.5	□ 5"	□ 48"	□ 24"	
			□ 72"	□ 48"	
25.8	□ 6"	□ 48"	□ 24"		
CURTAINROCK® 80 Curtain Wall Rigid mineral wool insulation board designed for fire rated curtain wall applications.	4.3	□ 1"	□ 48"	□ 24"	
	8.6	□ 2"	□ 48"	□ 24"	
			□ 60"	□ 36"	
			□ 72"	□ 48"	
	12.9	□ 3"	□ 48"	□ 24"	
			□ 60"	□ 36"	
			□ 60"	□ 48"	
			□ 72"	□ 48"	
	17.2	□ 4"	□ 48"	□ 24"	
□ 60"			□ 36"		
□ 72"			□ 48"		

Notes:



Product Description	R-value	Thickness	L	W	Location
ROXUL SAFE™ Firestop and Head of Wall Applications Semi-rigid, mineral wool insulation approved for use in fire rated joints, through penetrations and perimeter fire containment systems.	N/A*	<input type="checkbox"/> 2"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
		<input type="checkbox"/> 3"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
		<input type="checkbox"/> 4"	<input type="checkbox"/> 48"	<input type="checkbox"/> 24"	
COMFORTBATT® SS Exterior Steel Stud Batt Stone wool batt insulation designed for thermal resistance in exterior steel stud wall applications. It's special flexible characteristic at the insulation edge ensures the expected R-value is achieved.	10	<input type="checkbox"/> 2.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16.25"	
	14	<input type="checkbox"/> 3.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16.25"	
				<input type="checkbox"/> 24.25"	
	22.5	<input type="checkbox"/> 6"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16.25"	
				<input type="checkbox"/> 24.25"	
	24	<input type="checkbox"/> 6"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16.25"	
				<input type="checkbox"/> 24.25"	

Notes:



Product Description	R-value	AFB evo™	Thickness	L	W	Location	
<p>AFB®</p> <p>Interior Steel Stud</p> <p>Stone wool batt insulation for steel stud interior wall and floor applications. AFB® (Acoustical Fire Batt) provides superior sound absorbency and fire protection for overall occupant comfort and safety.</p>	N/A*	<input type="checkbox"/>	<input type="checkbox"/> 1"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"		
					<input type="checkbox"/> 24"		
		<input type="checkbox"/>	<input type="checkbox"/> 1.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"		
					<input type="checkbox"/> 24"		
		<input type="checkbox"/>	<input type="checkbox"/> 2"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"		
					<input type="checkbox"/> 24"		
		<input type="checkbox"/>	<input type="checkbox"/> 2.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"		
					<input type="checkbox"/> 24"		
		<p>*AFB evo™</p> <p>Interior Steel Stud</p> <p>No added formaldehyde stone wool batt insulation for interior partitions in commercial constructions where superior fire resistance and acoustical performance is required. This product is UL validated to be Formaldehyde Free.</p> <p>* Please contact your ROCKWOOL Sales Representative for information regarding pricing and availability of this product.</p>	<input type="checkbox"/>	<input type="checkbox"/> 3"	<input type="checkbox"/> 48"	<input type="checkbox"/> 15"	
						<input type="checkbox"/> 16"	
						<input type="checkbox"/> 24"	
			<input type="checkbox"/>	<input type="checkbox"/> 3.5"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"	
				<input type="checkbox"/> 24"			
<input type="checkbox"/>	<input type="checkbox"/> 4"		<input type="checkbox"/> 48"	<input type="checkbox"/> 16"			
				<input type="checkbox"/> 24"			
<input type="checkbox"/>	<input type="checkbox"/> 5"		<input type="checkbox"/> 48"	<input type="checkbox"/> 16"			
			<input type="checkbox"/> 24"				
<input type="checkbox"/>	<input type="checkbox"/> 6"	<input type="checkbox"/> 48"	<input type="checkbox"/> 16"				
			<input type="checkbox"/> 24"				

Product	ASTM C612	ASTM C665	CAN/ULC S702	CAN/ULC S114	ASTM E84	ASTM C665 CORROSIVE	ASTM C1104
CAVITYROCK®	Type IVB		Type 1	NC	Complies	Pass	0.07%
COMFORTBOARD™ 110	Type IVB		Type 1	NC	Complies	Pass	0.28%
CURTAINROCK®	Type IVA			NC	Complies	Pass	0.01%
CURTAINROCK® 40	Type IVB			NC	Complies	Pass	0.01%
CURTAINROCK® 80	Type IVB			NC	Complies	Pass	0.04%
ROXUL SAFE™	Type IVA			NC	Complies	Pass	0.04%
COMFORTBATT® SS		Type 1		NC	Complies	Pass	
AFB® & AFB evo™		Type 1	Type 1	NC	Complies	Pass	

ROCKWOOL
8024 Esquesing Line
Milton, Ontario L9T 6W3
Tel: 1 800 265 6878
www.ROCKWOOL.com

Disclaimer: Technical information contained in this document is intended to be used as a general guideline only. For the most up-to-date technical information please consult the technical data sheets available on ROCKWOOL.com.

*R-value is not required for application. Please contact the ROCKWOOL Technical Innovations team at 1-800-265-6878 for more information.

CAVITYROCK®, CURTAINROCK®, COMFORTBATT®, and AFB®, are registered trademarks of the ROCKWOOL Group in USA and ROXUL Inc. in Canada. COMFORTBOARD™, ROXUL SAFE™, and AFB evo™ are trademarks of the ROCKWOOL Group in USA and ROXUL Inc. in Canada.