



e.poly



### Product Description

**Basic Use:** e.poly is a polyester fabric that is designed to reinforce membrane terminations, transitions, penetrations, seams, and general repair areas. Used in every E.Series assembly, e.poly is installed between two layers of e.roll or e.spray.

**Composition:** e.poly is a 100% polyester textile material composed of staple fibers hydraulically entangled.

### Benefits

- Excellent conformability and elongation
- Exceptional tear resistance and high tensile strength
- Open weave allows complete saturation and integration

### Limitations

- Not suitable for expansion joints or areas where movement is desired

### Technical Data

**Properties:** See physical properties table

**Coverages:** 6", 12" and 40" rolls cover 150, 300, and 1,080 square feet, respectively

**Specification Writer:** Contact EPRO before writing specifications on this product. E.Series system assemblies should be reviewed in order to meet project specific site conditions.

### Installation

**Preparation:** Please refer to manufacturer's specifications for substrate requirements. Application of e.poly should be done when weather conditions meet the requirement of e.roll or e.spray.

**Installation:** Please refer to manufacturer's specifications. Install specified thickness of e.roll or e.spray and immediately embed e.poly into the initial layer of e.roll or e.spray. Once firmly pressed into the uncured membrane, fully saturate with additional layer of e.roll or e.spray to the specified thickness.

### Availability and Packaging

Contact EPRO sales representative for local distributors or authorized applicators ([www.eproinc.com](http://www.eproinc.com)).

Roll: 6" x 300', 12" x 300', and 40" x 324' rolls are available

### Warranty

**Limited Warranty:** EPRO Services, Inc. believes to the best of its knowledge that performance tables are accurate and reliable. EPRO warrants this product to be free from defects. EPRO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. EPRO's liability shall be limited in all events to supplying sufficient product to retreat the specific areas to which defective product has been applied. EPRO shall have no other liability, including liability for incidental or resultant damages, whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of EPRO or its distributors.

### Equipment

No special equipment is needed.

### Technical Services and Information

Complete technical services and information are available by contacting EPRO at 800.882.1896 or [www.eproinc.com](http://www.eproinc.com).

This product was formally known as Polyester.



e.poly

### Typical Physical Properties

Physical Property	Test Method	Value
Weight.....		3 oz.
Bursting Strength .....	ASTM D3786.....	177 lbs.
Tensile Strength .....	ASTM D1682.....	57.1 psi
Tear Strength.....	ASTM D1117.....	16.1 lbs
Elongation .....	ASTM D1682.....	62.0%
Conformability .....		Excellent
Ease of saturation .....		Excellent

Dimensions: 6" x 300', 12" x 300', and 40" x 324' rolls are available

