



## RAINPROOF-40 & RAINPROOF-60 HIGH PERFORMANCE ROOF UNDERLAYMENT

A cold applied self-adhering SBS modified, rubberized asphalt sheet waterproofing underlayment reinforced with a strong non-woven polyester fabric. The membrane has a white reflective fabric topping. It is used as a complete waterproof roofing underlayment on new and retro-fit roofs under most roof coverings. Can be used at low slope areas: hip, ridge, valleys, rake edges, confined rake edges, around skylights and chimneys.

- 12 month exposure rating
- Fully self adhered roofing underlayment system
- 2½" zip strip release liner for ease of edge overlap adhesion
- Durable white reflective topping for added footing safety and heat reduction
- Seals around properly installed fasteners
- Can be installed horizontally or vertically (as code allows)
- Can be installed on roof pitches down to 2"/12"
- Florida Product Approval FL#17155
- Roll sizes available: Rainproof-40: 36" x 67', Rainproof-60: 36" x 50'
- High temperature: 250°F



## PROTECTO ROOF EDGE SEAL

A double-sided, internally reinforced peel and stick membrane designed to bond the roof covering edge to the roof. Prevents wind blow-offs and protects against the damaging effects of harsh weather. Typical applications include rake edges, ridge caps, eave edges and skylights.

- Double sided SBS modified adhesive
- Bonds the roof covering to the roof deck
- Seals around fasteners
- Lightweight
- All temperature adhesive allows for application in all climates
- Low profile 40 mil thickness will not telegraph through the roof covering
- Quick and easy to install
- Evaluation report IAPMO ER #390 and Florida Building Code FL17155
- Roll sizes available: 12" x 25' • High temperature: 250°F

