

SAFETY DATA SHEET



Issue Date 13-Aug-2015

Revision Date 10-Jan-2018

Version 1

1. IDENTIFICATION

Product identifier

Product Name PUMADEQ GRIP 40 - CLEAR

Other means of identification

Product Code HEPU862C

UN/ID no UN1866

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Industrial Coatings

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800

El Segundo, CA 90245-2716

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Company Phone Number 800-486-1278

Emergency Telephone US and Canada only (toll-free) : 3E Company - 1-866-519-4752 (access code 334832)
US/Canada, all other countries: 3E Company - +1-760-476-3962 (access code 334832)
Mexico (additional contact option): 3E Company - +52 55 41696225 (Code 334832)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Skin sensitization | Category 1 |
| Carcinogenicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Flammable liquids | Category 2 |

Label elements

Emergency Overview

Danger

Hazard statements

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

Suspected of causing cancer
May cause respiratory irritation
Highly flammable liquid and vapor



Appearance viscous

Physical state liquid

Odor Strong Aromatic

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ ventilating / lighting/ / equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable

Mixture

| Chemical Name | CAS No | Weight-% |
|--|-------------|----------|
| Resin-polymer Blend * | Proprietary | 40 - 70 |
| Methyl methacrylate * | 80-62-6 | 10 - 30 |
| 2-Ethylhexyl acrylate * | 103-11-7 | 10 - 30 |
| Titanium dioxide * | 13463-67-7 | 0 - 5 |
| Silica, amorphous, fumed, crystalline-free * | 112945-52-5 | 1 - 5 |
| Benzenamine, N,N,4-trimethyl- * | 99-97-8 | 0.1 - 1 |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

| | |
|---|---|
| General advice | Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician. |
| Eye contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. |
| Skin contact | Wash off immediately with soap and plenty of water. Wash contaminated clothing before reuse. If skin irritation persists, call a physician. |
| Inhalation | Remove to fresh air. If symptoms persist, call a physician. Artificial respiration and/or oxygen may be necessary. |
| Ingestion | Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person. |
| Self-protection of the first aider | Remove all sources of ignition. Use personal protective equipment as required. |

Most important symptoms and effects, both acute and delayed

| | |
|-----------------|---|
| Symptoms | May cause redness and tearing of the eyes. May cause skin irritation. Redness. Coughing and/ or wheezing. |
|-----------------|---|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|--|
| Note to physicians | May cause sensitization in susceptible persons. Treat symptomatically. |
|---------------------------|--|

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO₂, sand, earth, water spray or regular foam.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

In the event of fire and/or explosion do not breathe fumes. May cause sensitization in susceptible persons. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Burning produces heavy smoke.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use personal protective equipment as required. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers.

Incompatible materials Strong oxidizing agents. Strong acids. Strong bases. Amines. Halogens.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--------------------------------|------------------------------|--|--|
| Methyl methacrylate 80-62-6 | STEL: 100 ppm TWA: 50 ppm | TWA: 100 ppm TWA: 410 mg/m ³ | IDLH: 1000 ppm TWA: 100 ppm TWA: 410 mg/m ³ |
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust | IDLH: 5000 mg/m ³ |

NIOSH IDLH *Immediately Dangerous to Life or Health*

Appropriate engineering controls

Engineering Controls Minimize exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

| | |
|---------------------------------------|---|
| Skin and body protection | Wear protective gloves and protective clothing. |
| Respiratory protection | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. |
| General Hygiene Considerations | When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|---------------------------------------|--------------------------|-------------------------|-----------------|
| Physical state | liquid | Odor | Strong Aromatic |
| Appearance | viscous | Odor threshold | 0.34 ppm |
| Color | pigmented | | |
| Property | Values | Remarks • Method | |
| pH | No information available | | |
| Melting point / freezing point | -18 °C / 0 °F | | |
| Boiling point / boiling range | 101 °C / 213 °F | | |
| Flash point | 12 °C / 53 °F | Tag Closed Cup | |
| Evaporation rate | 3.1 (nBuOAc = 1) | | |
| Flammability (solid, gas) | No information available | | |
| Flammability Limit in Air | | | |
| Upper flammability limit: | 12.5% | | |
| Lower flammability limit: | 2.1% | | |
| Vapor pressure | 4.7 | @ 20 °C | |
| Vapor density | No information available | | |
| Relative density | 1.36 | | |
| Water solubility | Insoluble in water | | |
| Solubility in other solvents | No information available | | |
| Partition coefficient | No information available | | |
| Autoignition temperature | No information available | | |
| Decomposition temperature | >250 C | | |
| Kinematic viscosity | No information available | | |
| Dynamic viscosity | No information available | | |
| Explosive properties | Not an explosive | | |
| Oxidizing properties | Not applicable | | |

Other Information

| | |
|-------------------------|--------------------------|
| Softening point | No information available |
| Molecular weight | No information available |
| VOC Content (%) | No information available |
| Density | No information available |
| Bulk density | No information available |

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Amines. Halogens.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

| | |
|---------------------|---|
| Inhalation | May cause irritation. |
| Eye contact | Irritating to eyes. |
| Skin contact | Irritating to skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. |
| Ingestion | Based on available data, the classification criteria are not met. |

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|---|-------------------------|--------------------------------------|
| Methyl methacrylate 80-62-6 | = 7900 mg/kg (Rat) = 7872 mg/kg (Rat) | > 5 g/kg (Rabbit) | = 4632 ppm (Rat) 4 h |
| 2-Ethylhexyl acrylate 103-11-7 | = 4435 mg/kg (Rat) | = 7522 mg/kg (Rabbit) | - |
| Titanium dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| Silica, amorphous, fumed, crystalline-free 112945-52-5 | = 3160 mg/kg (Rat) | - | - |
| Benzenamine, N,N,4-trimethyl- 99-97-8 | = 1650 mg/kg (Rat) | > 2000 mg/kg (Rat) | = 1400 mg/m ³ (Rat) 4 h |

Information on toxicological effects

Symptoms May cause an allergic skin reaction. May cause redness and tearing of the eyes. May cause skin irritation. Redness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Based on available data, the classification criteria are not met.
Germ cell mutagenicity Based on available data, the classification criteria are not met.
Carcinogenicity This product contains titanium dioxide which is classified as a possible carcinogen when present as respirable dust. This is not relevant for this product since it is a liquid. The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|--|-------|----------|-----|------|
| Resin-polymer Blend | - | Group 3 | - | - |
| Methyl methacrylate 80-62-6 | - | Group 3 | - | - |
| 2-Ethylhexyl acrylate 103-11-7 | - | Group 3 | - | - |
| Titanium dioxide 13463-67-7 | - | Group 2B | - | X |
| Silica, amorphous, fumed, crystalline-free 112945-52-5 | - | Group 3 | - | - |
| Benzenamine, N,N,4-trimethyl- 99-97-8 | - | Group 2B | - | - |

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity Based on available data, the classification criteria are not met.

| | |
|---------------------------------|---|
| STOT - single exposure | May cause disorder and damage to the. Respiratory system. Eyes. Skin. |
| STOT - repeated exposure | Based on available data, the classification criteria are not met. |
| Chronic toxicity | Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. |
| Target Organ Effects | Eyes, Respiratory system, Skin, lungs. |
| Aspiration hazard | Based on available data, the classification criteria are not met. |

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

| | |
|----------------------------------|----------------|
| ATEmix (oral) | 5,995.00 mg/kg |
| ATEmix (dermal) | 6,544.00 mg/kg |
| ATEmix (inhalation-vapor) | 9,079.00 mg/l |

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Harmful to aquatic life with long lasting effects

64.8 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|--|--|--|-------------------------------------|
| Methyl methacrylate 80-62-6 | 170: 96 h Pseudokirchneriella subcapitata mg/L EC50 | 243 - 275: 96 h Pimephales promelas mg/L LC50 flow-through 125.5 - 190.7: 96 h Pimephales promelas mg/L LC50 static 153.9 - 341.8: 96 h Lepomis macrochirus mg/L LC50 static 79: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 79: 96 h Oncorhynchus mykiss mg/L LC50 static 170 - 206: 96 h Lepomis macrochirus mg/L LC50 flow-through 326.4 - 426.9: 96 h Poecilia reticulata mg/L LC50 static | 69: 48 h Daphnia magna mg/L EC50 |
| 2-Ethylhexyl acrylate 103-11-7 | 44: 72 h Desmodesmus subspicatus mg/L EC50 47: 96 h Desmodesmus subspicatus mg/L EC50 | 23: 48 h Leuciscus idus melanotus mg/L LC50 | 17.45: 48 h Daphnia magna mg/L EC50 |
| Benzenamine, N,N,4-trimethyl- 99-97-8 | - | 42 - 50.5: 96 h Pimephales promelas mg/L LC50 flow-through | - |

Persistence and degradability

No information available.

Bioaccumulation

| Chemical Name | Partition coefficient |
|--|-----------------------|
| Methyl methacrylate 80-62-6 | 0.7 |
| 2-Ethylhexyl acrylate 103-11-7 | 4.64 |
| Benzenamine, N,N,4-trimethyl- 99-97-8 | 2.81 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001 U162

| Chemical Name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|--------------------------------|------|-----------------------------------|------------------------|------------------------|
| Methyl methacrylate 80-62-6 | U162 | Included in waste stream: F039 | - | U162 |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|--------------------------------|-----------------------------------|
| Methyl methacrylate 80-62-6 | Toxic Ignitable |

14. TRANSPORT INFORMATION

DOT

UN/ID no UN1866
 Proper shipping name Resin solution
 Hazard Class 3
 Packing Group II
 Special Provisions 149, B52, IB2, T4, TP1, TP8
 Description UN1866, Resin solution, 3, II
 Emergency Response Guide Number 127

TDG

UN/ID no UN1866
 Proper shipping name Resin solution
 Hazard Class 3
 Packing Group II
 Description UN1866, Resin solution, 3, II

IATA

UN/ID no UN1866
 Proper shipping name Resin solution
 Hazard Class 3
 Packing Group II
 ERG Code 3L
 Special Provisions A3
 Description UN1866, Resin solution, 3, II

IMDG

UN/ID no UN1866
 Proper shipping name Resin solution
 Hazard Class 3
 Packing Group II
 EmS-No F-E, S-E
 Description UN1866, Resin solution, 3, II, (12°C c.c.)

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDL Complies
 EINECS/ELINCS Complies
 IECSC Complies
 KECL Complies
 PICCS Complies
 AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % |
|-------------------------------|-------------------------------|
| Methyl methacrylate - 80-62-6 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute health hazard | Yes |
| Chronic Health Hazard | No |
| Fire hazard | Yes |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|--------------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Methyl methacrylate 80-62-6 | 1000 lb | - | - | X |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|--------------------------------|--------------------------|----------------|---|
| Methyl methacrylate 80-62-6 | 1000 lb | - | RQ 1000 lb final RQ RQ 454 kg final RQ |

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 |
|---|---------------------------|
| Titanium dioxide - 13463-67-7 | Carcinogen |
| Benzenamine, N,N,4-trimethyl- - 99-97-8 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|-----------------------------------|------------|---------------|--------------|
| Methyl methacrylate 80-62-6 | X | X | X |
| 2-Ethylhexyl acrylate 103-11-7 | X | X | X |
| Titanium dioxide 13463-67-7 | X | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

| | | | | |
|-------------|------------------|----------------|--------------------|------------------------------------|
| <u>NFPA</u> | Health hazards 2 | Flammability 3 | Instability 0 | Physical and Chemical Properties - |
| <u>HMIS</u> | Health hazards 2 | Flammability 3 | Physical hazards 0 | Personal protection X |

Issue Date 13-Aug-2015

Revision Date 10-Jan-2018

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet