



PlaniLevel™ 500

Quick-Setting, High-Compressive-Strength Underlayment and Topping

PlaniLevel 500 is a calcium-aluminate-based, quick-setting, self-drying, self-leveling material. It is specially formulated for the resurfacing and construction of interior horizontal surfaces as a high-compressive-strength underlayment with maximum resistance to the wheel tracking and indentations experienced in softer underlayments. *PlaniLevel 500* is suitable for use as a commercial wear topping in warehouse and alternate industrial applications where an exceptionally flat and smooth concrete surface is desired.

	Product Code	Packaging
U.S.	7494523	Bag: 50 lbs. (22.7 kg)



PlaniLevel™ 560

High-Compressive-Strength, Open-Environment-Rated, Self-Leveling Underlayment

PlaniLevel 560 is an advanced hydraulic-cement-based, self-leveling compound designed for fast-track underlayment applications. It is especially formulated for leveling interior, horizontal concrete surfaces where environmental controls are not operational or the building is not enclosed. When combined with an epoxy moisture barrier and an epoxy primer with sand broadcast, *PlaniLevel 560* creates a leveling system that improves construction efficiency and eliminates the wait times before floor coverings can be installed.

	Product Code	Packaging
U.S.	0348923	Bag: 50 lbs. (22.7 kg)



Primer L™

Advanced-Technology, Acrylic Latex Primer for Concrete

Primer L is a concentrated, solvent-free acrylic primer used before the installation of underlayments. It is green for easy identification. *Primer L* improves the bond between a properly prepared and profiled concrete substrate, and a self-leveling underlayment. *Primer L* can also be used as a primer for gypsum-based underlayments and patches.

	Product Code	Packaging
U.S.	36068000 36053000	Pail: 5 U.S. gals. (18.9 L) Pail: 1 U.S. gal. (3.79 L)