



ROOFING & SIDING

Roofing and Siding

Roofing Nail

For applying roofing asphalt shingles, insulation board, and felt-to-wood substrates. Large head and heavier shank gauge provide greater holding power. Electrogalvanized nail also appropriate for use with vinyl siding. Made to conform to ASTM F1667.



Roofing Nail		Electrogalvanized Ring Shank		
Size	Gauge	Head Size	Approx. Count Per Pound	SKU
7/8"	11	7/16"	306	78EGRSRFG
1"	11	7/16"	272	1EGRSRFG
1-1/4"	11	7/16"	218	114EGRSRFG
1-1/2"	11	7/16"	186	112EGRSRFG

Roofing Nail Electrogalvanized Smooth or Barbed Shank

Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1/2"	11	7/16"	528	12EGRFG
5/8"	11	7/16"	436	58EGRFG
3/4"	11	7/16"	348	34EGRFG
7/8"	11	7/16"	306	78EGRFG
1"	11	7/16"	272	1EGRFG
1-1/4"	11	7/16"	218	114EGRFG
1-1/2"	11	7/16"	186	112EGRFG
1-3/4"	11	7/16"	152	134EGRFG
2"	11	7/16"	144	2EGRFG
2-1/2"	11	7/16"	114	212EGRFG
3"	11	7/16"	92	3EGRFG
3-1/2"	11	7/16"	89	312EGRFG
4"	11	7/16"	78	4EGRFG

Roofing Nail Hot Dipped Galvanized Ring Shank

Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1"	11	7/16"	255	1HGATRFG
1-1/4"	11	7/16"	210	114HGATRFG
1-1/2"	11	7/16"	180	112HGATRFG
1-3/4"	11	7/16"	150	134HGATRFG
2"	11	7/16"	138	2HGATRFG
2-1/2"	11	7/16"	108	212HGATRFG
3"	11	7/16"	90	3HGATRFG

Tin Cap

Used with fasteners to create a larger surface area for holding materials in place.



Tin Cap Round Metal Cap

Diameter	Approx. Count Per Pound*	SKU
1-5/8"	250	TINSM
2"	150	TINMD

* Based on approximate metal cap thickness of .007".

Roofing Nail Hot Dipped Galvanized Smooth or Barbed Shank

Size	Gauge	Head Size	Approx. Count Per Pound	SKU
1/2"	11	7/16"	510	12HGRFG
5/8"	11	7/16"	417	58HGRFG
3/4"	11	7/16"	315	34HGRFG
7/8"	11	7/16"	280	78HGRFG
1"	11	7/16"	255	1HGRFG
1-1/4"	11	7/16"	210	114HGRFG
1-1/2"	11	7/16"	180	112HGRFG
1-3/4"	11	7/16"	150	134HGRFG
2"	11	7/16"	138	2HGRFG
2-1/2"	11	7/16"	108	212HGRFG
3"	11	7/16"	90	3HGRFG
3-1/2"	11	7/16"	87	312HGRFG
4"	11	7/16"	77	4HGRFG

Grip-Cap® Plastic Cap Nail

For anchoring housewrap, sheathing, and felt. Wide head and ringed shank for greater holding power.



Grip-Cap Nail Electrogalvanized Ring Shank With Round Plastic Cap

Size	Gauge	Head Size	Approx. Count Per Pound	SKU
3/4"	12	1"	266	GC34
7/8"	12	1"	275	GC78
1"	12	1"	250	GC1
1-1/4"	12	1"	212	GC114
1-1/2"	12	1"	185	GC112
1-3/4"	12	1"	168	GC134
2"	12	1"	153	GC2
2-1/2"	11	1"	133	GC212
3"	11	1"	117	GC3

* All Grip-Rite hot dipped galvanized fasteners meet ASTM A-153 requirements and can be used with treated lumber.