
# **ROLLERS** - MISC

# **Roller Gauge End Caps**

The thick film roller gauge works for urethane cement, cement overlays, epoxies, anti-skids, and vapor barriers. Spread, gauge, and back roll; snaps on ends of roller in seconds; precise gauging, no guessing, no waste.

Item No. Description

	48182	Roller Gauge End Caps, Low Mil 6-pk, Yellow, Approx 4 mils
	48183	Roller Gauge End Caps, Med Mil 6-pk, Red, Approx 12 mils
	48184	Roller Gauge End Caps, High Mil 6-pk, Blue, Approx 22 mils
	48185	Roller Gauge End Caps, Thick Film 6-pk, Gray, 1/2" Depth
	48186	Roller Gauge End Caps, Thick Film 6-pk, Black, 1/4" Depth



# **End Caps**



Item No.	Description
SA30005	1/4" End Caps (Set of 2)
SA30042	1/4" End Caps (Box of 24)
SA30045	3/8" End Caps (Set of 2)
SA30048	3/8" End Caps (Bag of 24)

# **Roller Frames**

The **48400** has a quick release spring that prevents roller slippage, smooth bearings for reliable applications, a polypropylene grip and a threaded handle adapter. It is one of the best universal roller frames on the market. The **48403** is a traditional "paint roller" style frame and the handle contains a threaded handle adapter. The **48410** adjusts to hold all roller covers from 9" to 18" wide. It has a rigid and durable steel frame with a threaded handle adapter, yet weighs less than one pound. The **48418** is a lightweight, yet the durable polypropylene 18" non-adjustable frame can accommodate any of the 18" roller covers we offer. This frame offers a threaded handle adapter and the fiber-glass-reinforced nylon legs are replaceable.

Item No. Description

48400	9" Wooster® Sherlock® Frame (R017)
48403	9" Wooster® Magikage® Ninety Frame (R016)
48540	9" Wooster® Acme™ Heavy-Duty Roller Frame (F0010)
48410	Wooster® Sherlock Wide Boy™ 18" Frame (BR036)
48418	Wooster® Big Ben® 18" Frame (BR045)
SA30006	Replacement Nylon Legs for 48418 - Set of 2 (R085)





## Heavy-Duty Fixed Width Aluminum Frames EXCLUSIVE

These are the most durable frames on the market. They are available in widths of 9", 18", 24" and 36" and can be used with any of our roller covers and nylon and metal tined rollers. The frames can be ordered with either a threaded handle adapter or with a fixed handle assembly. These heavy-duty solid aluminum frames are solvent-resistant and can be easily cleaned after each use. Special 3/8" post hole end caps are available for use with these exclusive frames when using 9" - 36" roller covers and spiked rollers. These polypropylene end caps are used to adapt the frames to any standard 1-1/2" roller. They are sold in quantities of 1 pair or a bag of 24 (see top of page).



_				1 A		- 1	. 1		
-1	ra	m	Δ	١٨	/ı	N	t	h	

Description	Item No. 9"	Item No. 18"	Item No. 24"	Item No. 36"
Heavy-Duty Aluminum Frame with Threaded Handle Adapter	60108	60110	60113	60115
Heavy-Duty Aluminum Frame with 66" Powder-Coated Aluminum Handle	60109	60112	60114	60116

# SPIKEDR

- 4 Tine Lengths Available: 1/2", 13/16", 1-1/2" & 2"
- Abrasion-Resistant Nylon Tines Provide Superior Tool Life
- 3/8" End-Caps Allow Use with Midwest Rake® 9" Radial Frame, Medium-Duty Frame or Heavy-Duty Aluminum Frame
- Designed for Maximum Effectiveness in Releasing Entrapped Air and Promoting Self-Leveling of Coatings
- Engineered to Improve the Application Characteristics of Resurfacing (Over/Underlayment) Products

## **Choose Your Frame:**

## MEDIUM-DUTY FRAME



59030	18" Medium-Duty Aluminum Frame
59050	24" Medium-Duty Aluminum Frame
59070	36" Medium-Duty Aluminum Frame

## **REPLACEMENT PARTS**

59089	Hardware Bag for 18" & 24" & 36" Medium-Duty Aluminum Frames
59091	Threaded Handle Adapter & Screw for Medium-Duty Frame

**Choose Your Roller:** 

## **RADIAL FRAME**



59010 9" Radial Frame

## REPLACEMENT PARTS

Hardware Bag for 9" Radial Frame (Washers / Spring Clip)







- All frames have a threaded handle adapter.
- Both nylon tined & metal tined rollers come with 3/8" end-caps allowing them to fit any of the frames listed above.
- 2" NYLON SPIKED ROLLERS CAN ONLY BE USED WITH THE 9" RADIAL FRAME OR THE MEDIUM-DUTY FRAMES.


## **HEAVY-DUTY FRAME**



	60108	9" Heavy-Duty Aluminum Frame with Threaded Handle Adapter
	60109	9" Heavy-Duty Aluminum Frame with 66" Powder Coated Aluminum Handle
	60110	18" Heavy-Duty Aluminum Frame with Threaded Handle Adapter
	60112	18" Heavy-Duty Aluminum Frame with 66" Powder Coated Aluminum Handle
	60113	24" Heavy-Duty Aluminum Frame with Threaded Handle Adapter
	60114	24" Heavy-Duty Aluminum Frame with 66" Powder Coated Aluminum Handle
	60115	36" Heavy-Duty Aluminum Frame with Threaded Handle Adapter
	60116	36" Heavy-Duty Aluminum Frame with 66" Powder Coated Aluminum Handle

## REPLACEMENT PARTS

SA30035	Hardware Bag, Axles for Heavy-Duty Frame
SA30010	THA Kit (Threaded Handle Adapter, Gusset Braces & Hardware)



Ideal for Resinous Coatings (Epoxy & Urethane)

13/16" SUPER SHARP	59012	9" Spiked Roller, 13/16" Supersharp Tines
(32 TINES)	59032	18" Spiked Roller, 13/16" Supersharp Tines
	59052	24" Spiked Roller, 13/16" Supersharp Tines
	59072	36" Spiked Roller, 13/16" Supersharp Tines

Ideal for Cementitious and Gypsum Resurfacing Materials

1-1/2" SUPER SHARP (32 TINES)	
(32 TINES)	

	Item No. Description				
)	59013	9" Spiked Roller, 1-1/2" Supersharp Tines			
	59033	18" Spiked Roller, 1-1/2" Supersharp Tines			
	59053	24" Spiked Roller, 1-1/2" Supersharp Tines			
	59073	36" Spiked Roller, 1-1/2" Supersharp Tines			

Ideal for Cementitious and Gypsum Resurfacing Materials

2" SUPER SHARP	59014	9" Spiked Roller, 2" Supersharp Tines
(32 TINES)	59034	18" Spiked Roller, 2" Supersharp Tines
	59054	24" Spiked Roller, 2" Supersharp Tines
	59074	36" Spiked Roller, 2" Supersharp Tines

Ideal for Cementitious and Gypsum Resurfacing Materials 2" Nylon Spiked Rollers Can Only Be Used with the 9" Radial Frame or the Medium-Duty Frames

# SPIKEDRELLER

- 2 Tine Lengths Available: 1/2" & 1-1/4" Nominal 1-1/2" Standard Size Core Dense Configuration of Tin-Plated Steel Tines
  - Designed for Maximum Effectiveness in Releasing Entrapped Air & Promoting Self-Leveling of Coatings
  - Engineered to Improve the Application Characteristics of Resurfacing (Over/Underlayment) Products
- 3/8" End-Caps Allow Use with Midwest Rake® 9" Radial Frame, Medium-Duty Frame or Heavy-Duty Aluminum Frame

## **RADIAL FRAME**



59010	∣9" Radial	Frame

### REPLACEMENT PARTS

59019 Hardware Bag for 9" Radial Frame (Washers / Spring Clip)

## Choose Your Frame:

## **MEDIUM-DUTY FRAME**



59030	18" Medium-Duty Aluminum Frame		
59050	24" Medium-Duty Aluminum Frame		
59070	36" Medium-Duty Aluminum Frame		

## **REPLACEMENT PARTS**

59089	Hardware Bag for 18" & 24" & 36" Medium-Duty Aluminum Frames	
59091	Threaded Handle Adapter & Screw for Medium-Duty Frame	

## **HEAVY-DUTY FRAME**



	60108	9" Heavy-Duty Aluminum Frame with Threaded Handle Adapter
60109 9" Heavy-Duty A		9" Heavy-Duty Aluminum Frame with 66" Powder Coated Aluminum Handle
	60110	18" Heavy-Duty Aluminum Frame with Threaded Handle Adapter
	60112	18" Heavy-Duty Aluminum Frame with 66" Powder Coated Aluminum Handle
	60113	24" Heavy-Duty Aluminum Frame with Threaded Handle Adapter
	60114	24" Heavy-Duty Aluminum Frame with 66" Powder Coated Aluminum Handle
	60115	36" Heavy-Duty Aluminum Frame with Threaded Handle Adapter
	60116	36" Heavy-Duty Aluminum Frame with 66" Powder Coated Aluminum Handle

## **REPLACEMENT PARTS**

SA30035	Hardware Bag, Axles for Heavy-Duty Frame	
SA30010	THA Kit (Threaded Handle Adapter, Gusset Braces & Hardware)	

## **Choose Your Roller:**



1-1/4" SUPER SHARP	48093	9" Metal Tined Roller, 1-1/4" Tines
	48094	18" Metal Tined Roller, 1-1/4" Tines
	48095	24" Metal Tined Roller, 1-1/4" Tines

Item No. Description

# **Metal-Tined Spiked Roller Covers**

Midwest Rake® spiked rollers are premium quality and engineered to provide maximum performance to minimize out-gassing and promote leveling characteristics of resinous coatings as well as resurfacing materials of all types. A more dense steel tine configuration, modeled after the traditional "porcupine" roller. These rollers have a 1-1/2" aluminum core. Metal-tined spiked rollers work remarkably well with cementitious and gypsum based overlays to promote self-leveling and reduce out-gassing. All spiked rollers come with 3/8" black end-caps.

