

For 50 years, we've been the innovators in subfloor prep. With our new line of products for commercial projects, we're offering more ways than ever to help you get the job done right. Every time.

The leaders. The innovators. The name you can trust. [maxxon.com](http://maxxon.com)

## UNDERLAYMENTS & PATCH PRODUCTS



### MAXXON<sup>®</sup> COMMERCIAL Level EZ™

#### PRODUCT DESCRIPTION

A low-prep, hydraulic cement-based underlayment that provides a strong, durable, smooth surface for floor coverings. Can be poured or pumped. UL Fire Rated.

#### INFO

Installation Depth: Featheredge to 2"  
Compressive Strength: Minimum 5,000 psi  
Bag Size: 50 lb  
Coverage at 1/4": 21 ft<sup>2</sup>



### MAXXON<sup>®</sup> COMMERCIAL EZ Crete™

#### PRODUCT DESCRIPTION

A low-prep, cost-effective cementitious underlayment for leveling, smoothing and repairing interior gypsum and concrete subfloors. UL Fire Rated.

#### INFO

Installation Depth: 3/8" to 3"  
Compressive Strength: Minimum 3,500 psi  
Bag Size: 50 lb  
Coverage at 3/8": 16 ft<sup>2</sup>



### MAXXON<sup>®</sup> COMMERCIAL Low Density Fill™

#### PRODUCT DESCRIPTION

An ultra-lightweight proprietary cement with lightweight aggregate that is easy to place and can be sloped with no thickness limitation. Ready to be capped with a Maxxon underlayment the next day.

#### INFO

Density: 28-32 pcf  
Bag Size: 40 lb  
Coverage at 2": 9 ft<sup>2</sup>



### MAXXON<sup>®</sup> COMMERCIAL Gyp-Fix EZ Patch

#### PRODUCT DESCRIPTION

A high-strength, quick-drying, patch or skim coat over interior gypsum, concrete, and all subfloors. Flooring-ready in as little as 40 minutes. UL Fire Rated.

#### INFO

Compressive Strength: Minimum 4,000 psi  
Bag Size: 25 lb  
Coverage at 1/8": 31 ft<sup>2</sup>

## PRIMERS



### MAXXON<sup>®</sup> COMMERCIAL Fortify™

#### PRODUCT DESCRIPTION

A high-performance primer to consolidate soft or dusty gypsum underlayments, strengthening and readying the surface for a Maxxon underlayment.

#### INFO

Packaging: 5 gal bucket  
Total Coverage: 400 ft<sup>2</sup> as consolidator



### MAXXON<sup>®</sup> COMMERCIAL Multi-Use Acrylic

#### PRODUCT DESCRIPTION

Primes concrete, gypsum, and wood subfloor before application of a Maxxon underlayment.

#### INFO

Packaging: 5 gal bucket  
Total Coverage: Up to 2,100 ft<sup>2</sup>  
*Varies by application*



### MAXXON<sup>®</sup> COMMERCIAL Gypsum Overspray

#### PRODUCT DESCRIPTION

Seals Maxxon underlayments before the installation of glue down finished floor goods.

#### INFO

Packaging: 5 gal bucket  
Total Coverage: 10,500 ft<sup>2</sup>

## MOISTURE MITIGATION



### **MAXXON** COMMERCIAL **MVP One Primer**

#### PRODUCT DESCRIPTION

Ready-to-use, single-component moisture mitigation primer. Two-coat application dries in 60 minutes per coat. Meets ASTM E96 and mitigates up to 100% RH, 25 lbs MVER, and pH of 14.

#### INFO

Packaging: 5 gal bucket  
Total Coverage: 1,250 ft<sup>2</sup>



### **MAXXON** COMMERCIAL **MVP Two-Part Epoxy**

#### PRODUCT DESCRIPTION

Two-part epoxy moisture barrier. Meets ASTM E96 and mitigates up to 100% RH, 25 lbs MVER, and pH of 14.

#### INFO

Packaging: 2.5 gal kit  
Total Coverage: 312 ft<sup>2</sup>



### **MAXXON** COMMERCIAL **MVP SMART Primer**

#### PRODUCT DESCRIPTION

A spray-applied curing agent and moisture barrier for concrete. Used as part of the Maxxon SMART System to expedite new concrete construction.

#### INFO

Dry Time: 30min – 2 hours  
Coverage: 175 ft<sup>2</sup>/gal  
Packaging: 4 gal bucket

## SOUND CONTROL



### **MAXXON** COMMERCIAL **Acusti-Top**

#### PRODUCT DESCRIPTION

A topical sound control mat designed for use over concrete, existing gypsum or lightweight concrete. Code compliant sound control at <1/16". Loose lay or glue down.

#### INFO

Roll coverage: 708 ft<sup>2</sup>  
Weight: 45 lbs



### **MAXXON** COMMERCIAL **Acusti-Top Adhesive**

#### PRODUCT DESCRIPTION

Pressure sensitive adhesive used to bond Acusti-Top<sup>®</sup> sound mat to concrete or gypsum subfloors.

#### INFO

Packaging: 5 gal bucket  
Total Coverage: 1,250 ft<sup>2</sup>

## SPECIALTY



### **MAXXON** COMMERCIAL **Profile**

#### PRODUCT DESCRIPTION

Concrete cleaner and profiler designed to purge contaminants from concrete surface, while creating a CSP of 1-4 with no shotblasting. Biodegradable, clean with water.

#### INFO

Dwell Time: Approximately 2 hours to CSP 2  
Coverage: 225-250 ft<sup>2</sup>/gal (5.5-6.1 m<sup>2</sup>/L) or  
900-1,000 ft<sup>2</sup> (84-93 m<sup>2</sup>/bucket)  
Packaging: 4 gal. (15.1 L) bucket



### **MAXXON** COMMERCIAL **Isolate**

#### PRODUCT DESCRIPTION

A two-part, water-based epoxy that isolates chemically-abated slabs, asbestos-containing material, and other contaminants in concrete slabs. Also prevents the migration of moisture vapor from adversely affecting floor coverings.

#### INFO

Dry Time: 4-6 hours  
Coverage: 150 ft<sup>2</sup>/gal (3.7 m<sup>2</sup>/L) or  
600 ft<sup>2</sup> (55.7 m<sup>2</sup>)/kit  
Packaging: 4 gal. (15.1 L) bucket



### **MAXXON** COMMERCIAL **ASR Barrier**

#### PRODUCT DESCRIPTION

A spray applied surface treatment that prevents efflorescence formation and osmotic blistering in slabs with Alkali Silica Reaction (ASR).

#### INFO

Dry Time: 30min – 2 hours  
Coverage: 225 ft<sup>2</sup>/gal  
Packaging: 4 gal bucket