

# ELASTOCOL<sup>®</sup> STICK



APPLICATIONS

ROOFING

PRODUCT DATA SHEET PD10134-Rev. 220202

## DESCRIPTION:

**ELASTOCOL Stick** is an SBS polymer based primer for use in approved multi-ply membrane and flashing assemblies. ELASTOCOL Stick is comprised of a proprietary blend of SBS polymers, solvents and additives used to increase adhesion when using self-adhered SBS membranes. ELASTOCOL Stick may be applied to gypsum, masonry, metal, wood and SOPREMA mineral aggregate surfaced membranes.

## STORAGE:

Store in pail and maintain in an upright position to prevent damage. Store in a clean dry location and cover as necessary to protect pails from environmental damage such as extreme cold, heat, or moisture. Monitor varying environmental conditions during storage, handling and application of ELASTOCOL Stick.

## APPLICATION:

Mix prior to application. **ELASTOCOL Stick** is applied to the approved area via brush, roller or spray equipment. ELASTOCOL Stick is applied at a rate of 0.7 to 1 gallon per 100 square feet over non porous substrates. Refer to the SOPREMA SBS Roofing Manual for additional application guidelines.

### QUICK FACTS

CONTAINER (gal)	COVERAGE RATE (gal/100ft <sup>2</sup> )
5.0 (18.9 L)	0.7-1.0 (0.3 - 0.4 L/m <sup>2</sup> )

### PRODUCT INFORMATION

Description	Proprietary blend of synthetic polymers, solvents
Installation	Brush or roller
Packaging	5 gallon (18.9 L) pail
Color	Copper/Green



FLORIDA BUILDING CODE

MIAMI-DADE COUNTY  
APPROVED

