

Waterproofing Membranes and Accessories

Product Name	Description	Packaging	Coverage Rate
CCW Waterproofing Membranes			
CCW-500	Single Component Hot Fluid Applied Waterproofing Membrane, for horizontal and vertical applications	45-lb. blocks, one block per carton, 64 cartons per pallet	215 mils - 1.52 lbs/sq. ft. or 7.46 sq. ft./gal 125 mils - 0.89 lbs./sq. ft. or 12.83 sq. ft./gal 90 mils - 0.64 lbs/sq. ft. or 17.83 sq. ft./gal
CCW Vapor-Lock	Utilizes CCW 711-90 sheet membrane as a preformed first course on difficult-to-waterproof substrates such as lightweight concrete and wood. Consists of CCW 711-90 sheet membrane and 125-mils of CCW 500	CCW 500: 45-lb. blocks, one block per carton, 64 cartons per pallet CCW 711-90: 12" x 45' roll 18" x 45' roll 24" x 45' roll 36" x 45' roll	215 mils - 1.52 lbs/sq. ft. or 7.46 sq. ft./gal 125 mils - 0.89 lbs./sq. ft. or 12.83 sq. ft./gal 90 mils - 0.64 lbs/sq. ft. or 17.83 sq. ft./gal 45 sq. ft. roll 67.5 sq. ft. roll 90 sq. ft. roll 135 sq. ft. roll
CCW Miraseal	Single Component, solvent free, cold-fluid applied waterproofing membrane for horizontal and vertical applications	5 gal pails	60 mils - 26 sq. ft./ gallon 120 mils - 13 sq.ft./gallon
CCW 525	Single Component, elastomeric modified polyurethane waterproofing membrane for horizontal and vertical applications	5 gallon pails 55 gallon drums	60 mils - 22 sq. ft./gallon 120 mils - 11 sq. ft./gallon
CCW MiraDRI 860/861	CCW MiraDRI 860 - Self-Adhering sheet membrane, 40 degrees and rising CCW MiraDRI 861 - Self-Adhering sheet waterproofing, 20-60 degrees Fahrenheit; horizontal and vertical applications	36" x 67' roll (200 sq. ft.)	200 sq. ft. roll