

Weeped Starter Track

One-piece support starter track designed with weep holes and an extended drip leg to move moisture away from opening headers in Exterior Insulation Finish Systems (EIFS).

Includes the Keylock™ Splice for connecting multiple sections and to assist in their alignment. Caulk all intersections, butt joints, ends, and corners at the time of installation.

Product Data & Ordering Information:

Product Code	Finish Thickness	Insulation Thickness (A)	Back Flange (B)	Perforated Flange (C)	PCS/Box
DCBSV-50-332	3/32"	1/2"	2-1/2"	3/4"	20
DCBSV-75-332	3/32"	3/4"	2-1/2"	3/4"	20
DCBSV-100-332	3/32"	1"	2-1/2"	3/4"	15
DCBSV-150-332	3/32"	1-1/2"	2-1/2"	3/4"	10
DCBSV-200-332	3/32"	2"	2-1/2"	3/4"	10
DCBSV-250-332	3/32"	2-1/2"	2-1/2"	3/4"	10
DCBSV-300-332	3/32"	3"	2-1/2"	3/4"	10
DCBSV-400-332	3/32"	4"	2-1/2"	3/4"	10

U.S. Patent Number 5,970,671 and 6,134,847

Code Approvals & Performance Standards

- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [ASTM E2110](#) Standard Terminology for Exterior Insulation and Finish Systems (EIFS)
- [ASTM E2511](#) Standard Guide for Detailing of EIFS-Clad Barrier and Drainage Wall Assemblies
- [ASTM E2568](#) Standard Specification for PB Exterior Insulation and Finish Systems
- [SDS Vinyl Corp](#) PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

