



NON-HARDENING PUTTY

SSP Putty & Putty Pads

SpecSeal® SSP Firestop Putty excels at sealing cabling penetrations and outlet boxes. SSP Putty is non-hardening and easily hand works around grouped cabling penetrations forming a re-enterable seal allowing for future work. When applied to outlet boxes, SSP Putty easily works into voids and seams forming a continuous seal against fire, smoke, and hot gases.

Features & Benefits

- Available in bars or preformed pads
- Remains pliable and workable for the lifetime of the installation
- Acoustically tested
- Will not harden over time



ORDERING INFORMATION

Catalog Number	UPC Number	Size	(EOM) Qty.	Case Qty.	Weight (Each)
SSP100	730573021057	36 in ³ (0.6 liter) bar	1	6	2.22 lbs (1.01 kg)
SSP28	730573021019	24 in ³ (0.4 liter) bar	1	1	1.42 lbs (0.64 kg)
SSP4S	73057302200	7.25" x 7.25" x 3/16" (184 mm x 184 mm x 4.8 mm) pad	1	20	0.64 lbs (0.29 kg)
SSP9S	73057302300	9.00" x 9.00" x 3/16" (229 mm x 229 mm x 4.8 mm) pad	1	20	0.85 lbs (0.39 kg)

TEST STANDARDS: ASTM E814 (UL 1479), CAN/ULC-S115, UL263



1-800-992-1180
stifirestop.com



Click here to learn more about



ZST13535 02020