


Sealants and Packing Material

3M™ Fire Barrier Water Tight Sealants 1003 SL (W-Rated)

3M™ Fire Barrier Water Tight Sealant 1003 SL is a ready-to-use, single component, neutral cure, silicone sealants that cure upon exposure to atmospheric humidity to form a flexible firestop seal. 3M™ Fire Barrier Water Tight Sealants helps control the spread of fire, smoke and noxious gasses before, during and after exposure to a fire when installed in accordance with a listed through penetration or fire-resistive joint assembly.

3M™ Fire Barrier Water Tight Sealant 1003 SL is a self-leveling firestop ideal for floor applications. The firestop sealant also meets UL Water Leakage Test, W Rating – Class 1 requirements for systems tested and listed in accordance with ANSI/UL 1479. Both products are elastomeric, are ready-to use and exhibit excellent weather ability.

Description	Water Tight Sealant Self-Leveling
Properties	Silicone
RoHS 2011/65/EU	Yes
Specifications	Fire Barrier 3 Hr; Smoke Seal L-Rated; Sound Barrier STC-Rating 56; Elastometric +-25%; Water Barrier UL W-Rating Class-1; ANSI/UL 1479; LEED® VOC environmental regulations
Agency Approvals	 Intertek; NEC (NFPA 70); IBC; IFC; IRC; NFPA 101; NFPA 5000



Order No.	UPC	Product Name	Color	Size	Case Quantity
1003-S/L-10.10Z	051115-11538	3M™ Fire Barrier Water Tight Sealant 1003 SL, 10.1 fl. oz., Cartridge	Light Gray	10.1 fl oz (295,6 ml)	12
1003SL	051115-18789	3M™ Fire Barrier Water Tight Sealant 1003 SL, 20 fl. oz., Sausage	Light Gray	20 fl oz (591,3 ml)	12
1003-S/L-4.5GAL	051115-11540	3M™ Fire Barrier Water Tight Sealant 1003 SL, 4.5 gallon, Pail	Light Gray	4.5 gal (15,1 l)	1