

## PRODUCT DATA SHEET

# Sika® Joint Tape SA Primer

Single component primer for use with Sika Joint Tape SA

### PRODUCT DESCRIPTION

Sika® Joint Tape SA Primer is a single component synthetic polymer-based primer for use with Sika Joint Tape SA to enhance adhesion to dusty/oxidized/porous surfaces, and to facilitate cold weather application in temperatures of 20 °F (-6 °C) to 40 °F (5 °C).

### USES

- Substrate surfaces contaminated with asphalt residue
- Porous masonry and concrete surfaces
- Wood substrate surfaces
- All applications with ambient and substrate temperatures below 40 °F (5 °C)

### CHARACTERISTICS / ADVANTAGES

- Sika® Joint Tape SA Primer improves adhesion of Sika Joint Tape SA to substrate surfaces that are difficult to clean, oxidized, or too porous to provide adequate surface area for bonding
- Sika® Joint Tape SA Primer enhances adhesion by preconditioning cold substrate surfaces
- Quick cure allows same-day Sika Joint Tape SA application

### PRODUCT INFORMATION

<b>Packaging</b>	1 gal. (3.8 L) cans
<b>Shelf Life</b>	12 months in original, unopened and undamaged sealed containers
<b>Storage Conditions</b>	Store dry at 41–86 °F (5–30 °C)
<b>Volatile organic compound (VOC) content</b>	588 g/l (ASTM D-2369-81)
<b>Viscosity</b>	135–152 cps. (at 75 °F (24 °C) and 50 % R.H.)

### APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	20 °F (-6 °C) min. / 95°F (35 °C) max.
<b>Relative Air Humidity</b>	80 % R.H. max
<b>Dew Point</b>	Beware of condensation. The substrate and uncured coating must be ≥ 5 °F (3 °C) above dew point.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

**Sika Corporation**

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Sarnafil**

100 Dan Road  
Canton, MA 02021  
Phone: +1 800-451-2504  
Fax: +1 781-828-5365  
[usa.sika.com/sarnafil](http://usa.sika.com/sarnafil)  
[webmaster.sarnafil@us.sika.com](mailto:webmaster.sarnafil@us.sika.com)

**Sika Mexicana S.A. de C.V.**

Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



**Product Data Sheet**

Sika® Joint Tape SA Primer  
April 2018, Version 01.02  
02091595100000033

SikaJointTapeSAPrimer-en-US-(04-2018)-1-2.pdf

