

SOPRASEAL®

STICK 1100T

SOPRASEAL Stick 1100T is a self-adhered waterproofing membrane. SOPRASEAL Stick 1100T is composed of a proprietary high quality elastomeric styrene-butadiene-styrene (SBS) polymer modified bitumen blend and a woven polyethylene composite facer. SOPRASEAL Stick 1100T is used as a self-adhered air, vapor and rain barrier on vertical walls of masonry, concrete or gypsum sheathing designed to be used as a base for exterior insulation and finish systems (EIFS). SOPRASEAL Stick 1100T may also be used as a transition membrane at doors, windows, penetrations, etc. The underside consists of a self-adhesive bitumen layer protected by a release paper.

INSTALLATION

Apply by peeling back the release film on the underside of the sheet and apply with hand pressure. Once the sheet is in place, roll entire sheet with a weighted roller. The application temperature range for SOPRASEAL Stick 1100T is 14 to 122°F (-10 to 50°C) and the service temperature range is -49 to 194°F (-45 to 90°C).

PRODUCT PROPERTIES

THICKNESS	40 mils (1.0 mm)
TOPSIDE	Tri-laminate Woven Polyethylene
UNDERSIDE	Release Film
GRADE	Summer & Winter

APPLICATION



SELF
ADHERED

RELATED PRODUCTS

ELASTOCOL STICK
ELASTOCOL STICK H20
ELASTOCOL STICK ZERO



AIR & VAPOR BARRIERS
SOPRASEAL®

SOPRASEAL STICK 1100T

PRODUCT CODE

D14046/D14033

Scan QR code with
the SOPREMA toolbox
app for more information.

