



INCRETE STAIN-CRETE

ACID-BASED CHEMICAL STAIN FOR CONCRETE

PACKAGING

1 gal (3.8 L) units.

YIELD

First Coat: Approximately 200 to 300 ft²/gal (4.9 to 7.4 m²/L). A second coat may be necessary for desired results.

APPEARANCE

Acid based liquid available in 9 colors

CLEAN UP

Avoid staining all unintended surfaces. Rinse spills and tools immediately with water.

SHELF LIFE

3 years in original, unopened container

SPECIFICATIONS AND COMPLIANCES

Complies with applicable air quality management regulations.

BRIEF OVERVIEW

INCRETE STAIN-CRETE is a penetrating, acid-based stain used to color old or new concrete. INCRETE STAIN-CRETE reacts chemically with cured concrete to provide a translucent, permanent color with a subtly shaded marbled effect, similar to the aged appearance of natural stone. INCRETE STAIN-CRETE's rich variegated finish will not peel, crack, chip, or fade from UV light. INCRETE STAIN-CRETE can also be used in conjunction with overlays, such as INCRETE LEVEL TOP STAIN, INCRETE THIN-CRETE, INCRETE SPRAY-DECK, or Euclid Chemical's EUCLID RE-COVER.

PRODUCT CHARACTERISTICS

ADVANTAGES

- Can be applied on integrally colored concrete or over color hardeners.
- Provides variegated appearances and long-lasting durability that will not peel or chip.
- Can be applied vertically or horizontally.
- Easy to clean and maintain.
- Available in 9 colors
- Realistic natural look
- UV safe

PHYSICAL PROPERTIES

- Colored acidic solution
- pH < 1.0

COMMON USES

- Residential or commercial applications.
- Hotels, entryways
- Restaurant floors
- Showrooms
- Patios, pool decks
- Basement or garage floors
- Large commercial projects
- Driveways, sidewalks

COMMON APPLICATION METHODS

- Sprayer
- Roller
- Brush
- Sponge

TECHNICAL INFORMATION

Acidic solution of various metallic salts.

DIRECTIONS FOR USE

For complete installation instructions, consult the INCRETE STAIN-CRETE Installation Guide.

PREPARATION

For best results, concrete must cure for a minimum of 28 days. Concrete surfaces must be structurally sound, free of loose or deteriorated concrete and free of dust, dirt, paint, efflorescence, oil and all other contaminants. Remove any loose material and any coatings such as paint, curing agents, and sealers. Increte Uni-Stripp is perfect for removing old coatings. Clean with a cleaner/degreaser specifically designed for concrete and paver surfaces. Mechanically abrade the surface to achieve a surface profile equal to CSP 1-2 in accordance with ICRI Guideline 310.2. Properly clean profiled area. Do not acid-etch.

APPLICATION

A small test area is recommended to ensure suitability for application and desired appearance. Apply INCRETE STAIN-CRETE to the concrete surface using an acid-resistant pump sprayer. Depending on surface porosity, an acid resistant brush may be used to assure the stain penetrates into the concrete. Brush the stain a circular motion until the fizzing-reaction stops. Avoid any puddling. Allow the stain to dry for eight hours, and apply a second coat if needed for a particular appearance. When staining is complete, scrub off all residue and salts with a stiff brush and water, and flush with clean water until all residue is gone. To neutralize the surface, mix either 1 lb (0.45 kg) baking soda or 1 qt (0.94 L) ammonia in a 5 gal (18.9 L) container of water. Apply to surface and then rinse thoroughly with clear water.

SEAL

Once the surface is dry and free of any residue, apply a clear sealer such as INCRETE CLEAR SEAL, INCRETE HIGH PERFORMANCE EPOXY, INCRETE WATER BASED URETHANE, or INCRETE POLYSEAL. The selection of the correct sealer will depend on the level of traffic, use and location of the project. If not sure what sealer will be better for your application call your Euclid Chemical representative.

MAINTENANCE

For Interior cleaning: Sweep and mop with a commercial floor cleaner. A periodic application of INCRETE HIGH GLOSS WAX is recommended to ease cleaning, to add luster, and to protect from wear.

For Exterior cleaning: Rinse with clean water. For heavily soiled areas use a cleaner/degreaser as directed. Periodic reapplication of sealer may be needed.

PRECAUTIONS/LIMITATIONS

- Use only in areas with adequate ventilation.
- Certain INCRETE STAIN-CRETE colors; Weathered Copper, Lime Green, Turquoise, and Bronze, should only be used for interior applications.
- Stained concrete must be protected from any source of water or excessive moisture.
- For professional use only.
- In all cases, consult the Safety Data Sheet before use

Rev. 07.21

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.