

**Protection Board** 

# **Product Description**

Tremco® 2450 Protection Board is an extruded, hollow-core polypropylene/polyethylene copolymer. The board is grey in color with a standard thickness of 0.08" (2.2 mm).

## **Basic Uses**

Tremco 2450 provides protection for most commonly used waterproofing membranes, both during and after construction. Typical applications include plaza decks, roof terraces, landscaped decks, planters and foundation walls.

## **Features and Benefits**

- Provides protection from normal construction traffic for most waterproofing membranes. Its light weight provides economic advantages in both application and on-site handling.
- · Easily cut or folded to conform to difficult site conditions. Positive adhesion to membranes makes it ideal for vertical applications such as planters and foundation walls.
- Tremco 2450 remains inert in landscaped areas and will not absorb moisture, thus providing long-term protection to the waterproofing membrane.

### Packaging

Sheets are 0.08" (2.2 mm) thick, 4' x 3' (1.2 m x 0.9 m)

Fifty sheets = 600 ft<sup>2</sup> (55.7 m<sup>2</sup>) per bundle

# Limitations

- Not intended for use directly under asphalt paving.
- Not recommended for permanent UV exposure.

### Warrantv

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Product proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.



#### 0417/T2450DS-BG

3735 Green Rd Beachwood OH 44122 216.292.5000 / 800.321.7906

**Tremco Commercial Sealants & Waterproofing** 1451 Jacobson Ave Ashland OH 44805 419.289.2050 / 800.321.6357

220 Wicksteed Ave Toronto ON M4H1G7 416.421.3300 / 800.363.3213

1445 Rue de Coulomb Boucherville QC J4B 7L8 514.521.9555

www.tremcosealants.com