



FINISHING AID™

FINISHING & TROWELING AID

SINAK Finishing Aid™ reduces friction while troweling freshly placed concrete. It is compatible with all curing agents, compounds, and evaporation retarders and is designed to be used as a troweling aid on any concrete surface.

Finishing Aid™ is especially effective with low slump concrete and colored concrete. It excels in adverse weather conditions, and is a simple, ready-to-use product that does not require dilution or mixing on the job site.



FEATURES & BENEFITS

- UNIVERSALLY COMPATIBLE
- INCREASES WORKABILITY
- REDUCES DUSTING
- MITIGATES PLASTIC SHRINKAGE CRACKS

SINAK Finishing Aid™ prevents, dusting, crazing and surface cracking. It improves workability, reduces surfaces defects without impacting the color or appearance.

SINAK Finishing Aid™ does not overwater concrete that can lead to weak paste composition. The addition of SINAK Finishing Aid™ to the surface allows concrete finishing to stay on schedule. SINAK recognizes that each concrete placement is unique. Weather conditions, mix designs and geography all play a role in the ability to place and finish the concrete surface. SINAK Finishing Aid™ is recommended for use in conjunction with SINAK moisture vapor control and SINAK curing products.



WHERE TO USE FINISHING AID™

- MEDICAL FACILITIES
- CONCRETE PAVEMENTS
- ROLLER COMPACTED CONCRETE (RCC)
- CAST-IN-PLACE
- STRUCTURAL CONCRETE
- COMMERCIAL
- SCHOOLS
- WAREHOUSE/DISTRIBUTION

COMPOSITION & MATERIALS

SINAK Finishing Aid™ is a proprietary water-based formula in solution. SINAK Finishing Aid™ requires no mixing, diluting, or agitation. Color: Water Clear; Net Weight: 8.6 lbs/gal; Toxicity: Non-toxic; VOC: Contains no volatile organic compounds or solvents.

INSTALLATION

SINAK Finishing Aid™ is a ready to use formula. SINAK Finishing Aid™ may be used in ride on power trowels, pump sprayers, or small spray bottles for use on hand tools. SINAK recommends that a 0.50 GPM (1.9 LPM) fan spray tip or smaller be used.

PRECAUTIONS

Apply only enough material as needed based on the site testing. Do not flood the surface. Do not allow to puddle. Protect adjoining surfaces from overspray. Clean spray equipment and tools with warm soapy water.

SINAK SYSTEMS

- **SINAK FINISHING AID™**: All concrete and cementitious products
- **SINAK VC-5™**: 20-year flooring/roofing warranty
- **SINAK LITHIUMCURE 2000™**: Hard trowelled or burnished slabs or polished concrete
- **SINAK LITHIUMCURE 1000™**: Textured or broom finished slabs or potable water applications
- **CURE3D™**: Interior and exterior concrete

COVERAGE RATES (SUBJECT TO SURFACE FINISH)

SINAK Finishing Aid™ is a ready to use formula designed for an application rate of 1000 sq ft per gallon or greater (25 sq m per liter). Contact SINAK for additional information. Each concrete placement is unique. Weather conditions, mix designs, and geography all play a role in the ability to finish the concrete surface. To determine the need for use and coverage rates, a small test sample is recommended.

STORAGE & HANDLING

SINAK Finishing Aid™ has an indefinite shelf life when stored in a cool dry area out of direct sunlight. Must be kept in tightly secured containers to prevent evaporation and contamination. SINAK Finishing Aid™ MUST be protected from freezing. Product that has frozen will not function as intended and should be discarded.

AVAILABILITY

SINAK Finishing Aid™ is available in 1-gallon (3.78-liter) jugs, 5-gallon (18.9-liter) pails, 55-gallon (208.2-liter) drums and 275-gallon (1041-liter) totes from selected distributors.

TECHNICAL ASSISTANCE

Technical assistance is available from the manufacturer.

SINAK warrants its products to be free from manufacturing defects and to meet the technical properties on the current product information sheet. To the maximum extent permitted by law, this express warranty and the remedies specified below are exclusive and in lieu of all other warranties and remedies. Any implied warranties including without limitation implied warranties of merchantability and fitness for a particular purpose are excluded. SINAK's liability under this product warranty shall be limited to a refund of purchase price or replacement of the product. SINAK shall have no liability for any loss of use, interruption of business, lost profits or goodwill, or for any special, incidental or consequential damages of any kind arising from the purchase or use of the warranted product, even if SINAK has been advised of the possibility of such loss, interruption or damage. This limited warranty may not be modified by representatives of SINAK, its distributors or dealers. Any claim made under this warranty must be made within one (1) year of purchase and shall be accompanied by any reports or test results that form the basis of the warranty claim. Prior to settlement of a warranty claim, SINAK shall have the right, but not the obligation, to conduct site inspections and perform tests pertaining to the customer's warranted product and its manner of use.