



METACAULK® FIRESTOP SEALANTS cont.

Metacaulk® 835+

Elastomeric, silicone firestop sealant

| Code | Description | Qty. |
|-------|-----------------------|------|
| 66645 | 10.15 oz. cartridge | 12 |
| 66019 | 5 gal. caulk grade | 1 |
| 66300 | 20.2 oz caulk grade | 12 |
| 66301 | 20.2 oz self-leveling | 12 |
| 66295 | 5 gal. spray | 1 |



Intertek
CONTROL NO.
5009113
SPRAY ONLY

FEATURES

- Exterior/Interior use
- Weather/chemical resistant
- Excellent moisture resistance
- Tested in accordance with ASTM E814 (UL 1479) & ASTM E1966 (UL 2079), ASTM 1399 & ASTM E90
- Class 1 W Rating (caulk & SL)
- STC rating 55
- Caulk-Meets ASTM C920, Type S, Grade NS, Class 25, Use NT, M, G, A, O (For SL- Meets ASTM C920, Type S, Grade SL, Class 25, Use NT, M G, A, O.)
- Spray - Meets ASTM C920 Type S, , Grade P, Class 25, Use NT, M G, A, O
- Caulk 2 year shelf life, Spray 18 months shelf life
- Color: Gray

APPLICATION • Used in systems where constant dynamic movement is expected • Resistant to chemical exposure

RECOMMENDED FOR

- Cable and cable trays • EMT
- Insulated and uninsulated steel pipe • Construction and control joints • Interior expansion joints • Spandrel glass & unitize backpan spandrel glass • Concrete panel & exterior gypsum sheathing



Metacaulk® 950

Non-combustible firestop sealant

| Code | Description | Qty. |
|-------|--------------------|------|
| 66643 | 10.3 oz. cartridge | 12 |



Intertek
CONTROL NO.
5007154

FEATURES

- Gas/Smokeless under fire exposure
- Hardened cure
- Interior application
- Tested in accordance with ASTM E814 (UL 1479) & ASTM E1966 (UL 2079)
- 2 year shelf life
- Color: Beige

APPLICATION • Formulated with inorganic materials

- Will not create smoke or toxic gases • For interior applications only
- Not for use in vibration or wet environments

RECOMMENDED FOR

- PVC/CPVC pipe (closed only) • EMT • Steel, Copper, and Aluminum Pipe • Multiple Pipes, Conduit, and Cable
- Telephone, Power, Romex Cable • Static Construction Joints



*FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology. The FBC System Compatible Logo, FBC™, FlowGuard Gold®, BlazeMaster®, Corzan® and TempRite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.