

AIR & VAPOR BARRIERS

SOPRASEAL®



SOPRASEAL LM 204 VP

PRODUCT CODE

A506

Scan QR code with
the SOPREMA toolbox
app for more information.



SOPRASEAL®

LM 204 VP

SOPRASEAL LM 204 VP is a one-component, high solids content, liquid applied, vapor-permeable air barrier membrane used in wall construction. SOPRASEAL LM 204 VP is an STPE technology that contains 98% solids and has excellent freeze-thaw characteristics. This moisture curable hybrid material is a non-flammable vapor permeable air barrier, which provides moisture protection behind wall claddings such as brick, siding, metal panels, EIFS and stucco. Utilization of a drainage plane is required for stucco cladding.


INSTALLATION

To apply SOPRASEAL LM 204 VP keep the product in the original packaging and mix with a clean, slow speed (200-400 rpm) mechanical agitator. SOPRASEAL LM 204 VP can be applied down to 25°F (-4°C) without the use of additional additives. The most effective application method utilizes spray equipment but a 3/4" (19mm) nap roller or a pain brush may be used.

PRODUCT PROPERTIES

COLOR	Blue
SOLIDS	98 %
VOLUME	5 gal (19 L)/ 50 gal (189 L) Drums

APPLICATION



LIQUID APPLIED



BRUSH



ROLLER

RELATED PRODUCTS

SOPRASEAL STICK 1100T
SOPRASOLIN HD
SOPRASEAL LIQUID FLASHING