



EUCLID CHEMICAL

# CONCRETE REPAIR MORTARS



## VERTICAL & OVERHEAD SURFACES

### FORM AND POUR/PUMP

**EucoRepair SCC**  
Self-consolidating structural repair mortar that is shrinkage compensated and contains polymer, microfiber, and corrosion inhibitor. Can be placed from 1 inch (25 mm) to full depth without aggregate extension. Also available in a faster setting version, **EucoRepair SCC Fast**.

**Eucocrete**  
High strength, microsilica modified repair mortar that has an extended working time for ease of placement. Can be placed full depth with aggregate extension.

**Tamms Form and Pour**  
Shrinkage compensated concrete repair mortar that utilizes a smaller aggregate for increased flowability.

### HAND APPLIED

**EucoRepair V100**  
NSF/ANSI Standard 61 approved, quick setting, low shrinkage repair mortar fortified with polymer and microfiber for high performance vertical and overhead repair.

**Speed Crete Red Line**  
Rapid setting concrete and masonry repair mortar that can be shaved to match the contour of the surrounding concrete. Reaches final set in just 30 minutes.

**Speed Crete PM**  
Polymer modified, easy to use repair mortar that can be applied from featheredge to 3 inches (76 mm) per lift.

For additional product information refer to the technical data sheet at [www.euclidchemical.com](http://www.euclidchemical.com).

**Verticoat Supreme**  
Microsilica and latex modified, non-sag repair mortar for trowel applied vertical and overhead repairs requiring high performance.

**Verticoat**  
Two part latex modified mortar that sets rapidly for quick and easy repair of vertical or overhead concrete surfaces.

**Eucopatch**  
Fast setting repair mortar for vertical and overhead concrete that can also be used in light-duty, pedestrian, horizontal applications.

**Tammscrete**  
Polymer modified, cement based material used to produce a smooth finish on precast, cast-in-place, tilt-up or other concrete surfaces with bugholes or other imperfections.

**Tamms Structural Mortar**  
NSF/ANSI Standard 61 approved repair mortar with fiber reinforcement and a corrosion inhibitor designed for low pressure spray application or hand applied concrete repair.

### SHOTCRETE

**Eucoshot**  
Silica fume modified, dry shotcrete repair material. Available in versions that include fiber reinforcement, silica fume, water repellents, and more.

### UNDERWATER

**Speed Crete Blue Line**  
Fast setting underwater concrete patching material that can be installed without forming at a zero-slump consistency.

## VERTICAL & OVERHEAD SURFACES

PLACEMENT CATEGORY	FORM AND POUR/PUMP			CEMENTITIOUS TROWELABLE							TROWELABLE & SPRAYABLE	SPRAYABLE	UNDERWATER	
	PRODUCT NAME	EucoRepair SCC EucoRepair SCC Fast	Eucocrete	Tamms Form and Pour	EucoRepair V100	Eucopatch	Tammscrete	Verticoat	Verticoat Supreme	Speed Crete Red Line	Speed Crete PM	Tamms Structural Mortar	Eucoshot	Speed Crete Blue Line
PRODUCT CHARACTERISTICS		Self-Consolidating, Fiber Reinforced, Low Shrinkage, Full Depth Without Extending	High Strength, Full Depth Repairs (if extended)	Smaller Aggregate, Enhanced Pumpability	Low Shrinkage, Fiber Reinforced, NSF/ANSI 61	Versatile, Color Similar to Plain Concrete	Polymer Modified, Smooth Consistency	Two Part, Polymer Modified	Corrosion Inhibitor, Polymer and Microsilica Modified	Fast Setting, Can be Shaved to Desired Shape	Polymer Modified	Fiber Reinforced, NSF/ANSI 61, Spray or Trowel	Silica Fume Modified	Underwater Patching Material, Rapid Set
Number of Components		One	One	One	One	One	One	Two	One	One	One	One	One	One
Extendable		No	Yes	Yes	No	No	Yes	No	No	Yes	No	No	No	No
Yield, ft <sup>3</sup> (m <sup>3</sup> )	Neat Extended	.37 (.0105) NA	37 (.0105) .46 (.013)	.42 (.0119) .62 (.02)	.45 (.0127) NA	.44 (.0124) NA	.40 (.0113) .45 (.013)	.48 (.0136) NA	.48 (.0136) NA	.47 (.0133) .70 (.02)	.50 (.0142) NA	.45 (.0127) NA	.42 (.0119) NA	.47 (.0133) NA
Minimum Thickness, in. (mm)		1" (25.4)	1" (25.4)	3/4" (19)	1/8" (3.2)	1/16" (1.6)	Featheredge	1/8" (3.2)	1/4" (6)	3/4" (19)	Featheredge	3/8" (10)	1" (25.4)	3/4" (19)
Maximum Thickness in. (mm)	Neat Extended	Full Depth NA	6" (152) Full Depth	3" (76) Full Depth	V: 4" (102) OH: 2" (51) 6" (152)	4" (102) NA	1/8" (3) 1/4" (6)	4" (102) NA	2" (51) NA	2" (51) 4" (102)	3" (76) NA	2" (51) NA	6" (152) NA	3" (76) NA
Working Time, minutes		SCC:180/SCC Fast: 30	150	60	15	6	20	20	30	5	10	30	180	2-3
Initial Set, hr:min		SCC 9:00/SCC Fast 0:50	3:00	6:20	:20	:08	:25	:25	1:00	:08 - :10	:15	1:00	3:40	:03 - :05
Final Set, hr:min		SCC 10:00/SCC Fast 1:00	4:00	7:30	:35	:20	:40	:40	3:00	:20	:40	2:00	4:40	:20
Temperature Limitations		> 45°F (7°C)	> 45°F (7°C)	> 40°F (4°C)	> 45°F (7°C)	> 45°F (7°C)	> 40°F (4°C)	> 45°F (7°C)	> 45°F (7°C)	> 35°F (2°C)	> 45°F (7°C)	> 40°F (4°C)	> 40°F (4°C)	> 32°F (0°C)
Compressive Strength, psi (MPa)		SCC SCC Fast												
4 Hour		2,750 (19)	3,000 (21)	5,000 (34)	2,000 (14)	2,000 (14)	3,000 (21)	4,000 (28)	2,000 (14)	2,550 (18)	2,500 (17)	3,200 (22)	3,500 (24)	3,200 (22)
1 Day		4,800 (33)	4,500 (31)	5,000 (34)	3,000 (21)	4,500 (31)	4,500 (31)	6,000 (41)	3,500 (24)	4,000 (28)	6,500 (45)	6,200 (43)	7,000 (48)	4,000 (28)
7 Day		5,600 (39)	6,000 (41)	8,800 (61)	4,500 (31)	6,500 (45)	4,500 (31)	6,500 (45)	5,500 (38)	5,700 (39)	7,000 (48)	8,500 (59)	9,500 (65)	6,015 (42)
Final			8,000 (55)	10,000 (69)	6,000 (41)	6,500 (45)	4,500 (31)	6,500 (45)	5,500 (38)	5,700 (39)	7,000 (48)	8,500 (59)	9,500 (65)	6,015 (42)
Compatible with Galvanic Anodes			✓			✓		✓		✓	✓	✓	✓	
Structural Repairs		✓	✓	✓	✓			✓			✓	✓	✓	✓
Cosmetic Repairs						✓	✓	✓		✓				
NSF/ANSI Standard 61 Certified					✓							✓		

Technical results shown were determined at laboratory conditions.



EUCLID CHEMICAL

19215 Redwood Road  
Cleveland, OH 44110  
t 800-321-7628  
f 216-481-7072

[www.euclidchemical.com](http://www.euclidchemical.com)

**B31 Concrete Repair Mortars Pocket Guide** © 2018 The Euclid Chemical Company. This material is provided for informational purposes only. The Euclid Chemical Company expressly disclaims any liability relating to the use of this material. Nothing stated herein shall give rise to or constitute any warranty by The Euclid Chemical Company, express or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The information provided in this material is not intended to be all inclusive, as the manner in which any product is used or handled may involve other or additional considerations that are not addressed herein.

## ADDITIONAL EUCLID CHEMICAL SOLUTIONS FOR CONCRETE REPAIR AND PROTECTION

- Cathodic protection
- Epoxy crack injection
- Crystalline waterproofing
- Chemical grouts
- Floor and traffic deck coatings
- Architectural wall coatings
- Moisture mitigation systems
- Water repellent sealers



## HORIZONTAL SURFACES

### FORM AND POUR/PUMP

#### EucoRepair SCC

Self-consolidating structural repair mortar that is shrinkage compensated and contains polymer, microfiber, and corrosion inhibitor. Can be placed from 1 inch (25 mm) to full depth without aggregate extension. Also available in a faster setting version, **EucoRepair SCC Fast**.

#### Euocrete

High strength, microsilica modified repair mortar that has an extended working time for ease of placement. Can be placed full depth with aggregate extension.

#### Tamms Form and Pour

Shrinkage compensated concrete repair mortar that utilizes a smaller aggregate for increased flowability.

### HAND APPLIED

#### Versaspeed 100

Rapid hardening, low shrinkage, microfiber reinforced repair mortar. Repaired areas can be open to standard tire traffic 2 hours following final set and an epoxy coatings can be applied after 4 hours.

#### Versaspeed LS 100

Similar to Versaspeed 100, but with a longer set time. Can be open to light traffic after 4 hours and coated with epoxy after 5 hours.

#### Tamms Thin Patch

Polymer modified mortar formulated for horizontal, vertical, or overhead repair from featheredge up to 1 inch (25 mm).

#### Express Repair

Single component, cement based patching mortar with rapid strength gain.

### HORIZONTAL TOPPING

#### Concrete-Top Supreme

Latex and microsilica modified, cementitious topping providing protection from corrosion and excellent durability under freeze-thaw conditions. Suitable for application depth from 3/8 inch to 2 inches (9.5 mm to 50 mm).

#### Thin-Top Supreme

Similar to Concrete-Top Supreme in application and performance, but for thinner toppings from 1/16 inch to 3/8 inch (1.6 mm to 9.5 mm).

#### Euco Re-Cover

Polymer modified, microfiber reinforced resurfacer that gives a fresh appearance to new concrete that has been marred by rain or plastic coverings, or concrete damaged by deicing chemicals or freeze-thaw cycling.

#### Tammspatch II

Two component, polymer modified, cementitious repair mortar and underlayment for numerous applications. Can be mixed at different consistencies, from very flowable to stiff, to meet the requirements of the repair project.

### SELF-LEVELING UNDERLAYMENTS

#### EucoFloor SL 160

Single component, portland cement based self-leveling underlayment for installation from featheredge to 1 inch (25 mm) neat. Can also be used as an indoor, light duty wearing surface when protected by a Euclid Chemical epoxy/urethane coating system.

#### Super Flo-Top

Single-component, flowable, portland cement based underlayment that delivers high early strength.

### POLYMER BASED HORIZONTAL REPAIR

#### Euco QWIKstitch

Two component very low viscosity hybrid urethane that repairs cracks, spalls, popouts, and damaged joints. Concrete repaired with QWIKstitch can be opened to traffic in less than one hour. Bulk units can be pigmented with Euclid Universal Color Packs, available in 33 standard colors.

#### EUCO 456S

Epoxy and iron aggregate repair material for use where exceptional impact and abrasion resistance are required.

#### Duralflex Fastpatch

Low modulus, natural aggregate epoxy repair mortar designed to provide a high strength, wear resistant surface to damaged high-use floors. Duralflex Fastpatch can be pigmented on the jobsite with Euclid Universal Color Packs, available in 33 standard colors.

## HORIZONTAL SURFACES

PLACEMENT CATEGORY		FORM AND POUR/PUMP			HAND APPLIED				TOPPING			REPAIR & UNDERLAYMENT	SELF-LEVELING UNDERLAYMENTS		POLYMER BASED REPAIR		
PRODUCT NAME		EucoRepair SCC EucoRepair SCC Fast	Euocrete	Tamms Form and Pour	Express Repair	Versaspeed 100	Versaspeed LS 100	Tamms Thin Patch	Concrete-Top Supreme	Thin-Top Supreme	Euco Re-Cover	Tammspatch II	EucoFloor SL 160	Super Flo-Top	Euco QWIKstitch	Euco 456S	Duralflex Fastpatch
PRODUCT CHARACTERISTICS		Self-Consolidating, Fiber Reinforced, Low Shrinkage, Full Depth Without Extending	High Strength, Full Depth Repairs (if extended)	Smaller Aggregate, Enhanced Pumpability	Rapid Strength Gain, Meets ASTM C 928	Fast Setting, Contains Microfiber, Coat in 4 hrs	Extended Working Time, Coat in 5 hrs	Versatile, Easy to Use	Heavy Duty, High Strength	Heavy Duty, High Strength, Thin Applications	Thin Resurfacer, Microfiber Reinforced	Easy to Use, Can be Applied Horizontally or Vertically	Portland Based Underlayment or Light Duty Wearing Surface	Portland Based Underlayment	Low Viscosity Hybrid Urethane, Fast Cure	Epoxy & Iron Aggregate Mortar, Impact & Abrasion Resistant	Low Modulus Epoxy Mortar
Number of Components		One	One	One	One	One	One	One	One	One	One	Two	One	One	Two	Three	Three
Extendable		No	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	No	Yes	Yes	Yes	Yes	No	No
Yield ft <sup>3</sup> (m <sup>3</sup> )	Neat	.37 (.0105)	.37 (.0105)	.42 (.0119)	.42 (.0119)	.37 (.0105)	.39 (.011)	.40 (.0113)	.40 (.0113)	.43 (.012)	.48 (.0136)	.42 (.0119)	.52 (.015)	.52 (.0147)	33 in <sup>3</sup> (540 cm <sup>3</sup> ) per 20 oz. cartridge	.35 (.0099)	.40 (.0113)
	Extended	NA	.46 (.013)	.62 (.018)	.75 (.021)	.52 (.015)	.52 (.015)	NA	.47 (.013)	.53 (.015)	N/A	.55 (.016)	.65 (.018)	.65 (.018)	NA	NA	NA
Minimum Thickness, in. (mm)		1" (25.4)	1" (25.4)	3/4" (19)	1/2" (13)	1/4" (6)	1/4" (6)	Featheredge	3/8" (10)	1/16" (1.6)	Featheredge	Featheredge	Featheredge	Featheredge	NA	1/8" (3)	1/4" (6)
Maximum Thickness in. (mm)	Neat	Full Depth	6" (152)	3" (76)	1.5" (38)	2" (51)	2" (51)	1" (25.4)	2" (51)	3/8" (10)	3/8" (10)	1" (25.4)	1" (25.4)	1" (25.4)	NA	2" (50)	3" (76)
	Extended	NA	Full Depth	Full Depth	3" (76)	6" (152)	6" (152)	NA	6" (152)	1.25" (32)	N/A	2.5" (64)	2.5" (64)	3" (76)	NA	NA	NA
Working Time, minutes		SCC:180/SCC Fast: 30	150	60	20	15	45	20	30	35	30	45	15	15	10	75	25
Initial Set, hr:min		SCC 9:00/SCC Fast 0:50	3:00	6:20	:20 to :50	:10 to :20	:30 to 1:00	:30 to 1:00	1:00	1:00 to 1:30	1:00	1:30 to 3:00	:45	:45	NA	NA	NA
Final Set, hr:min		SCC 10:00/SCC Fast 1:00	4:00	7:30	1:00	:20 to :40	1:00 to 1:40	1:00 to 2:00	3:00	3:00	2:30	4:00 to 5:00	1:00	1:00 to 1:30	NA	NA	NA
Temperature Limitations		> 45°F (7°C)	> 45°F (7°C)	> 40°F (4°C)	> 35°F (2°C)	> 35°F (2°C)	> 45°F (7°C)	> 40°F (4°C)	> 45°F (7°C)	> 45°F (7°C)	> 50°F (10°C)	> 40°F (4°C)	> 40°F (4°C)	> 40°F (4°C)	> 0°F (-18°C)	> 50°F (10°C)	> 40°F (4°C)
Compressive Strength, psi (MPa)		SCC	SCC Fast														
4 Hour			3,000 (21)	—	3,200 (22)	5,000 (34)	2,800 (19)	—	—	—	—	—	900 (7)	1,300 (9)	4,600 (32)	—	—
1 Day		2,750 (19)	4,500 (31)	—	5,800 (40)	6,000 (41)	4,000 (28)	1,200 (8)	4,000 (28)	2,000 (14)	1,650 (11)	—	2,000 (14)	2,200 (15)	12,000 (83)	7,000 (49)	—
7 Day		4,800 (33)	6,000 (41)	—	7,000 (48)	7,500 (52)	5,000 (34)	—	7,000 (48)	4,000 (28)	2,100 (14)	3,000 (21)	3,000 (21)	3,000 (21)	4,800 (33)	—	—
Final		5,600 (39)	8,000 (55)	—	9,000 (62)	10,500 (72)	8,000 (55)	3,500 (24)	9,500 (66)	6,000 (41)	4,000 (28)	5,000 (34)	3,500 (24)	3,500 (24)	4,800 (33)	13,500 (93)	9,800 (68)
Compatible with Galvanic Anodes			✓		✓				✓								
Structural Repair		✓	✓	✓	✓	✓	✓		✓	✓					✓	✓	✓
Cosmetic Repair								✓			✓	✓	✓	✓			

Technical results shown were determined at laboratory conditions.

For additional product information refer to the technical data sheet at [www.euclidchemical.com](http://www.euclidchemical.com).