

MasterProtect P 8100AP

Version **Revision Date:** SDS Number: Date of last issue: -

07/15/2020 000000261398 Date of first issue: 07/15/2020 1.0

SECTION 1. IDENTIFICATION

Product name : MasterProtect P 8100AP

Product code 00000000050341562 00000000050341562

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier Master Builders Solutions Canada Inc.

Address 1800 CLARK BLVD

Brampton ON L6T 4M7

Emergency telephone ChemTel: +1-813-248-0585;

Recommended use of the chemical and restrictions on use

Recommended use Product for construction chemicals

Restrictions on use Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

FLAMMABLE LIQUIDS 2

Skin corrosion/irritation 2

Serious eye damage/eye

irritation

: Category 2A

Skin sensitization : 1

Carcinogenicity 2

Specific target organ toxicity : 2 (Auditory organ)

- repeated exposure

Short-term (acute) aquatic

hazard

Long-term (chronic) aquatic

hazard

GHS label elements

Hazard pictograms











MasterProtect P 8100AP

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapour.

H319 Causes serious eve irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer.

H373 May cause damage to organs (Auditory organ) through

prolonged or repeated exposure. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P273 Avoid release to the environment.

P260 Do not breathe dust or mist.

P201 Obtain special instructions before use. P243 Take action to prevent static discharges.

P202 Do not handle until all safety precautions have been read

and understood.

P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?]

equipment.

P272 Contaminated work clothing should not be allowed out of the workplace.

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P240 Ground and bond container and receiving equipment. P264 Wash face, hands and any exposed skin thoroughly after

handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.

P391 Collect spillage.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse

P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

P370 + P378 In case of fire: Use water spray, alcohol-resistant

foam, dry chemical or carbon dioxide to extinguish. P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.



MasterProtect P 8100AP

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

Storage:

P405 Store locked up.

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

Other hazards

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
zinc	7440-66-6	>= 50 - < 75
Methylethylketone	78-93-3	>= 7 - < 10
xylene	1330-20-7	>= 7 - < 10
Reaction product: bisphenol-A- (epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)	25068-38-6	>= 5 - < 7
ethylbenzene	100-41-4	>= 1 - < 3
cyclohexanone	108-94-1	>= 1 - < 3
talc	14807-96-6	>= 1 - < 3

SECTION 4. FIRST AID MEASURES

General advice : Remove contaminated clothing.

Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

tion.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash thoroughly with soap and water

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Wash affected eyes for at least 15 minutes under running

water with eyelids held open, consult an eye specialist.

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.



MasterProtect P 8100AP

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

Beware of vapors accumulating to form explosive concentra-

tions. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, ver-

miculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : no smoking

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, well-ventilated

place.

Protect from direct sunlight.

Materials to avoid : Segregate from metals.

Segregate from lyes.



MasterProtect P 8100AP

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

Segregate from oxidants.

Segregate from foods and animal feeds.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methylethylketone	78-93-3	STEL value	300 ppm	ACGIHTLV
		TWA value	200 ppm	ACGIHTLV
		REL value	200 ppm 590 mg/m3	NIOSH
		STEL value	300 ppm 885 mg/m3	NIOSH
		PEL	200 ppm 590 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	200 ppm 590 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	300 ppm 885 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	200 ppm 590 mg/m3	CA AB OEL
		STEL	300 ppm 885 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	50 ppm 150 mg/m3	CA QC OEL
		STEV	100 ppm 300 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
ethylbenzene	100-41-4	TWA value	20 ppm	ACGIHTLV
		STEL value	125 ppm 545 mg/m3	NIOSH
		REL value	100 ppm 435 mg/m3	NIOSH
		PEL	100 ppm 435 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 435 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	125 ppm 545 mg/m3	29 CFR 1910.1000



MasterProtect P 8100AP

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

		1	I	(Table Z-1-A)
		TWA	100 ppm	CA AB OEL
			434 mg/m3	
		STEL	125 ppm	CA AB OEL
			543 mg/m3	
		TWA	20 ppm	CA BC OEL
		STEV	125 ppm	CA QC OEL
			543 mg/m3	
		TWAEV	100 ppm	CA QC OEL
			434 mg/m3	
		TWA	20 ppm	ACGIH
cyclohexanone	108-94-1	TWA value	20 ppm	ACGIHTLV
		STEL value	50 ppm	ACGIHTLV
		REL value	25 ppm	NIOSH
		111111111111111111111111111111111111111	100 mg/m3	
		PEL	50 ppm	29 CFR
			200 mg/m3	1910.1000
			J	(Table Z-1)
		TWA value	25 ppm	29 CFR
			100 mg/m3	1910.1000
				(Table Z-1-A)
		TWA	20 ppm	CA AB OEL
			80 mg/m3	
		STEL	50 ppm	CA AB OEL
			200 mg/m3	
		TWA	20 ppm	CA BC OEL
		STEL	50 ppm	CA BC OEL
		TWAEV	25 ppm	CA QC OEL
			100 mg/m3	
		TWA	20 ppm	ACGIH
		STEL	50 ppm	ACGIH
zinc oxide	1314-13-2	TWA value	2 mg/m3	ACGIHTLV
		(Respirable	3	
		fraction)		
		STEL value	10 mg/m3	ACGIHTLV
		(Respirable		
		fraction)		
		REL value	5 mg/m3	NIOSH
		(fumes/smok		
		e)		
		REL value	5 mg/m3	NIOSH
		(dust)		
		STEL value	10 mg/m3	NIOSH
		(fumes/smok		
		e)		
		Ceil_Time	15 mg/m3	NIOSH
		(dust)		
		PEL (Total	15 mg/m3	29 CFR
		dust)		1910.1000
				(Table Z-1)
		PEL (Respir-	5 mg/m3	29 CFR
		able fraction)		1910.1000
				(Table Z-1)



MasterProtect P 8100AP

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

PEL (fumes/smok e)					
(fumes/smok e)			PEL	5 mg/m3	29 CFR
e) (Table Z-1) TWA value (furmes/smok e) (29 CFR 1910.1000 (Table Z-1-0) TWA value (Respirable fraction) (Table Z-1-A) TWA value (Respirable fraction) (Table Z-1-A) TWA value (Total dust) (10 mg/m3 29 CFR 1910.1000 (Table Z-1-A) STEL value (furmes/smok e) (10 mg/m3 29 CFR 1910.1000 (Table Z-1-A) STEL value (furmes/smok e) (10 mg/m3 29 CFR 1910.1000 (Table Z-1-A) TWA (Respirable) (10 mg/m3 29 CFR 1910.1000 (Table Z-1-A) TWA (Respirable) (10 mg/m3 29 CA AB OEL 1910.1000 (Table Z-1-A) TWA (Respirable) (10 mg/m3 20 CA AB OEL 1910.1000 (Table Z-1-A) TWA (Respirable) (10 mg/m3 20 CA BC OEL 1910.1000 (Table Z-1-A) STEL (Respirable) (10 mg/m3 20 CA BC OEL 1910.1000 (Table Z-1-A) TWAEV (Grumes) (10 mg/m3 20 CA OC OEL 1910.1000 (Table Z-1-A) TWAEV (Furmes) (10 mg/m3 20 CA OC OEL 1910.1000 (Table Z-1-A) TWA (Respirable particulate matter) (10 mg/m3 20 CA OC OEL 1910.1000 (Table Z-1-A) STEL (Respirable particulate matter) (10 mg/m3 20 CA OC OEL 1910.1000 (Table Z-1-A) TWA value (100 ppm ACGIHTLV PEL 100 ppm ACGIHTLV PE				59,	
TWA value (fumes/smok e)			,		
(fumes/smok e)				F/ 0	
P				5 mg/m3	
TWA value (Respirable fraction)			`		
Respirable firaction 1910.1000 (Table Z-1-A)			e)		(Table Z-1-A)
Respirable fraction (Table Z-1-A)			TWA value	5 mg/m3	29 CFR
fraction (Table Z-1-A)			(Respirable		1910.1000
TWA value (Total dust)					
(Total dust)				10 mg/m2	•
STEL value (fumes/smok e)				10 mg/ms	
STEL value (fumes/smok e)			(Total dust)		
(fumes/smok e)					
Part Carlot Car				10 mg/m3	
TWA (Respirable) STEL (Respirable) TWA (Respirable)			(fumes/smok		1910.1000
TWA (Respirable) STEL (Respirable) TWA (Respirable)			e)		(Table Z-1-A)
Dirable STEL (Respirable TWA (Respirable TWA (Respirable TWA (Respirable TWA (Respirable TWA (Respirable TWA (Respirable TWAEV STEL (Respirable TWAEV STEL (Respirable TWAEV STEL (Respirable TWAEV STEV TWA (Respirable particulate matter STEL (Respirable particulate matter STEL (Respirable particulate matter STEL (Respirable particulate matter TWA (Respirable particulate matter TWA (Respirable particulate matter TWA (Respirable particulate matter TWA (RESPIRABLE (RE				2 ma/m3	
STEL (Respirable)				g/o	S, (, L) OLL
pirable TWA (Respirable TWA (Respirable TWA (Respirable TWA (Respirable TWA (Respirable TWAEV TWAEV TWAEV (Fumes TWAEV (total dust) TWAEV (total dust) TWAEV (Fumes TWAEV (Fume				10 m = /m 2	CAADOE
TWA (Respirable)				io mg/ma	CA AB OEL
pirable STEL (Respirable) STEL (Respirable) STEL (Respirable) STEL (Respirable) STEV (Fumes) STEV (Fumes) STEV (Fumes) STEV (Fumes) STEV (Fumes) STEV (Fumes) STEL (Respirable particulate matter) STEL (Respirable particulate matter) STEL (Respirable particulate matter) STEL value STEV (STEV Value STEV VALUE VAL				ļ	
STEL (Respirable)				2 mg/m3	CA BC OEL
pirable TWAEV (Fumes 5 mg/m3 CA QC OEL (Fumes TWAEV (total dust) 10 mg/m3 CA QC OEL					
pirable TWAEV (Fumes 5 mg/m3 CA QC OEL (Fumes TWAEV (total dust) 10 mg/m3 CA QC OEL			STEL (Res-	10 mg/m3	CA BC OEL
TWAEV (Fumes)					
(Fumes) TWAEV (total dust) TWAEV (total dust) TWA (Respirable particulate matter) TWA (Respirable particulate matter) TWA value TWA value TWA (RESPIRATION OF MATTER STEL Value TWA (RESPIRATION OF MATTER STEL Value TWA VAIDE				5 mg/m3	CA OC OFI
TWAEV (to-tal dust)				o mg/mo	071 00 022
tal dust) STEV 10 mg/m3 CA QC OEL				10	CA OC OF!
STEV (Fumes)				10 mg/m3	CA QC OEL
(Fumes) TWA (Respirable particulate matter) 2 mg/m3 ACGIH STEL (Respirable particulate matter) 10 mg/m3 ACGIH xylene 1330-20-7 TWA value 100 ppm ACGIHTLV STEL value 150 ppm ACGIHTLV PEL 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1) TWA value 100 ppm 29 CFR 435 mg/m3 1910.1000 STEL value 150 ppm 29 CFR 655 mg/m3 1910.1000 (Table Z-1-A) REL value 100 ppm 435 mg/m3 NIOSH STEL value 150 ppm NIOSH STEL value 150 ppm NIOSH					
TWA (Respirable particulate matter) STEL (Respirable particulate matter) STEL (Respirable particulate matter) xylene 1330-20-7 TWA value 100 ppm ACGIHTLV STEL value 150 ppm ACGIHTLV PEL 100 ppm 435 mg/m3 1910.1000 (Table Z-1) TWA value STEL value STEL value 150 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1-A) STEL value STEL value 150 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1-A) STEL value 150 ppm 655 mg/m3 NIOSH STEL value STEL value 150 ppm 435 mg/m3 STEL value 150 ppm 435 mg/m3				10 mg/m3	CA QC OEL
pirable particulate matter) STEL (Respirable particulate matter) Xylene			(Fumes)		
pirable particulate matter) STEL (Respirable particulate matter) STEL (Respirable particulate matter) STEL value 100 ppm ACGIHTLV			TWA (Res-	2 mg/m3	ACGIH
ticulate matter) STEL (Respirable particulate matter) xylene 1330-20-7 TWA value 150 ppm ACGIHTLV PEL 100 ppm AS5 mg/m3 1910.1000 (Table Z-1-A) STEL value 150 ppm 655 mg/m3 NIOSH STEL value STEL value 150 ppm ACGIHTLV PEL 100 ppm ASS mg/m3 NIOSH NIOSH			pirable par-		
ter) STEL (Respirable particulate matter) 10 mg/m3 ACGIH xylene 1330-20-7 TWA value 100 ppm ACGIHTLV STEL value 150 ppm ACGIHTLV PEL 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1) TWA value 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1-A) STEL value 150 ppm 29 CFR 655 mg/m3 1910.1000 (Table Z-1-A) REL value 100 ppm NIOSH STEL value 150 ppm NIOSH STEL value 150 ppm NIOSH					
STEL (Respirable particulate matter) Xylene 1330-20-7 TWA value 100 ppm ACGIHTLV					
Dirable particulate matter)				10 mg/m2	ACCIH
Ticulate matter) xylene 1330-20-7 TWA value 100 ppm ACGIHTLV				TO HIG/IIIS	ACGIN
xylene 1330-20-7 TWA value 100 ppm ACGIHTLV STEL value 150 ppm ACGIHTLV PEL 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1) TWA value 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1-A) STEL value 150 ppm 29 CFR 655 mg/m3 1910.1000 (Table Z-1-A) REL value 100 ppm NIOSH STEL value 150 ppm NIOSH STEL value 150 ppm NIOSH					
xylene 1330-20-7 TWA value 100 ppm ACGIHTLV STEL value 150 ppm ACGIHTLV PEL 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1) TWA value 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1-A) STEL value 150 ppm 29 CFR 655 mg/m3 1910.1000 (Table Z-1-A) REL value 100 ppm NIOSH STEL value 150 ppm NIOSH STEL value 150 ppm NIOSH					
STEL value					
STEL value 150 ppm ACGIHTLV PEL 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1) TWA value 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1-A) STEL value 150 ppm 29 CFR 655 mg/m3 1910.1000 (Table Z-1-A) REL value 100 ppm NIOSH 435 mg/m3 STEL value 150 ppm NIOSH 655 mg/m3 NIOSH	xylene	1330-20-7		100 ppm	ACGIHTLV
PEL 100 ppm 29 CFR 1910.1000 (Table Z-1) TWA value 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1-A) STEL value 150 ppm 29 CFR 655 mg/m3 1910.1000 (Table Z-1-A) REL value 100 ppm NIOSH REL value 150 ppm NIOSH STEL value 150 ppm NIOSH			STEL value		
A35 mg/m3					
TWA value			'		
TWA value 100 ppm 29 CFR 435 mg/m3 1910.1000 (Table Z-1-A) STEL value 150 ppm 29 CFR 655 mg/m3 1910.1000 (Table Z-1-A) REL value 100 ppm 435 mg/m3 STEL value 150 ppm 655 mg/m3 NIOSH				TOO IIIg/IIIO	
## A35 mg/m3			T) A / A - 1 -	400	
STEL value			I vv A value		
STEL value				435 mg/m3	
655 mg/m3					
655 mg/m3			STEL value	150 ppm	29 CFR
REL value					1910.1000
REL value 100 ppm 435 mg/m3 STEL value 150 ppm NIOSH 655 mg/m3					
435 mg/m3 STEL value 150 ppm NIOSH 655 mg/m3			RFI value	100 nnm	
STEL value 150 ppm NIOSH 655 mg/m3			INEL VAIUE		INIOSIT
655 mg/m3			OTEL		NIOCUI
			SIEL value		NIOSH
TMA 100 nnm 10A AB OF					
			TWA	100 ppm	CA AB OEL
434 mg/m3					



MasterProtect P 8100AP

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

		STEL	150 ppm 651 mg/m3	CA AB OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		STEV	150 ppm 651 mg/m3	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
aluminium oxide	1344-28-1	TWA value (Respirable fraction)	1 mg/m3	ACGIHTLV
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	CA AB OEL
		TWAEV (to-	10 mg/m3	CA QC OEL
		tal dust)	(Aluminum)	
		TWA (Res- pirable)	1 mg/m3 (Aluminum)	CA BC OEL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		TWAEV (fi- bers)	1 fibres per cubic centimeter	CA QC OEL
		TWAEV (respirable dust)	3 mg/m3	CA QC OEL
		TWA	0.1 fibres per cubic centimeter	CA BC OEL
		TWA (Res- pirable par- ticulates)	2 mg/m3	CA AB OEL
		TWA (Res- pirable)	2 mg/m3	CA BC OEL
		TWA	2 fibres per cubic centimeter	CA ON OEL
		TWA (Res- pirable frac- tion)	2 mg/m3	CA ON OEL



MasterProtect P 8100AP

Version **Revision Date:** SDS Number: Date of last issue: -

07/15/2020 000000261398 Date of first issue: 07/15/2020 1.0

TWA	0.1 fibres per cubic centimeter	ACGIH
TWA (Respirable particulate matter)	2 mg/m3	ACGIH

Engineering measures No applicable information available.

Personal protective equipment

Respiratory protection When workers are facing concentrations above the occupa-

tional exposure limits they must use appropriate certified

respirators.

Hand protection

The suitability for a specific workplace should be discussed Remarks

with the producers of the protective gloves.

Eye protection Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures Avoid contact with the skin, eyes and clothing.

> In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

liquid Appearance

Color gray

Odor solvent

pΗ neutral to slightly alkaline

Freezing point No applicable information available.

79.44 - 141.11 °C **Boiling point**

MBCC GROUP

MasterProtect P 8100AP

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

Flash point : 4.44 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper

flammability limit

13.7 %(V)

Lower explosion limit / Lower

flammability limit

1.0 %(V)

Relative vapor density : Heavier than air.

Relative density : 2.04

Density : 2.04 g/cm3 (20 °C)

approx. 16.97 lb/USg (20 °C)

Solubility(ies)

Solubility in other solvents : No applicable information available.

Autoignition temperature : No data available

Viscosity

Viscosity, kinematic : No applicable information available.

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong bases

Strong acids Oxidizing agents

Hazardous decomposition

products

carbon oxides



MasterProtect P 8100AP

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Auditory organ) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Product:

General Information : Remarks: According to experience, the product is considered

to be harmless to health if used in the correct manner.

Further information

Product:

Remarks : Solvents may degrease the skin.

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

zinc:

Partition coefficient: n-

octanol/water

Remarks: The value has not been determined because the

substance is inorganic.

Methylethylketone:

Partition coefficient: n-

octanol/water

log Pow: 0.29

Method: other (measured)

GLP: no data

Remarks: Information taken from reference works and the

literature.

xylene:

Partition coefficient: n-

octanol/water

: log Pow: 3.12 - 3.20 (25 °C) Method: other (calculated)

GLP: no

Remarks: Information taken from reference works and the

literature.

ethylbenzene:

Partition coefficient: n-

octanol/water

: Pow: 4,170 (20 °C) log Pow: 3.6 (20 °C)

pH: 7.8

Method: Partition coefficient

GLP: yes

cyclohexanone:

Partition coefficient: n-

octanol/water

log Pow: 0.86 (25 °C)

Method: Partition coefficient (n-octanol/water), Shake-flask

method GLP: no

talc:



MasterProtect P 8100AP

Version **Revision Date:** SDS Number: Date of last issue: -

07/15/2020 000000261398 Date of first issue: 07/15/2020 1.0

Partition coefficient: n-

octanol/water

Remarks: not applicable

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number **UN 1139**

COATING SOLUTION Proper shipping name

(METHYLETHYLKETONE,)

Class 3 Packing group Ш Labels 3

IATA-DGR

UN/ID No. UN 1139

Proper shipping name **COATING SOLUTION**

Class 3 Packing group Ш

Flammable Liquids Labels

Packing instruction (cargo

aircraft)

Packing instruction (passen-

353

364

ger aircraft)

IMDG-Code

UN number UN 1139

COATING SOLUTION Proper shipping name



MasterProtect P 8100AP

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

(METHYLETHYLKETONE,)

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1139

Proper shipping name : COATING SOLUTION

Class : 3
Packing group : II
Labels : 3
ERG Code : 127
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1) 1910.1000

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)

29 CFR 1910.1000 (Table Z- : Short Term Exposure Limit (STEL):

Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

1-A) / STEL value

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value : Time Weighted Average (TWA):
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average CA BC OEL / STEL : short-term exposure limit

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

NIOSH / Ceil_Time : Ceiling Limit Value and Time Period (if specified):

NIOSH / REL value : Recommended exposure limit (REL): NIOSH / STEL value : Short Term Exposure Limit (STEL):

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 07/15/2020



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/15/2020 000000261398 Date of first issue: 07/15/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

CA / EN