

9 | 09 67 23
 Resinous
 Flooring

MasterTop[®] SRS 40TC

Multi-purpose, flexible methyl-methacrylate resin
 for use as a primer, overlay or topcoat

FORMERLY SRS DEGADUR[®] 410

PACKAGING

4.5 Gallon (17 L) Pail
 53.5 Gallon (202.5 L) Drum Color

YIELD

All coverage rates are approximate. Coverage rates will vary with the desired texture and porosity of substrate. Please refer to individual flooring system data sheets for coverage rate information.

COLOR

Clear - See Performance Flooring Color Guide for pigment color offerings.

SHELF LIFE

2 years when properly stored

STORAGE

Keep stored in cool, dry environment, and out of direct sunlight.

VOC CONTENT

0 g/L less water and exempt solvents

DESCRIPTION

MasterTop SRS 40TC is a methyl-methacrylate (MMA) resin for use within the MasterTop SRS flooring systems. MasterTop SRS 40TC is a solvent free, 2-component, 100% reactive resin that can be utilized as a primer, overlay or topcoat within a flooring system. MasterTop SRS 102AP bond promoter can be utilized with the MasterTop SRS 40TC as a suitable primer for metal substrate applications. MasterTop SRS 40TC can also be mixed with the MasterTop F 100SL to create a self-leveling formulation that reduces application time. MasterTop SRS 40TC is a transparent resin that can be pigmented using the MasterTop PGM 155.

PRODUCT HIGHLIGHTS

- Fully cures in one hour with proper application, reducing downtime for a quick return to service
- Flexible resin is ideal for areas encountering temperature changes
- Can be applied at -20° F (-29° C) to meet a wide range of application and timing requirements
- Primes to metal substrates when used with MasterTop SRS 102AP
- Please refer to individual flooring system data sheets for application instructions.
- Every MasterTop SRS flooring system is a multiple component system that utilizes a methyl-methacrylate (MMA) resin. It is critical that the instructions listed in the Safety Data Sheet and on the product label for every component of the system be read, understood and followed. MMA resins are flammable liquids in their uncured state. Smoking, open flames or sparks should not be permitted during the handling of the product. Explosion safe ventilation must be used during the application to minimize vapor collection in the installation area and to improve overall air quality for the crew. All foodstuffs must be removed during installation of the flooring system.

APPLICATIONS

- Used as a primer within the following MasterTop SRS flooring systems:
 - Metal substrates using the HP Bond Promoter
- Used as an overlay within the following MasterTop SRS flooring systems:
 - MasterTop 1841 SRS CF
 - MasterTop 1843 SRS CQ
 - MasterTop 1845 SRS CP
 - MasterTop 1851 SRS CF
- Used as a topcoat within the following MasterTop SRS flooring systems:
 - MasterTop 1823 SRS CQ

Technical Data

Composition

MasterTop SRS 40TC contains cement, graded sand, and proprietary additives.

Test Data

| PROPERTY | RESULTS | TEST METHOD |
|----------------------------------|-------------|-------------|
| Percentage Reactive Resin, % | 100 | Lab Method |
| Percentage Solids, % | 100 | |
| Water Absorption, (% / 24 hours) | < 0.1% | ASTM D570 |
| Tensile Strength, psi (MPa) | 1,350 (9.3) | ASTM D638 |
| Elongation @ Break | 140 | ASTM D638 |
| Hardness, (Shore D) | 61 | ASTM D2240 |
| Viscosity, cps | 450 – 550 | ASTM D2393 |

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.master-builders-solutions.com/en-us, e-mailing your request to mbsbscst@mbcc-group.com or calling 1(800)433-9517. Use only as directed.

IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.

LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.

Master Builders Solutions Construction Systems US, LLC

889 Valley Park Drive, Shakopee, MN 55379
www.master-builders-solutions.com/en-us

Customer Service +1 (800) 433-9517
Technical Service +1 (800) 243-6739

