

The listed systems are typical applications only. Please refer to the volume of your 3M specification guide for your specific application or use the 3M System Selector available at 3M.com/firestop

Fire Barrier Water Tight Sealants & Tape

3M™ Fire Barrier Water Tight Sealant 3000 WT

3M™ Fire Barrier Water Tight Sealant 3000 WT Intumescent Sealant forms an effective barrier to fire and water in through penetrations. This high-performance sealant helps prevent water and moisture intrusion while protecting buildings and their occupants by preventing the spread of fire, smoke and toxic gas.

- Intumescent silicone for use in systems with a firestop rating up to 4 hours when tested in accordance with ASTM E 814 (UL1479)
- Meets UL Water Leakage Test, W Rating: Class 1 requirements for systems tested in accordance with ANSI/UL 1479
- Helps prevent moisture and water migration through a building
- Minimizes noise transfer: STC-rating of 53 when tested in STC 54-rated wall assembly
- Excellent weathering properties
- Ideal for fast-track construction
- Easy application with standard caulking gun or pneumatic pump
- Excellent bonding
- Gray color with black flecks



FIRE BARRIER	SMOKE SEAL	WATER BARRIER	SOUND BARRIER
UP TO 4 HOUR Fire Protection	L RATED Meets Optional L Requirements	CLASS 1W Rating UL Water Leakage	STC 53 In STC 54-rated Wall Assembly



3M™ Fire Barrier Water Tight Sealant 1000 NS and 3M™ Fire Barrier Water Tight Sealant 1003 SL

3M™ Fire Barrier Water Tight Sealant 1000 NS (non-slump) and 3M™ Fire Barrier Water Tight Sealant 1003 SL Silicone Sealant (self-leveling) are ready to use, one-component silicone elastomers. Both cure upon exposure to atmospheric humidity to form a flexible seal. Both sealants remain elastomeric and are weather resistant. They bond to most common construction materials.

- Firestop tested up to 3 hours in accordance with ASTM E 814 (UL 1479)
- Joint System Fire Resistance tested in accordance with ASTM E 1966 (UL 2079)
- Meets UL Water Leakage Test, W Rating: Class 1 requirements
- Minimizes noise transfer: STC-rating of 56 when tested in STC 56-rated wall assembly
- ±25% dynamic joint movement capability
- Excellent adhesion
- Cures upon exposure to atmospheric humidity
- Applied with conventional caulking equipment
- Re-enterable/repairable
- Aids in the prevention of moisture and water migration through a building
- Light gray color



FIRE BARRIER	WATER BARRIER	SMOKE SEAL	SOUND BARRIER	ELASTOMERIC
UP TO 3 HOUR Fire Protection	CLASS 1W Rating UL Water Leakage	L RATED Meets Optional L Requirements	STC 56 In STC 56-rated Wall Assembly	± 25% Movement Capability



3M™ Fire and Water Barrier Tape FWBT

3M™ Fire and Water Barrier Tape is a self-adhered membrane that provides a tough, elastomeric coating. This product has a unique pressure sensitive adhesive that aggressively sticks and stays stuck to a wide variety of substrates at both high and low temperatures, and will even adhere to damp surfaces.

- Up to 4-hour fire protection in construction joints per ASTM E 1966 (UL 2079)
- Up to 3-hour fire protection in perimeter joints per ASTM E 2307
- Up to 2-hour fire protection in through-penetration applications per ASTM E 814 (UL 1479)
- Elastic material maintains performance with up to ±50% movement capabilities
- Can be installed in temperatures as low as 0°F (18°C) and as high as 120°F (49°C)



Construction Joint Spray & Sealants (cont.)

3M™ Fire Barrier Water Tight Sealant 1000 NS and 3M™ Fire Barrier Water Tight Sealant 1003 SL

3M™ Fire Barrier Water Tight Sealant 1000 NS (non-slump) and 3M™ Fire Barrier Water Tight Sealant 1003 SL Silicone Sealant (self-leveling) are ready to use, one-component silicone elastomers. Both cure upon exposure to atmospheric humidity to form a flexible seal. Both sealants remain elastomeric and are weather resistant. They bond to most common construction materials.

- Firestop tested up to 3 hours in accordance with ASTM E 814 (UL 1479)
- Joint System Fire Resistance tested in accordance with ASTM E 1966 (UL 2079)
- Meets UL Water Leakage Test, W Rating: Class 1 requirements
- Minimizes noise transfer: STC-rating of 56 when tested in STC 56-rated wall assembly
- ±25% dynamic joint movement capability
- Excellent adhesion
- Cures upon exposure to atmospheric humidity
- Applied with conventional caulking equipment
- Re-enterable/repairable
- Aids in the prevention of moisture and water migration through a building
- Light gray color



FIRE BARRIER	WATER BARRIER	SMOKE SEAL	SOUND BARRIER	ELASTOMERIC
UP TO 3 HOUR Fire Protection	MEETS CLASS 1W Rating UL Water Leakage	L RATED Meets Optional L Requirements	STC 56 In STC 56-rated Wall Assembly	± 25% Movement Capability

3M™ Fire Barrier Watertight Spray













3M™ Fire Barrier Watertight Spray is a sprayable, moisture-curing hybrid siliconized polymer that forms a tough, elastomeric coating. This material is used to firestop perimeter joints (curtain wall) and construction joints.

- Up to 3-hour fire protection in construction joints per ASTM E 1966 (UL 2079)
- Up to 3-hour fire protection in perimeter joints per ASTM E 2307
- Elastic material maintains performance with up to ±10% movement capabilities
- Paintable with primer
- Broad range of applications (extensive portfolio of tested and listed building and perimeter joint systems)
- Improved spraying pattern: applied with conventional airless spray equipment
- Robust jobsite formula (freeze/thaw resistant and uniform seal formation in hot or cold conditions)



3M™ Fire Protection Products







3M™ Fire Barrier Water Tight Sealants and Spray (W-Rated) (cont.)

Product Number	Description	Size	Color	Unit	Billing UPC Number	Qty.	Price Unit
1003 SL 	Self-Leveling Silicone (Up to 3-hr Penetration/Joint Firestop)	10.1 oz.		 Tube	0-00-51115-11538-7	12/Cs	Each
	Self-Leveling Silicone (Up to 3-hr Penetration/Joint Firestop)	20 oz.		 Sausage	0-00-51115-18789-6	12/Cs	Each
	Self-Leveling Silicone (Up to 3-hr Penetration/Joint Firestop)	4.5 gal.		 Pail	5-00-51115-11540-5	1/Cs	Each
Watertight Spray 	Moisture-curing hybrid silicized polymer (Up to 3-hr Penetration/Joint Firestop)	5 gal.		 Pail	0-00-76308-98232-4	1/Cs	Each
	Moisture-curing hybrid silicized polymer (Up to 3-hr Penetration/Joint Firestop)	5 gal.		 Pail	0-00-76308-86113-1	1/Cs	Each

3M™ Fire and Water Barrier Tape FWBT

Product Number	Description	Size	Unit	Billing UPC Number	Qty.	Price Unit
FWBT2	Used to firestop perimeter joints (curtain wall), construction joints, and through penetration openings Up to 4-hour fire protection in construction joints	2" x 75' (51 mm x 22.8 m)	Rolls	0-00-76308-86899-4	24/Cs	Each
FWBT3		3" x 75' (76 mm x 22.8 m)	Rolls	0-00-76308-14448-7	16/Cs	Each
FWBT4		4" x 75' (101 mm x 22.8 m)	Rolls	0-00-76308-86900-7	12/Cs	Each
FWBT6		6" x 75' (152 mm x 22.8 m)	Rolls	0-06-38060-13883-0	8/Cs	Each
FWBT8		8" x 75' (202 mm x 22.8 m)	Rolls	0-00-76308-86901-4	4/Cs	Each
FWBT12		12" x 75' (303 mm x 22.8 m)	Rolls	0-00-76308-86902-1	4/Cs	Each

3M™ Fire Barrier Pass-Through Devices and Accessories

Product	Product Number	Description	Shipping Wt./Carton	Billing UPC Number	Qty.	Price Unit
Square Device 	PT4SD	4 in. Square Re-enterable Firestop Device (Up to 4-hr Firestop)	13.6 lbs.	0-00-51115-16597-9	6/Cs	Each
	Round Device 	PT2RD	2 in. Round Re-enterable Firestop Device (Up to 4-hr Firestop)	7.7 lbs.	0-00-51115-18773-5	6/Cs
PT4RD		4 in. Round Re-enterable Firestop Device (Up to 4-hr Firestop)	12.4 lbs.	0-00-51115-16598-6	6/Cs	Each
Product Accessories						
Single Mounting Brackets 	PT4SMB	For use with 4 in. Square Device	16.4 lbs.	0-00-51115-18752-0	24 Pair/Cs	Pair
	PT2RMB	For use with 2 in. Round Device	11.6 lbs.	0-00-51115-18774-2	24 Pair/Cs	Pair
	PT4RMB	For use with 4 in. Round Device	10.3 lbs.	0-00-51115-18754-4	24 Pair/Cs	Pair
Triplex Mounting Bracket 	PT4TMB	Gang up to three 4 in. Square Devices	29.1 lbs.	0-00-51115-18753-7	24 Pair/Cs	Pair
Sixplex Mounting Bracket 	PT4SSMB	Gang up to six 4 in. Square Devices	9.5 lbs.	0-00-51115-18777-3	6 Pair/Cs	Pair
Foam Plugs 	PT4SRP	For use with 4 in. Square Device	1.3 lbs.	0-00-51115-18794-0	24/Cs	Each
	PT2RRP	For use with 2 in. Round Device	0.4 lbs.	0-00-51115-18793-3	24/Cs	Each
	PT4RRP	For use with 4 in. Round Device	0.8 lbs.	0-00-51115-18791-9	24/Cs	Each