

Tinted Primer

100% acrylic-based primer

DESCRIPTION

100% acrylic-based primer

COLORS

Available in standard and custom colors.

PACKAGING

24.9 kg per 19-liter pail
(55 lbs per 5-gallon pail)

COVERAGE

Approximate coverage rate:
69.6–116.1 m² (750–1,250 ft²) per pail.
Coverage will vary greatly depending on porosity and condition of surface.

POINT OF SALE TINTING

The maximum pigment load should not exceed 50% of the equivalent finish formula.

SHELF LIFE

Shelf life is two years when unopened and stored as directed.

STORAGE

Store Master Builders Solutions materials in a cool, dry place protected from freezing. Store at no less than 4 °C (40 °F). Protect from extreme heat and direct sunlight.

USES

1. Master Builders Solutions Tinted Primer helps alleviate finish shadowing and enhances performance of the wall systems. For optimum results, Tinted Primer should closely match the color of the selected finish.
2. Master Builders Solutions Tinted Primer is also used when preparing substrates such as poured concrete, unit masonry, veneer plaster, or gypsum wall board (interior only) prior to application of finish.

MIXING

1. Thoroughly mix the factory-prepared Master Builders Solutions Tinted Primer with a paddle and drill to a uniform consistency.
2. A small amount of clean, potable water may be added to adjust workability. (Do not exceed 10 oz of water per 5 gallon pail.)
3. Additives are not permitted.
4. Close container when not in use.
5. Clean tools with soap and water immediately after use.

APPLICATION

1. Substrate shall be clean, dry, sound and free of releasing agents, paint, contaminants or other residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4 mm in 3 m (1/4" in 10').
2. Apply Master Builders Solutions Tinted Primer to substrate with a sprayer, 10 mm (3/8") nap roller, or good quality latex paint brush at a rate of approximately 69.6–116.1 m² (750–1,250 ft²).
3. Master Builders Solutions Tinted Primer shall be dry to the touch. Wait at least 24 hours before proceeding to the finish application.

FEATURES

Reduced suction by cement base coats and cementitious substrates

Tinted to match finish color

Improved water resistance

BENEFITS

Improves workability of finish application

Creates better final appearance, alleviates shadowing of light-colored, rilled finishes

Reduces chances of efflorescence in stucco and other cementitious substrates

TECHNICAL INFORMATION

Consult our Technical Services Department for specific recommendations concerning all other applications. Consult the Wall Systems' website, www.master-builders-solutions.com/en-us, for additional information about products and systems and for updated literature.

LIMITATIONS

1. Protect Master Builders Solutions materials during transportation and installation to avoid physical damage.
2. Store Master Builders Solutions materials in a cool, dry place protected from freezing. Store at no less than 4 °C (40 °F). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.
3. Do not apply Master Builders Solutions materials in ambient temperature below 4 °C (40 °F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4 °C (40 °F) prevail.
4. Do not apply Master Builders Solutions materials to frozen surfaces.
5. Do not exceed 10 oz of water per 5 gallon pail.

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.master-builders-solutions.com/en-us, e-mailing your request to mbsbcst@mbcc-group.com or calling +1 (800) 433-9517. Use only as directed.

IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.

LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control.

MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.

For the most current version of this literature, please visit our website at www.master-builders-solutions.com/en-us.