

Revision Date: 04/05/2019

SAFETY DATA SHEET

1. Identification

Material name: POWERply STANDARD

Material: 036STSM601

Recommended use and restriction on use

Recommended use: Article Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122

US

Contact person: EH&S Department Telephone: 216-292-5000

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Category 1A Carcinogenicity Specific Target Organ Toxicity -Category 1¹ Repeated Exposure

Target Organs

1. Lung

Unknown toxicity - Health

Acute toxicity, oral 61.33 % 69.14 % Acute toxicity, dermal Acute toxicity, inhalation, vapor 100 % Acute toxicity, inhalation, dust 99.99 % or mist

Label Elements

Hazard Symbol:



Signal Word: Danger



Revision Date: 04/05/2019

Hazard Statement: May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this

product.

Response: IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|---|------------|-------------------------|
| Calcium Carbonate (Limestone) | 1317-65-3 | 20 - <50% |
| Asphalt | 8052-42-4 | 20 - <50% |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 | 10 - <20% |
| Magnesite | 546-93-0 | 5 - <10% |
| Fibrous Glass | 65997-17-3 | 1 - <5% |

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. Get medical attention if

symptoms occur.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.



Revision Date: 04/05/2019

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions,

protective equipment and emergency procedures:

No data available.

Methods and material for containment and cleaning

up:

Collect spillage in containers, seal securely and deliver for disposal

according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood.

Obtain special instructions before use. Use personal protective equipment as required. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in

case of handling which causes formation of dust.



Revision Date: 04/05/2019

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| occupational Exposure L | | | |
|--|---------|-----------------------|--|
| Chemical Identity | Туре | Exposure Limit Values | Source |
| Calcium Carbonate | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air |
| (Limestone) - Total dust. | | · · | Contaminants (29 CFR 1910.1000) (02 2006) |
| Calcium Carbonate | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air |
| (Limestone) - Respirable | | | Contaminants (29 CFR 1910.1000) (02 2006) |
| fraction. | | | |
| Asphalt - Inhalable fume as | TWA | 0.5 mg/m3 | US. ACGIH Threshold Limit Values (03 2018) |
| benzene solubles | | | |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable | TWA | 0.025 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| fraction. | | | |
| Crystalline Silica (Quartz)/ | TWA | 0.05 mg/m3 | US. OSHA Specifically Regulated Substances |
| Silica Sand - Respirable dust. | | - | (29 CFR 1910.1001-1053) (03 2016) |
| - | OSHA_AC | 0.025 mg/m3 | US. OSHA Specifically Regulated Substances |
| | T | | (29 CFR 1910.1001-1053) (03 2016) |
| Crystalline Silica (Quartz)/ | PEL | 0.05 mg/m3 | US. OSHA Table Z-1 Limits for Air |
| Silica Sand - Respirable dust. | | | Contaminants (29 CFR 1910.1000) (03 2016) |
| Crystalline Silica (Quartz)/ | TWA | 2.4 millions | US. OSHA Table Z-3 (29 CFR 1910.1000) |
| Silica Sand - Respirable. | | of particles | (2000) |
| | | per cubic foot | |
| | TMA | of air | LIC OCUA Table 7.2 (20 CED 1010 1000) |
| | TWA | 0.1 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Magnesite - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Magnesite - Respirable | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air |
| fraction. | | ŭ | Contaminants (29 CFR 1910.1000) (02 2006) |
| Fibrous Glass - Inhalable fraction. | TWA | 5 mg/m3 | US. ACGIH Threshold Limit Values (03 2014) |
| Fibrous Glass - Fiber. | TWA | 1 fibers/cm3 | US. ACGIH Threshold Limit Values (03 2018) |
| | TWA | 1 fibers/cm3 | US. ACGIH Threshold Limit Values (03 2018) |
| | TWA | 1 fibers/cm3 | US. ACGIH Threshold Limit Values (03 2018) |
| | TWA | 1 fibers/cm3 | US. ACGIH Threshold Limit Values (03 2018) |
| | TWA | 1 fibers/cm3 | US. ACGIH Threshold Limit Values (03 2018) |
| | TWA | 0.2 | US. ACGIH Threshold Limit Values (03 2018) |
| | | fibers/cm3 | |

| Chemical name | Туре | Exposure Limit Values | Source |
|--|------|-----------------------|---|
| Calcium Carbonate (Limestone) - Total dust. | STEL | 20 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |



TREMCO.

Version: 1.1

Revision Date: 04/05/2019

| Calcium Carbonate (Limestone) - Respirable fraction. | TWA | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
|---|-----|--|---|
| Calcium Carbonate (Limestone) - Total dust. | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Asphalt - Aerosol, inhalable as benzene solubles | TWA | 0.5 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Asphalt - Inhalable fraction as benzene solubles | TWA | 0.5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Asphalt - Fume. | TWA | 5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | 0.025 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | 0.10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable dust. | TWA | 0.1 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Magnesite - Total dust. | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Fibrous Glass - Fiber. | TWA | 0.2 fibers/cm3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 1 fibers/cm3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Fibrous Glass - Inhalable fibers. | TWA | 5 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Fibrous Glass - Inhalable fraction. | TWA | 5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Fibrous Glass - Fiber. | TWA | 2 fibres/cm3 (non- asbestos fibres) size restrictions apply | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 1 fibres/cm3 (non- asbestos fibres) size restrictions apply | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Fibrous Glass - fibers, total dust | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Fibrous Glass - Respirable fibers. | TWA | 1 Fibers/cc | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017) |
| | TWA | 0.5 Fibers/cc | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017) |



TREMCO.

Version: 1.1

Revision Date: 04/05/2019

| Chemical name | Туре | Exposure Limit Values | Source |
|---|------|---|---|
| Calcium Carbonate (Limestone) - Total dust. | STEL | 20 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Calcium Carbonate (Limestone) - Respirable fraction. | TWA | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Calcium Carbonate (Limestone) - Total dust. | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Asphalt - Aerosol, inhalable as benzene solubles | TWA | 0.5 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Asphalt - Inhalable fraction as benzene solubles | TWA | 0.5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Asphalt - Fume. | TWA | 5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | 0.025 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | 0.10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable dust. | TWA | 0.1 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Magnesite - Total dust. | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Fibrous Glass - Fiber. | TWA | 0.2 fibers/cm3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 1 fibers/cm3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Fibrous Glass - Inhalable fibers. | TWA | 5 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Fibrous Glass - Inhalable fraction. | TWA | 5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Fibrous Glass - Fiber. | TWA | 2 fibres/cm3 (non- asbestos fibres) size restrictions apply | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 1 fibres/cm3 (non- asbestos fibres) size restrictions apply | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |



Revision Date: 04/05/2019

| Fibrous Glass - fibers, total dust | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
|--|---------|---------------|---|
| Fibrous Glass - Respirable fibers. | TWA | 1 Fibers/cc | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017) |
| | TWA | 0.5 Fibers/cc | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017) |
| Calcium stearate | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Calcium stearate | TWA | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Hydrotreated Oil - Mist. | TWA | 1 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Hydrotreated Oil - Inhalable fraction. | TWA | 5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| | TWA | 5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Hydrotreated Oil - Mist. | TWA | 5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | STEL | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Formaldehyde | TWA | 0.3 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | CEILING | 1 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Formaldehyde | STEL | 1 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | CEV | 1.5 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Formaldehyde | CEILING | 2 ppm 3 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists,

mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing.



Revision Date: 04/05/2019

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: solid
Color: Black
Odor: Slight

Odor threshold:

pH:

No data available.

Flash Point:

No data available.

Evaporation rate:

No data available.

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density:

Relative density:

1.0

Relative density: Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.



Revision Date: 04/05/2019

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition Thermal decomposition or combustion may liberate carbon oxides and

Products: other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: May be harmful in contact with skin.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Asphalt LD 50 (Rat): > 5,000 mg/kg

Magnesite LD 50 (Rat): > 2,000 mg/kg

Fibrous Glass LD 50 (Rat): > 2,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Asphalt LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.



Revision Date: 04/05/2019

Specified substance(s):

Asphalt LC 50 (Rat): > 94.4 mg/m3

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Asphalt in vivo (Rabbit): Not irritant Experimental result, Key study

Magnesite In vitro (Human, in vitro reconstituted epidermis model): Not irritant

Experimental result, Key study

Fibrous Glass in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Asphalt Rabbit, 24 hrs: Not irritating

Magnesite Reconstituted Corneal Epithelium model, 10 min: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.



Revision Date: 04/05/2019

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Asphalt Overall evaluation: Possibly carcinogenic to humans.

Crystalline Silica

(Quartz)/ Silica

Sand

Overall evaluation: Carcinogenic to humans.

Fibrous Glass Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall

evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans. Overall evaluation: Possibly

carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica Known To Be Human Carcinogen.

(Quartz)/ Silica

Sand

Fibrous Glass Reasonably Anticipated to be a Human Carcinogen. Reasonably Anticipated

to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Crystalline Silica

(Quartz)/ Silica

Cancer

Sand

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Repeated Exposure: Lung

Aspiration Hazard

Product: No data available.

Other effects: No data available.

11/17 00000002977



Revision Date: 04/05/2019

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Asphalt NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l Read-across from

supporting substance (structural analogue or surrogate), Key study LL 50 (Oncorhynchus mykiss, 28 d): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.



Revision Date: 04/05/2019

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical IdentityOSHA hazard(s)Crystalline Silicakidney effects(Quartz)/ Silica Sandlung effects

immune system effects

Cancer

Formaldehyde Acute toxicity

Skin irritation Skin sensitization Flammability

respiratory tract irritation Respiratory sensitization

Cancer Eye irritation



Revision Date: 04/05/2019

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

Asphalt 100 lbs. Formaldehyde 100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 302 Extremely Hazardous Substance

Reportable

Chemical Identity quantity Threshold Planning Quantity

Formaldehyde 100 lbs. 500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u> <u>Reportable quantity</u>

Asphalt 100 lbs. Formaldehyde 100 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u> <u>Threshold Planning Quantity</u>

Formaldehyde 500lbs Calcium Carbonate 10000 lbs

(Limestone)

Asphalt 10000 lbs Crystalline Silica (Quartz)/ 10000 lbs

Silica Sand

Magnesite 10000 lbs Fibrous Glass 10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity Reportable quantity

Formaldehyde lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer - www.P65Warnings.ca.gov



Revision Date: 04/05/2019

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium Carbonate (Limestone)

Asphalt

Crystalline Silica (Quartz)/ Silica Sand

Magnesite

Fibrous Glass

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium Carbonate (Limestone)

Asphalt

Crystalline Silica (Quartz)/ Silica Sand

Magnesite

Fibrous Glass

Formaldehyde

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium Carbonate (Limestone)

Asphalt

Crystalline Silica (Quartz)/ Silica Sand

Fibrous Glass

US. Rhode Island RTK

Chemical Identity

Calcium Carbonate (Limestone)

Asphalt

Crystalline Silica (Quartz)/ Silica Sand

Magnesite

Fibrous Glass

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and

: 0 g/l

exempt solvent)

VOC Method 310 : 0.00 %



Revision Date: 04/05/2019

Inventory Status:

Canada DSL Inventory List:

All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List: One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory:

One or more components in this product are

not listed on or exempt from the inventory.

US TSCA Inventory:

All components in this product are listed on or

exempt from the Inventory.

Japan ISHL Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Mexico INSQ: One or more components in this product are

not listed on or exempt from the Inventory.

Ontario Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Taiwan Chemical Substance Inventory:

One or more components in this product are

not listed on or exempt from the Inventory.

Australia AICS: All components in this product are listed on or

exempt from the Inventory.

China Inv. Existing Chemical Substances:

All components in this product are listed on or

exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

All components in this product are listed on or

exempt from the Inventory.

Philippines PICCS: All components in this product are listed on or

exempt from the Inventory.



Revision Date: 04/05/2019

16.Other information, including date of preparation or last revision

Revision Date: 04/05/2019

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.