



PNEUMATIC TOOLS

ROOFING

3 YEAR
Warranty

Coil Roofing Nailer GRTRN45

Applications:

Roofing installation, insulation board, and soft wall sheathing

Includes:

Carrying case, safety glasses, hex wrenches, tool oil, 1/4" male plug, and instruction manual



Features:

- Rotating metal belt hook
- Lightweight, durable aluminum housing
- Nosepiece long life carbide inserts
- Tool-free depth adjustment
- Dual feed pawl system
- Anti-skid grips
- Shingle placement guide
- Vinyl siding attachment available
- 3-year warranty

Specifications:

- Firing Mode: Bump fire
- Magazine Capacity: 120
- Operating Pressure: 70-120 PSI
- Fastener Type: 15° Coil Roofing Nails
- Collation: Wire
- Fastener Length: 7/8" to 1-3/4"
- Height: 10.9"
- Length: 10.5"
- Width: 3.2"
- Weight: 5.04 lb

For best results, use Grip-Rite® collated fasteners

15° Coil Roofing Nails				
Size	Electrogalvanized SKU	Hot Dipped Galvanized SKU	PrimeGuard MAX® Stainless Steel SKU	Pcs./Box
Ring Shank				
1"	N/A	N/A	MAXC62843	7.2M
1-1/4"	GRCR3DRGAL	N/A	MAXC62849	7.2M
1-1/2"	GRCR4DRGAL	N/A	MAXC62854	7.2M
Smooth Shank				
3/4"	GRCR19GAL	N/A	N/A	7.2M
7/8"	GRCR2DCGAL	N/A	MAXC62867	7.2M
1"	GRCR2DGAL	GRCR2DHDG	MAXC62842	7.2M
1-1/4"	GRCR3DGAL	GRCR3DHDG	MAXC62852	7.2M
1-1/2"	GRCR4DGAL	GRCR4DHDG	MAXC62847	7.2M
1-3/4"	GRCR5DGAL	GRCR5DHDG	MAXC62857	7.2M

Additional fasteners and packaging options available, including 1M tubs



Grip-Rite® tools are distributed by PrimeSource Building Products, Inc.

800-676-7777

www.grip-rite.com www.primesourcebp.com

GRTRN45
10/2016



HERRAMIENTAS NEUMÁTICAS

TECHO

Clavadora de bobina GRTRN45 de 15° para revestimiento

3 AÑOS
Garantía

Aplicaciones:

Instalación de techo, tablero aislante y revestimiento suave de pared

Incluye:

Estuche portátil, gafas de seguridad, llaves hexagonales, aceite para herramientas, enchufe macho de 1/4", y manual de instrucciones



Características:

- Gancho rotativo de cinturón
- Carcasa de aluminio liviana y duradera
- Embocadura de larga vida con insertos de carburo
- Ajuste de profundidad sin herramienta
- Sistema de doble trinquete de alimentación
- Agarraderas antirresbalantes
- Accesorio de revestimiento de vinilo disponible
- Garantía de 3 años

Especificaciones:

- Modalidad de disparo: Accionamiento de retroimpacto múltiple
- Capacidad del cargador: 120
- Presión de funcionamiento: 70-120 PSI
- Tipo de sujetador:
Clavos en carrete de 15° para techo
- Secuencia: Alambre
- Largo del sujetador: 7/8" a 1-3/4"
- Alto: 10.9"
- Largo: 10.5"
- Ancho: 3.2"
- Peso de la herramienta: 5.04 lb.



Para mejores resultados,
utilice sujetadores en secuencia Grip-Rite®

Clavos en carrete de 15° para techo

Tamaño	Electro galvanizado SKU	Galvanizado por inmersión en caliente SKU	Acero inoxidable PrimeGuard MAX® SKU	Pzas./Caja
Espiga anillada				
1"	N/A	N/A	MAXC62843	7.2M
1-1/4"	GRCR3DRGAL	N/A	MAXC62849	7.2M
1-1/2"	GRCR4DRGAL	N/A	MAXC62854	7.2M
Espiga lisa				
3/4"	GRCR19GAL	N/A	N/A	7.2M
7/8"	GRCR2DCGAL	N/A	MAXC62867	7.2M
1"	GRCR2DGAL	GRCR2DHDG	MAXC62842	7.2M
1-1/4"	GRCR3DGAL	GRCR3DHDG	MAXC62852	7.2M
1-1/2"	GRCR4DGAL	GRCR4DHDG	MAXC62847	7.2M
1-3/4"	GRCR5DGAL	GRCR5DHDG	MAXC62857	7.2M

Opciones adicionales de sujetadores y empaque disponibles, incluyendo envases de 1M



Las herramientas Grip-Rite son distribuidas por PrimeSource Building Products, Inc.

800-676-7777

www.grip-rite.com www.primesourcebp.com