

FLUID APPLIED AIR/VAPOR BARRIERS

ENVIRO-BARRIER™

Hohmann & Barnard's Enviro-Barrier™ is a single component, fluid applied, elastomeric membrane to provide an air, water and vapor barrier when applied to above-grade wall assemblies. It cures to form a resilient, monolithic, fully-adhered elastomeric membrane which meets & exceeds the highest industry standards for air barrier performance.

Features:

- Remains flexible over a wide temperature range.
- Cost effective, easy spray application.
- Asphalt-free formulation.
- Excellent adhesion to most construction materials including CMU, stone, gypsum board, wood, and metal.

• **ABAA Evaluated**

Product Data

COLOR	Dark blue
SOLIDS BY WEIGHT	65%
WEIGHT PER GALLON	10.2 pounds
COVERAGE RATE	25 sf/gal @ 60 mils wet (40 mils dry)
UV RESISTANCE	Up to 120 days
APPLICATION TEMPERATURE	40° – 120° F
DRY TIME	Tack Free: 2 – 4 hrs Full Cure: 4 – 24 hrs
PERFORMANCE TESTED	<ul style="list-style-type: none"> ■ ASTM E2178 ■ ASTM E96 ■ ASTM E2357 ■ NFPA 285



ENVIRO-BARRIER VP™

Enviro-Barrier VP™ is a single component fluid-applied elastomeric membrane to provide an air and water barrier when applied to above-grade wall assemblies. It cures to form a resilient, monolithic, fully-adhered membrane which resists air leakage and water penetration but allows vapor diffusion.



Product Data

COLOR	Light blue
SOLIDS BY WEIGHT	65%
WEIGHT PER GALLON	10.2 pounds
COVERAGE FOR CMU	60 sf/gal @ 25 mils wet
COVERAGE FOR EXT. SHEATHING	75 sf/gal @ 20 mils wet
UV RESISTANCE	Up to 120 days
APPLICATION TEMPERATURE	40° – 120° F
DRY TIME	Tack Free: 2 – 4 hrs Full Cure: 4 – 24 hrs
PERFORMANCE TESTED	<ul style="list-style-type: none"> ■ ASTM E2178 ■ ASTM E96 ■ ASTM E2357 ■ NFPA 285

* Please contact Hohmann & Barnard's technical department for specifications and test results.