

## MasterEmaco S 440

Version 1.0      Revision Date: 07/16/2020      SDS Number: 000000260156      Date of last issue: -  
Date of first issue: 07/16/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterEmaco S 440  
Product code : 000000000057191334 000000000057191334

**Manufacturer or supplier's details**

Company name of supplier : Master Builders-Admixtures US,LLC  
Address : 23700 CHAGRIN BLVD  
Beachwood OH 44122  
Emergency telephone : ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract  
Number MIS9240420

**Recommended use of the chemical and restrictions on use**

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Skin corrosion/irritation : 2  
Serious eye damage/eye irritation : 1  
Specific target organ toxicity - single exposure : 3 (Respiratory system)  
Short-term (acute) aquatic hazard : 3  
Long-term (chronic) aquatic hazard : 3  
Carcinogenicity (Inhalation) : 1A (Lung)  
Specific target organ toxicity - repeated exposure (Inhalation) : 2 (Kidney, Immune system)  
Specific target organ toxicity - repeated exposure (Inhalation) : 1

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.  
H315 Causes skin irritation.

## MasterEmaco S 440

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 07/16/2020     | 000000260156 | Date of first issue: 07/16/2020 |

H335 May cause respiratory irritation.  
H350 May cause cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H372 Causes damage to organs through prolonged or repeated exposure if inhaled.  
H402 Harmful to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.

## Precautionary Statements

:

**Prevention:**

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P201 Obtain special instructions before use.  
P271 Use only outdoors or in a well-ventilated area.  
P260 Do not breathe dust or mist.  
P202 Do not handle until all safety precautions have been read and understood.  
P273 Avoid release to the environment.  
P270 Do not eat, drink or smoke when using this product.  
P264 Wash face, hands and any exposed skin thoroughly after handling.

**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : No applicable information available.

**Components**

| Chemical name               | CAS-No.    | Concentration (% w/w) |
|-----------------------------|------------|-----------------------|
| Cement, portland, chemicals | 65997-15-1 | >= 15 - < 50          |

## MasterEmaco S 440

Version 1.0      Revision Date: 07/16/2020      SDS Number: 000000260156      Date of last issue: -  
Date of first issue: 07/16/2020

|   |            |                   |
|---|------------|-------------------|
| calcium oxide                                   | 1305-78-8  | $\geq 0.1 - < 1$  |
| copper(II) carbonate--copper(II) hydroxide(1:1) | 12069-69-1 | $\geq 0 - < 0.1$  |
| Quartz (SiO <sub>2</sub> )                      | 14808-60-7 | $\geq 50 - < 100$ |
| Calcium sulphate                                | 7778-18-9  | $\geq 0.3 - < 3$  |
| Gypsum (Ca(SO <sub>4</sub> ).2H <sub>2</sub> O) | 13397-24-5 | $\geq 0.3 - < 3$  |
| Limestone                                       | 1317-65-3  | $\geq 0 - < 3$    |

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause cancer.  
Causes damage to organs through prolonged or repeated exposure if inhaled.  
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing : High volume water jet

## MasterEmaco S 440

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 07/16/2020     | 000000260156 | Date of first issue: 07/16/2020 |

---

media  
Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Avoid dust formation.  
Avoid breathing dust.  
Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

---

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Avoid dust formation.  
Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Avoid formation of respirable particles.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Containers should be stored tightly sealed in a dry place.

Materials to avoid : Segregate from metals.  
Segregate from acids and bases.

---

## MasterEmaco S 440

Version 1.0      Revision Date: 07/16/2020      SDS Number: 000000260156      Date of last issue: -  
 Date of first issue: 07/16/2020

Segregate from oxidants.  
 Segregate from foods and animal feeds.

Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

| Components       | CAS-No.                                    | Value type<br>(Form of exposure)   | Control parameters / Permissible concentration | Basis                                |
|------------------|--|------------------------------------|--|--------------------------------------|
| calcium oxide    | 1305-78-8                                  | TWA value                          | 2 mg/m <sup>3</sup>                            | ACGIH TLV                            |
|                  |  | REL value                          | 2 mg/m <sup>3</sup>                            | NIOSH                                |
|                  |  | PEL                                | 5 mg/m <sup>3</sup>                            | 29 CFR<br>1910.1000<br>(Table Z-1)   |
|                  |  | TWA value                          | 5 mg/m <sup>3</sup>                            | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                  |  | TWA                                | 2 mg/m <sup>3</sup>                            | ACGIH                                |
|                  |  | TWA                                | 2 mg/m <sup>3</sup>                            | NIOSH REL                            |
|                  |  | TWA                                | 5 mg/m <sup>3</sup>                            | OSHA Z-1                             |
| Limestone        | 1317-65-3                                  | TWA                                | 5 mg/m <sup>3</sup>                            | OSHA P0                              |
|                  |  | REL value<br>(Respirable)          | 5 mg/m <sup>3</sup>                            | NIOSH                                |
|                  |  | REL value<br>(Total)               | 10 mg/m <sup>3</sup>                           | NIOSH                                |
|                  |  | PEL (Respirable fraction)          | 5 mg/m <sup>3</sup>                            | 29 CFR<br>1910.1000<br>(Table Z-1)   |
|                  |  | PEL (Total dust)                   | 15 mg/m <sup>3</sup>                           | 29 CFR<br>1910.1000<br>(Table Z-1)   |
|                  |  | TWA value<br>(Respirable fraction) | 5 mg/m <sup>3</sup>                            | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                  |  | TWA value<br>(Total dust)          | 15 mg/m <sup>3</sup>                           | 29 CFR<br>1910.1000<br>(Table Z-1-A) |
|                  |  | TWA (total dust)                   | 15 mg/m <sup>3</sup>                           | OSHA Z-1                             |
|                  |  | TWA (respirable fraction)          | 5 mg/m <sup>3</sup>                            | OSHA Z-1                             |
|                  |  | TWA (Total dust)                   | 15 mg/m <sup>3</sup>                           | OSHA P0                              |
|                  |  | TWA (respirable dust fraction)     | 5 mg/m <sup>3</sup>                            | OSHA P0                              |
| TWA (Respirable) | 5 mg/m <sup>3</sup><br>(Calcium carbonate) | NIOSH REL                          |  |                                      |
| TWA (total)      | 10 mg/m <sup>3</sup>                       | NIOSH REL                          |  |                                      |

**SAFETY DATA SHEET**

**MasterEmaco S 440**

Version  
1.0

Revision Date:  
07/16/2020

SDS Number:  
000000260156

Date of last issue: -  
Date of first issue: 07/16/2020

|   |            |                                    |                         |                                |
|---|------------|------------------------------------|-------------------------|--------------------------------|
|   |            |                                    | (Calcium carbonate)     |                                |
| Calcium sulphate                                | 7778-18-9  | TWA value (Inhalable fraction)     | 10 mg/m3                | ACGIHTLV                       |
|   |            | REL value (Respirable)             | 5 mg/m3                 | NIOSH                          |
|   |            | REL value (Total)                  | 10 mg/m3                | NIOSH                          |
|   |            | PEL (Respirable fraction)          | 5 mg/m3                 | 29 CFR 1910.1000 (Table Z-1)   |
|   |            | PEL (Total dust)                   | 15 mg/m3                | 29 CFR 1910.1000 (Table Z-1)   |
|   |            | TWA value (Respirable fraction)    | 5 mg/m3                 | 29 CFR 1910.1000 (Table Z-1-A) |
|   |            | TWA value (Total dust)             | 15 mg/m3                | 29 CFR 1910.1000 (Table Z-1-A) |
|   |            | TWA (Respirable)                   | 5 mg/m3                 | NIOSH REL                      |
|   |            | TWA (total)                        | 10 mg/m3                | NIOSH REL                      |
|   |            | TWA (total dust)                   | 15 mg/m3                | OSHA Z-1                       |
|   |            | TWA (respirable fraction)          | 5 mg/m3                 | OSHA Z-1                       |
|   |            | TWA (Total dust)                   | 15 mg/m3                | OSHA P0                        |
|   |            | TWA (respirable dust fraction)     | 5 mg/m3                 | OSHA P0                        |
|   |            | TWA (Inhalable particulate matter) | 10 mg/m3 (Calcium)      | ACGIH                          |
| copper(II) carbonate--copper(II) hydroxide(1:1) | 12069-69-1 | PEL (Dust and mist)                | 1 mg/m3 (copper (Cu))   | 29 CFR 1910.1000 (Table Z-1)   |
|   |            | REL value (Dust and mist)          | 1 mg/m3 (copper (Cu))   | NIOSH                          |
|   |            | REL value (fumes/smoke)            | 0.1 mg/m3 (copper (Cu)) | NIOSH                          |
|   |            | TWA                                | 1 mg/m3 (Copper)        | NIOSH REL                      |
| Gypsum (Ca(SO4).2H2O)                           | 13397-24-5 | TWA value (Inhalable fraction)     | 10 mg/m3                | ACGIHTLV                       |
|   |            | REL value (Respirable)             | 5 mg/m3                 | NIOSH                          |
|   |            | REL value (Total)                  | 10 mg/m3                | NIOSH                          |

**SAFETY DATA SHEET**

**MasterEmaco S 440**

Version  
1.0

Revision Date:  
07/16/2020

SDS Number:  
000000260156

Date of last issue: -  
Date of first issue: 07/16/2020

|                             |            |                                     |  |                                |
|-----------------------------|------------|-------------------------------------|--|--------------------------------|
|                             |            | PEL (Total dust)                    | 15 mg/m3                                       | 29 CFR 1910.1000 (Table Z-1)   |
|                             |            | PEL (Respirable fraction)           | 5 mg/m3  | 29 CFR 1910.1000 (Table Z-1)   |
|                             |            | TWA value (Total dust)              | 15 mg/m3                                       | 29 CFR 1910.1000 (Table Z-1-A) |
|                             |            | TWA value (Respirable fraction)     | 5 mg/m3  | 29 CFR 1910.1000 (Table Z-1-A) |
|                             |            | TWA (Respirable)                    | 5 mg/m3  | NIOSH REL                      |
|                             |            | TWA (total)                         | 10 mg/m3                                       | NIOSH REL                      |
|                             |            | TWA (total dust)                    | 15 mg/m3                                       | OSHA Z-1                       |
|                             |            | TWA (respirable fraction)           | 5 mg/m3  | OSHA Z-1                       |
|                             |            | TWA (Total dust)                    | 15 mg/m3                                       | OSHA P0                        |
|                             |            | TWA (respirable dust fraction)      | 5 mg/m3  | OSHA P0                        |
|                             |            | TWA (Inhalable particulate matter)  | 10 mg/m3 (Calcium)                             | ACGIH                          |
| Cement, portland, chemicals | 65997-15-1 | TWA value (Respirable fraction)     | 1 mg/m3  | ACGIHTLV                       |
|                             |            | REL value (Total)                   | 10 mg/m3                                       | NIOSH                          |
|                             |            | REL value (Respirable)              | 5 mg/m3  | NIOSH                          |
|                             |            | PEL (Total dust)                    | 15 mg/m3                                       | 29 CFR 1910.1000 (Table Z-1)   |
|                             |            | PEL (Respirable fraction)           | 5 mg/m3  | 29 CFR 1910.1000 (Table Z-1)   |
|                             |            | TWA value (Total dust)              | 10 mg/m3                                       | 29 CFR 1910.1000 (Table Z-1-A) |
|                             |            | TWA value (Respirable fraction)     | 5 mg/m3  | 29 CFR 1910.1000 (Table Z-1-A) |
|                             |            | TWA value                           | 50 millions of particles per cubic foot of air | 29 CFR 1910.1000 (Table Z-3)   |
|                             |            | TWA (Respirable particulate matter) | 1 mg/m3  | ACGIH                          |
|                             |            | TWA (Res-                           | 5 mg/m3  | NIOSH REL                      |

## MasterEmaco S 440

Version  
1.0Revision Date:  
07/16/2020SDS Number:  
000000260156Date of last issue: -  
Date of first issue: 07/16/2020

|                            |            |                                     |                                     |                       |
|----------------------------|------------|-------------------------------------|-------------------------------------|-----------------------|
|                            |            | pirable)                            |                                     |                       |
|                            |            | TWA (total)                         | 10 mg/m3                            | NIOSH REL             |
|                            |            | TWA (total dust)                    | 15 mg/m3                            | OSHA Z-1              |
|                            |            | TWA (respirable fraction)           | 5 mg/m3                             | OSHA Z-1              |
|                            |            | TWA (Total dust)                    | 10 mg/m3                            | OSHA P0               |
|                            |            | TWA (respirable dust fraction)      | 5 mg/m3                             | OSHA P0               |
|                            |            | TWA (Dust)                          | 50 Million particles per cubic foot | OSHA Z-3              |
| Quartz (SiO <sub>2</sub> ) | 14808-60-7 | TWA value (Respirable fraction)     | 0.025 mg/m3                         | ACGIHTLV              |
|                            |            | REL value (Respirable dust)         | 0.05 mg/m3                          | NIOSH                 |
|                            |            | TWA value                           | 0.05 mg/m3 (Respirable dust)        | 29 CFR 1910.1001-1050 |
|                            |            | OSHA Action level                   | 0.025 mg/m3 (Respirable dust)       | 29 CFR 1910.1001-1050 |
|                            |            | TWA (Respirable dust)               | 0.05 mg/m3                          | OSHA Z-1              |
|                            |            | TWA (respirable)                    | 10 mg/m3 / %SiO <sub>2</sub> +2     | OSHA Z-3              |
|                            |            | TWA (respirable)                    | 250 mppcf / %SiO <sub>2</sub> +5    | OSHA Z-3              |
|                            |            | TWA (respirable dust fraction)      | 0.1 mg/m3                           | OSHA P0               |
|                            |            | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica)                | ACGIH                 |
|                            |            | PEL (respirable)                    | 0.05 mg/m3                          | OSHA CARC             |
|                            |            | TWA (Respirable dust) (Silica)      | 0.05 mg/m3 (Silica)                 | NIOSH REL             |

**Engineering measures** : Provide local exhaust ventilation to maintain recommended P.E.L.

**Personal protective equipment**

Respiratory protection : Breathing protection if dusts are formed.  
Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles



## MasterEmaco S 440

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 07/16/2020     | 000000260156 | Date of first issue: 07/16/2020 |

|                          |   |  |
|--------------------------|---|--|
| Skin and body protection | : | Wear face-shield and protective suit for abnormal processing problems.<br>Choose body protection according to the amount and concentration of the dangerous substance at the work place.   |
| Protective measures      | : | Avoid contact with the skin, eyes and clothing.<br>Avoid inhalation of dusts.<br>In order to prevent contamination while handling, closed working clothes and working gloves should be used.<br>Handle in accordance with good building materials hygiene and safety practice. |
| Hygiene measures         | : | When using do not eat or drink.<br>When using do not smoke.<br>Wash hands before breaks and at the end of workday.   |

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

|  |   |  |
|--|---|--|
| Appearance                                       | : | powder   |
| Color  | : | gray   |
| Odor Threshold                                   | : | Not determined due to potential health hazard by inhalation.   |
| pH   | : | neutral to slightly alkaline   |
| Boiling point                                    | : | No applicable information available.   |
| Flash point                                      | : | does not flash   |
| Evaporation rate                                 | : | No applicable information available.   |
| Flammability (solid, gas)                        | : | not determined   |
| Self-ignition                                    | : | not self-igniting  |
| Upper explosion limit / Upper flammability limit | : | As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use. |
| Lower explosion limit / Lower flammability limit | : | As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use. |
| Vapor pressure                                   | : | No applicable information available.   |
| Relative vapor density                           | : | No applicable information available.   |
| Relative density                                 | : | 2.8  |
| Density  | : | not applicable   |
| Bulk density                                     | : | 1,800 - 2,400 kg/m <sup>3</sup>  |
| Solubility(ies)                                  | : |  |
| Water solubility                                 | : | No data available  |

## MasterEmaco S 440

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 07/16/2020     | 000000260156 | Date of first issue: 07/16/2020 |

---

|  |   |  |
|--|---|--|
| Solubility in other solvents           | : | No applicable information available.   |
| Partition coefficient: n-octanol/water | : | No applicable information available.   |
| Autoignition temperature               | : | No applicable information available.   |
| Decomposition temperature              | : | No decomposition if stored and handled as prescribed/indicated.                |
| Viscosity                              |   |  |
| Viscosity, dynamic                     | : | No data available.   |
| Viscosity, kinematic                   | : | No applicable information available.   |
| Explosive properties                   | : | Not explosive<br>Not explosive   |
| Oxidizing properties                   | : | Based on its structural properties the product is not classified as oxidizing. |
| Self-heating substances                | : | No data available  |
| Sublimation point                      | : | No applicable information available.   |
| Molecular weight                       | : | No data available  |

**SECTION 10. STABILITY AND REACTIVITY**

|                                    |   |  |
|------------------------------------|---|--|
| Reactivity                         | : | No decomposition if stored and applied as directed.                                |
| Chemical stability                 | : | No decomposition if stored and applied as directed.                                |
| Possibility of hazardous reactions | : | No decomposition if stored and applied as directed.                                |
| Conditions to avoid                | : | See SDS section 7 - Handling and storage.  |
| Incompatible materials             | : | Strong bases<br>Strong acids   |
| Hazardous decomposition products   | : | No hazardous decomposition products if stored and handled as prescribed/indicated. |

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Product:**

|                           |   |   |
|---------------------------|---|---|
| Acute oral toxicity       | : | Remarks: No applicable information available. |
| Acute inhalation toxicity | : | Remarks: No applicable information available. |
| Acute dermal toxicity     | : | Remarks: No applicable information available. |

## MasterEmaco S 440

Version 1.0      Revision Date: 07/16/2020      SDS Number: 000000260156      Date of last issue: -  
Date of first issue: 07/16/2020

---

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Product:**

Remarks : Chromate in this product has been reduced. Sensitization due to chromate within stated shelf-life is unlikely.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure if inhaled.  
May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : The product has not been tested. The statement has been derived from the properties of the individual components.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

## MasterEmaco S 440

Version 1.0      Revision Date: 07/16/2020      SDS Number: 000000260156      Date of last issue: -  
Date of first issue: 07/16/2020

---

**Persistence and degradability****Product:**

Biodegradability : Remarks: Not applicable for inorganic substances.

**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: The product will not be readily bioavailable due to its consistency and insolubility in water.

**Components:****Cement, portland, chemicals:**

Partition coefficient: n-octanol/water : GLP: no  
Remarks: not applicable

**calcium oxide:**

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

**copper(II) carbonate--copper(II) hydroxide(1:1):**

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

**Quartz (SiO<sub>2</sub>):**

Partition coefficient: n-octanol/water : Remarks: not applicable

**Calcium sulphate:**

Partition coefficient: n-octanol/water : GLP: no  
Remarks: The value has not been determined because the substance is inorganic.

**Gypsum (Ca(SO<sub>4</sub>).2H<sub>2</sub>O):**

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

**Mobility in soil****Product:**

Distribution among environmental compartments : Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.  
The substance will not evaporate into the atmosphere from the water surface.

**Other adverse effects****Product:**

## MasterEmaco S 440

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 07/16/2020     | 000000260156 | Date of first issue: 07/16/2020 |

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life.  
Harmful to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with national, state and local regulations.  
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****US State Regulations****Pennsylvania Right To Know**

|   |            |
|---|------------|
| Limestone                                       | 1317-65-3  |
| Calcium sulphate                                | 7778-18-9  |
| Gypsum (Ca(SO <sub>4</sub> ).2H <sub>2</sub> O) | 13397-24-5 |
| Cement, portland, chemicals                     | 65997-15-1 |
| Quartz (SiO <sub>2</sub> )                      | 14808-60-7 |

**New Jersey Right To Know**

**MasterEmaco S 440**

|                |                              |                             |  |
|----------------|------------------------------|-----------------------------|--|
| Version<br>1.0 | Revision Date:<br>07/16/2020 | SDS Number:<br>000000260156 | Date of last issue: -<br>Date of first issue: 07/16/2020 |
|----------------|------------------------------|-----------------------------|--|

|                             |            |
|-----------------------------|------------|
| Limestone                   | 1317-65-3  |
| Calcium sulphate            | 7778-18-9  |
| Cement, portland, chemicals | 65997-15-1 |
| Quartz (SiO2)               | 14808-60-7 |

**California Prop. 65**

WARNING: This product can expose you to chemicals including Quartz (SiO2), which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).


**The ingredients of this product are reported in the following inventories:**

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA 704:**



**HMIS® IV:**

|                        |                      |                      |
|------------------------|----------------------|----------------------|
| <b>HEALTH</b>          | <input type="text"/> | <input type="text"/> |
| <b>FLAMMABILITY</b>    | <input type="text"/> |                      |
| <b>PHYSICAL HAZARD</b> | <input type="text"/> |                      |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- 29 CFR 1910.1000 (Table Z-3) : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
- 29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)

## MasterEmaco S 440

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 07/16/2020     | 000000260156 | Date of first issue: 07/16/2020 |

|  |   |   |
|--|---|---|
| NIOSH REL                                  | : | USA. NIOSH Recommended Exposure Limits  |
| OSHA CARC                                  | : | OSHA Specifically Regulated Chemicals/Carcinogens   |
| OSHA P0                                    | : | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000                             |
| OSHA Z-1                                   | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants          |
| OSHA Z-3                                   | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts                        |
| 29 CFR 1910.1000 (Table Z-1-A) / TWA value | : | Time Weighted Average (TWA):  |
| 29 CFR 1910.1000 (Table Z-1) / PEL         | : | Permissible exposure limit  |
| 29 CFR 1910.1000 (Table Z-3) / TWA value   | : | Time Weighted Average (TWA):  |
| 29 CFR 1910.1001-1050 / OSHA Action level  | : | OSHA Action level:  |
| 29 CFR 1910.1001-1050 / TWA value          | : | Time Weighted Average (TWA):  |
| ACGIH / TWA                                | : | 8-hour, time-weighted average   |
| ACGIHTLV / TWA value                       | : | Time Weighted Average (TWA):  |
| NIOSH / REL value                          | : | Recommended exposure limit (REL):   |
| NIOSH REL / TWA                            | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| OSHA CARC / PEL                            | : | Permissible exposure limit (PEL)  |
| OSHA P0 / TWA                              | : | 8-hour time weighted average  |
| OSHA Z-1 / TWA                             | : | 8-hour time weighted average  |
| OSHA Z-3 / TWA                             | : | 8-hour time weighted average  |

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -

## MasterEmaco S 440

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: -           |
| 1.0     | 07/16/2020     | 000000260156 | Date of first issue: 07/16/2020 |

---

Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/16/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN