

HYDRO BAN® Sheet Membrane

HYDRO BAN® Sheet Membrane is a high performance low-perm waterproofing membrane for use in interior residential and commercial waterproofing applications including steam showers and steam rooms.

FEATURES

- Approved for steam showers/rooms
- Allows for polymer-modified or unmodified mortar usage[^]
- Pliable construction – conforms easily to substrate
- Allows for installation over green mortar beds
- Complete line of accessories – single source supply



ASTM E96/E96M
PROCEDURE E
PERM RATING LESS
THAN 0.5

ANSI A118.10
EXCEEDS ALL
REQUIREMENTS

ASTM C627
RATED
EXTRA HEAVY



ICC
ES
PMG
REPORT # 1229



HYDRO BAN® SHEET MEMBRANE ROLLS

3'3" x 33' = 108 ft² (1 m x 10 m = 10 m²)

3'3" x 98'5" = 323 ft² (1 m x 30 m = 30 m²)

HYDRO BAN SEALING TAPE

5" x 16'5" (125 mm x 5 m)	individually packaged – 12/carton
5" x 98'5" (125 mm x 30 m)	individually packaged

HYDRO BAN PREFORMED CORNERS

Inside Corners – 2 per package – 12/carton
Outside Corners – 2 per package – 12/carton

HYDRO BAN COLLARS

3/4" (19 mm) Pipe Collar – use with 1/2" – 3/4" pipe (12.7 mm – 20 mm) packaged individually – 12 per carton
4 1/2" (114 mm) Mixing Valve Collar – individually packaged – 10/carton

[^]See Data Sheet 230.99 for complete warranty information. [^]Use a substrate and application appropriate thin-set mortar to install HYDRO BAN® Sheet Membrane. See product Data Sheet DS 041.0 for complete product and installation information.