

Step #	Installation Step	Installation Methods	Products & Mix Ratios	Theoretical Coverage Rates
	Mechanically Prepare Substrate	a. High pressure Power Wash or	MiraGard HD 400 Sealer must be applied to a clean,	
		b. Degreaser and Scrubbing or	sound, and mechanically prepared concrete substrate,	N/A
1	Note: Minimum (CSP) concrete surface profile	c. Sandblasting or	as per the ICRI's Technical Guideline No.03732,	
	of CSP-2 or higher is required depending on	d. Shotblasting or	"Selecting and Specifying Concrete Surface Preparation"	
	substrate conditions & coating requirements.	e. Diamond grinding or		
		f. Other similar and approved	Concrete surface must be dry at the time of application.	
		mechanical methods		
	Apply 1st Coat of MiraGard HD 400 Sealer	a. Hudson-type sprayer or	MiraGard HD 400 Sealer	320 SF/Gal
		b. Dip and Roll or	(Available in Gloss or Low Gloss)	5 mils WFT
2		c. Brush for detail work		
	Caution			Note: Coverage depends on surface
	Avoid application of sealer when surface			texture and profile. Consumption may
	temperatures are approaching 90+°F.			be greater on more irregular surfaces.
	Apply 2nd Coat of MiraGard HD 400 Sealer	a. Hudson-type sprayer or	MiraGard HD 400 Sealer	320 SF/Gal
		b. Dip and Roll or	(Available in Gloss or Low Gloss)	5 mils WFT
3		c. Brush for detail work		
	Caution			Note: Coverage depends on surface
	Avoid application of sealer when surface			texture and profile. Consumption may
	temperatures are approaching 90+°F.			be greater on more irregular surfaces.
	Optional - Addition of Synthetic Aggregate	Same as Above	BT Solid Glass Beads	
	for Skid Resistance	With Exception - Do Not Use Hudson-type sprayers	Add 2 -4 Ounces/Gal to MiraGard HD 400 Sealer	

Note: Prior to starting the application of any Miracote Product or System be sure to read the Installation Guide(s), Product Data Sheets, MSDS and other pertinent documents published by Crossfield Product Corp. for information, including but not limited to, Precautions, Limitations, Disclaimers and Warranties.



Pay special attention to substrate moisture content, physical condition of the substrate, method(s) of surface preparation, surface restoration, detailing of cracks, joints, transitions and terminations, and any applicable specifications. Review carefully for unknown site conditions or defects.

The theoretical coverage rates stated in the Installation Guides are for estimating purposes only. Factors, such as, allowance for material waste, unusual or abnormal substrate conditions and other unforeseen job site conditions that may affect actual product yields are the responsibility of the installer.