

ALSAN® RS

223 MIXING POWDER

ALSAN® RS 223
MIXING POWDER

PRODUCT # L-RS223

PRODUCT DATA SHEET

DESCRIPTION & FEATURES

ALSAN RS 223 Mixing Powder is utilized in conjunction with ALSAN RS 210 to create ALSAN RS 233 Self-Leveling Mortar. It may also be used with ALSAN RS 240 LO to create ALSAN RS 263 LO Self-Leveling Mortar.

STORAGE

Always store closed containers in cool, ventilated and dry locations away from heat and oxidizing agents. Do not store in direct sunlight or in temperatures below 32°F (0°C) or above 77°F (25°C). Approximate shelf life is twelve months from date of manufacture when properly stored sealed and unmixed.

APPLICATION

ALSAN RS 233 Self-Leveling Mortar and ALSAN RS 263 LO Self-Leveling Mortar is applied using a notched trowel or masonry float. The applicator is responsible for ensuring conditions are appropriate to proceed with proper application methods. ALSAN RS 223 Mixing Powder is mixed with ALSAN RS 210 or ALSAN RS 240 LO to make ALSAN RS 233 Self-Leveling Mortar or ALSAN RS 263 LO Self-Leveling Mortar respectively.

Refer to ALSAN RS 210 product data sheet, ALSAN RS 233 Self-Leveling Mortar product data sheet, ALSAN RS 240 LO product data sheet and ALSAN RS 263 LO Self-Leveling Mortar product data sheet for additional mixing and application information.



QUICK FACTS

WEIGHT
(kg)

23
(50.7 lb)



SOPREMA®

www.soprema.us

310 Quadral Drive, Wadsworth, Ohio 44281

Toll Free: (800) 356-3521 | Tel: (330) 334-0066

PD10236 - REV. 035016