



Proven Protection For Drywall Construction

3M™ FireDam™ 200 Spray

This sprayable coating is a quick and easy method for firestopping fire rated construction joints, including: head-of-wall, floor-to-wall, floor-to-floor, and perimeter joints. The coating has a high coverage rate, is fast-drying, and is a low-sag formula which helps reduce your overall installation time. When your project is complete you can simply clean-up with water.

- High coverage rate reduces installation time
- Fast-dry, low-sag formula
- Applies with conventional airless spray equipment
- Paintable when cured
- Applies as 1/8" wet coating, dries 1/16"
- STC Rating 56 when installed in 56 STC rated assembly
- Elastomeric – forms a flexible seal with compression/extension of up to $\pm 50\%$ of nominal joint width
- Easy clean-up with water
- Available in 5 gallons pails
- Provides up to a 4-hour fire rating with tested and listed systems
- Low VOC



Available in
• Grey
• Red

3M™ FireDam™ 150+ Sealant

Tested and approved for use in fire-rated construction joints.

- Water-based for easy installation, cleanup and disposal
- Solvent-free
- High-solids formula means limited shrinkage
- Multiviscosity grade offers excellent caulking properties
- Provides a continuous seal with a movement capability of $\pm 19\%$ when fully cured
- Available in limestone color
- Provides up to a 3-hour fire rating in tested and listed systems
- Dries to touch in 30 to 60 minutes and can be painted



Available in
• Limestone
• Blue

3M™ Fire Barrier Watertight Sealant 1000 NS

Non-slumping silicone with up to 3-hour fire protection

- Ready-to-use, one component, silicone elastomers used to fire stop openings and penetrations
- For use in head-of-wall firestopping applications





Other 3M Drywall Solutions

Sanding

3M™ Drywall Sanding Sponges

- Ideal for sanding drywall and plaster during spot repair.
- When finished, simply rinse and reuse.



3M™ Drywall Sanding Sheets

- Designed for sanding drywall joints, patching compounds and plaster.
- Pre-cut for easy attachment to hand or pole sander.



3M™ Drywall Sanding Screens

- Made with sharp silicon carbide mineral for long-lasting performance.
- Pre-cut for easy attachment to hand or pole sander.



Safety

3M™ Drywall Sanding Respirator

- Ideal for particles from drywall sanding.
- Advanced filter media for easier breathing.



Clean-up

3M™ Easy Trap Duster Sheets

- An easier way to clean up drywall dust.
- Attach to drywall sanding tools, like pole sanders, for removal of drywall dust from floors, walls and textures.



Warranty; Limited Remedy

This product will be free from defects in material and manufacture for a period of ninety (90) days from the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. If this product is defective within the warranty period stated above, your exclusive remedy and 3M's sole obligation shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product.

Limited Liability

Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



Building & Commercial Services Division

3M Center
Building 223-2N-21
St. Paul, MN 55144-1000
U.S.A.
1-800-328-1687
www.3m.com/firestop

3M, FireDam and Pro-pak are trademarks of 3M.
Please recycle. Printed in U.S.A.
© 3M 2009. All rights reserved.
98-0213-4384-7