

3M Application Profile

Market: Construction, MRO

Application Description: Sealing HVAC insulation and flexible duct joints.



Key Application Requirements

For sealing fiberglass duct work and flexible duct systems, tapes must meet UL 181 A/B-FX standard. Scotch® Foil Tape 3326 meets these UL standards, which include specifications for tensile, adhesion, shear holding as well mold growth resistance.

For general duct sealing and MRO repair applications, Scotch® Foil Tape 3311 is an excellent choice. This tape meets UL 723 standard, which specifies burning characteristics of flame spread and smoke development. This is a standard important to the construction industry.

Benefits/Advantages To Customer

UL identification printed on the 3326 tape: Ensures that correct tape is used and is recognized by those who may be inspecting the installation.

Lined tapes: Easy to use; protects the integrity of the adhesive and allows user to put tape through narrow gaps.

Synthetic rubber adhesive on 3311 tape: Good instant tack and adhesion to many surfaces.

Acrylic adhesive on 3326 tape: Has very long life and is not readily degraded by high temperature.

PRODUCT

Scotch® Foil Tape 3311
Scotch® Foil Tape 3326

Key Decision Makers

Job Site Foreman
Contractors
Purchasing

For Additional Information

To request additional product information or to arrange for sales assistance, call 1-800-362-3550. Address correspondence to: 3M Industrial Business Customer Response Center, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55106. Our fax number is 651-733-9175. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including warranty, contract, negligence, or strict liability.



Industrial Business

Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55106

Printed in the USA
Hvacsidj3311.pdf
© 3M 2005