PercoDrain 15-B Data Sheet

PercoDrain 15-B is a three-part prefabricated geocomposite drain consisting of a formed polystyrene core covered on one side with polypropylene filter fabric. The fabric allows water to pass into the drain core while restricting the movement of soil particles which might clog the core. The core allows the water to flow to designated drainage exits. PercoDrain 15-B is designed for vertical applications. PercoDrain 15-B has a built-in Polymeric film protection layer for use as required by manufacture of some waterproofing materials in order to be a compatible protection layer. PercoDrain 15-B with ½" height can move more drainage water per foot width than a layer of stone which is 1' wide and 180" high.



PHYSICAL PROPERTIES	TYPICAL US VALUE	TYPICAL SI VALUE	TEST METHOD
FABRIC PROPERTIES			
Material	Polypropylene	Polypropylene	
Grab Tensile Strength	110 lbs	50 kg	ASTM D-4632
Puncture Strength	65 psi	65 psi	ASTM D-4833
Grab Elongation	60%	60%	ASTM D-4632
EOS (AOS)	100 Sieve	0.152 mm	ASTM D-4751
UV at 500 hours (strength retained)	70%	70%	ASTM D-4355
Flow Rate	150 gal/min/ft ²	6110 L/min/m ²	ASTM D-4491
CORE PROPERTIES			
Material	Polystyrene	Polystyrene	
Thickness	7/16 in.	1.11 cm	ASTM D-1777
Compressive Strength (+ or - 5%)	15,000 lbs/ft ²	72 x 10 ³ kg/m ²	ASTM D-1621 (mod
Polymeric film layer	Yes	Yes	
DRAIN PROPERTIES			
Flow Capacity	16 gpm/ft of width	200 l/min/m of width	ASTM D-4716
Roll Length	50 ft	15.24 m	
Roll Width	4 ft	1.22 m	
Roll Width		20 A Ive	
Roll Weight	45 lbs	20.4 kg	

properties are typical values. Standard variations in mechanical properties of 10% and in hydraulic properties of 20% are normal.



26 5th St SE - Hickory, NC - 28602, USA

Office 980-428-2779

www.usdrainage.co

Travis.obermeyer@gmail.com