



## HYDRAULIC WATER-STOP CEMENT

Rapid setting, high strength repair material designed to plug leaks instantly in concrete and masonry. Sets in 3-5 minutes and can be used above and below grade. **Use For:**

- Blocking running water or leaks in cracked masonry or concrete surfaces
- Can be used on swimming pools, foundations and for sealing around concrete pipe

Item No.	Package Size	Metric	Quantity
1126-11	10 lb. pail	4.5 kg	4/case
1126-20	20 lb. pail	9.1 kg	60/pallet
1126-50	50 lb. pail	18.1 kg	64/pallet
<b>White</b>			
1126-15	10 lb. pail	4.5 kg	4/case



## ZIP & MIX - REPAIR MORTAR

Polymer modified fast-setting repair mortar in a new zip closure pouch. Add water directly to the pouch, zip the pouch closed and knead the bag for 3 minutes, then apply right out of the pouch. **Use For:**

- Vertical or horizontal repairs to concrete and masonry surfaces from 1/8" to 2" thick.

Item No.	Package Size	Metric	Quantity
1241-15	3 lb. bag	1.36 kg	12/case



## CONCRETE PATCHING COMPOUND

Pre-mixed, ready to apply, acrylic patching compound for non-structural repairs to concrete and masonry surfaces. Use for patches up to 1/4" thick. No mixing required. **Use for:**

- Sidewalks
- Walkways
- Steps
- Patios

Item No.	Package Size	Metric	Quantity
8650-35	1 qt. pail	.95 L	12/case



## HEAVY DUTY MASONRY COATING

A powdered mixture of Portland cement, waterproofing agents and sand used to seal and beautify concrete, block, brick, stucco, and stone walls. Can be used in both interior and exterior applications both above grade and below. Available in white and gray. **Use For:**

- Basement walls
- Retaining walls
- Ponds
- Swimming pools

Item No.	Package Size	Metric	Quantity
<b>White</b>			
2401-20	20 lb. pail	9.1 kg	60/pallet
1301-40	40 lb. bag	18.1 kg	63/pallet
<b>Gray</b>			
2402-20	20 lb. pail	9.1 kg	60/pallet
1312-40	40 lb. bag	18.1 kg	63/pallet




## MULTI-PURPOSE CONCRETE RESURFACER

Polymer modified Portland cement based trowel applied repair material designed to provide a new, durable and wear resistant surface over worn or scaling concrete. Ideal for resurfacing large areas. **Use for:**

- Sidewalks
- Patios
- Loading docks
- Steps
- Driveways
- Traffic barriers
- Ramps
- Floors

Item No.	Package Size	Metric	Quantity
1131-45	40 lb. bag	18.1 kg	64/pallet

**April 1988** Runs first national TV ads with Don Knotts featuring Fast-Setting Concrete and The QUIKRETE® Concrete Repair Center



**January 1991** Introduces Gray Concrete Crack Seal & Fiber-Reinforced Concrete



**January 1992** Introduces QUIKRETE® 5000, Mason Mix & WALKMAKER

