

Sealants and Packing Material

3M™ Fire Barrier Water Tight Sealant 1000 NS

3M™ Fire Barrier Water Tight Sealant 1000 NS is a ready-to-use, single component, neutral cure, silicone sealant that cures upon exposure to atmospheric humidity to form a flexible firestop seal. 3M™ Fire Barrier Water Tight Sealant helps control the spread of fire, smoke and noxious gasses before, during and after exposure to a fire when installed in accordance with a listed through penetration or fire-resistive joint assembly.

3M™ Fire Barrier Water Tight Sealant 1000 NS is a non-slump firestop used primarily on vertical surfaces. The firestop sealant also meets UL Water Leakage Test, W Rating – Class 1 requirements for systems tested and listed in accordance with ANSI/UL 1479. Product is elastomeric, ready-to use and exhibits excellent weather ability.

Description	Water Tight Sealant Non-Slump
Properties	Silicone
RoHS 2011/65/EU	Yes
Specifications	Fire Barrier 3 Hr; Smoke Seal L-Rated; Sound Barrier STC-Rating 56; Elastometric +-25%; Water Barrier UL W-Rating Class-1; ANSI/UL 1479; LEED® VOC environmental regulations
Agency Approvals	  Intertek; NEC (NFPA 70); IBC; IFC; IRC; NFPA 101; NFPA 5000



Order No.	UPC	Product Name	Color	Size	Case Quantity
1000-N/S-10.10Z	051115-11535	3M™ Fire Barrier Water Tight Sealant 1000 NS, 10.1 fl. oz., Cartridge	Light Gray	10.1 fl oz (295,6 ml)	12
1000NS	051115-18790	3M™ Fire Barrier Water Tight Sealant 1000 NS, 20 fl. oz., Sausage	Light Gray	20 fl oz (591,3 ml)	12
1000-N/S-4.5GAL	051115-11537	3M™ Fire Barrier Water Tight Sealant 1000 NS, 4.5 gallon, Pail	Light Gray	4.5 gal (15,1 l)	1