

## PRODUCT DATA SHEET

# SikaProof® ExTape-100

Self-adhesive tape for external jointing and detailing of the SikaProof® A+ waterproofing system

### PRODUCT DESCRIPTION

SikaProof® ExTape-100 is a self-adhesive tape based on a butyl adhesive for external jointing and detailing of the SikaProof® A+ membrane system. The tape is composed of a grey aluminium/PET carrier and a divided release liner.

### USES

The product is used for:

- Sealing external joints and details within the SikaProof® A+ membrane system.

Please note:

- Do not use the Product in areas where it is permanently exposed to weathering or UV-light.

### CHARACTERISTICS / ADVANTAGES

- High adhesion and sealing ability
- Divided release liner for quick and easy installation

### PRODUCT INFORMATION

<b>Packaging</b>	6 rolls packed in one box. Individual roll size: Length 65 ft (20 m) / Width 4 in (100 mm)
<b>Shelf Life</b>	24 months from date of production
<b>Storage Conditions</b>	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +40 °F (+5 °C) and +85 °F (+30 °C). Always refer to packaging.
<b>Appearance / Color</b>	Grey carrier coated with black butyl adhesive covered by divided white release liner.
<b>Length</b>	65 ft   20 m
<b>Width</b>	4 in   100 mm
<b>Thickness</b>	40 mils   1.0 mm

### SYSTEM INFORMATION

<b>System Structure</b>	System Components SikaProof® A+ sheet membranes
-------------------------	--

## APPLICATION INFORMATION

Ambient Air Temperature	Maximum	+104 °F   +35 °C
	Minimum	+40 °F   +5 °C
Substrate Temperature	Minimum	+40 °F   +5 °C

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## ENVIRONMENTAL, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION INSTRUCTIONS

### IMPORTANT

#### Strictly follow installation procedures

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

### IMPORTANT

#### Application by trained personnel

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

## SUBSTRATE QUALITY

The contact surface is the light yellow SikaProof® membrane side. It must be dry, clean and free of any materials that could impair adhesion.

#### Application outside of specified application conditions

Note: Under certain circumstances, the Product can be applied in conditions other than the ones specified in this data sheet. However, this requires specific precautions and application methods.

1. Contact Sika technical services for more information.

## APPLICATION

### IMPORTANT

#### Exposure to UV or weathering

The Product is not resistant to permanent UV exposure or weathering.

- Protect as soon as possible but not later than 90 days after application
1. Remove the release liner
  2. Apply onto the yellow membrane side
  3. Press firmly using a pressure roller

## OTHER RESTRICTIONS

See Legal Disclaimer.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS**

**PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT  
OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD  
BY OTHERS.**

Sale of SIKA products are subject to the Terms and  
Conditions of Sale which are available at  
<https://usa.sika.com/en/group/SikaCorp/termsandconditions.html>  
or by calling 1-800-933-7452.

**Sika Corporation**

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)



**Product Data Sheet**  
SikaProof® ExTape-100  
August 2022, Version 01.01  
02072030800000019

SikaProofExTape-100-en-US-(08-2022)-1-1.pdf

