LATAPOXY® 310 STONE ADHESIVE

Refer to Data Sheets 679.0 and 679.3 See Price Book



A strong, two-component epoxy adhesive for spot-bonding large format tile and stone on vertical surfaces. Easier and faster than traditional methods of veneer installation.

FEATURES/BENEFITS:

- For interior or approved exterior applications
- Both standard and rapid version for faster curing
- No drilling, cutting kerfs, or setting pins
- Allows for quick plumb adjustment while stone is in place to compensate for uneven walls and stone thickness variations
- Won't deteriorate over time
- ANSI A118.3 and ISO 13007-1 R2T classification

PACKAGING:

Full Unit Kit: 2.6 gal (10 L): All components packed in one carton 1.3 gal (5 L) Part A pail, 1.3 gal (5 L) Part B pail 40 cartons per pallet, Available in standard and rapid version Mini Unit Kit: 2 gal (8 L): units packed in one carton 8 mini jars of Part A 0.5 qt (0.5 L), 8 mini jars of Part B 0.5 gt (0.5 L), 40 cartons per pallet Available in standard and rapid versions

Cartridge Packs: 2.3 gal (9 L) Cartridge Pack (for use in LATAPOXY® 310 Cordless Mixer): 15 x 20 oz (600 ml) cartridge packs of Part A and Part B per carton, 27 cartons per pallet Available in standard and rapid versions

MIXING:

Combine equal volumes of Part A and Part B (1:1).

Approximate Coverage		
Inches (or millimeters) Out of Plumb	LATAPOXY 310 Stone Adhesive Thickness	2.6 gal (10 L) Full Units
Plumb Wall (3 mm)	1/8" Thick (3 mm)	300 - 325 ft ² (27 - 30 m ²)
1/4" (6 mm)	1/4" Thick (6 mm)	150 - 170 ft ² (14 - 16 m ²)
1/2" (12 mm)	1/2" Thick (12 mm)	75 - 80 ft ² (7- 7.5 m ²)



LATAPOXY 310 CORDLESS MIXER

Refer to Data Sheet 683.0 RT8480310/RT8480500



This dual-component mixer quickly dispenses LATAPOXY 310 Stone Adhesive onto tile, porcelain, and stone veneers.

FEATURES/BENEFITS:

- Triples productivity of vertical stone and tile installations
- Install hundreds of square feet per day
- Design and gear systems allow speed and dosing control
- No mixing just insert the dual component cartridge, screw on the mixing nozzle, and pull the trigger

PACKAGING:

1 LATAPOXY 310 Cordless Mixer per carton; 24 cartons per pallet

MVIS™ PREMIUM MORTAR BED

Refer to Data Sheet 263.0 9329-0060-21



A polymer fortified blend of carefully selected raw materials, portland cement and graded aggregates. MVIS™ Premium Mortar Bed does not require the use of latex admixtures. Just add water to produce thick bed mortar with exceptional strength. MVIS Premium Mortar Bed is ideal as the brown coat over wire lath. May be used to level walls and may also be used for sloping horizontal applications.

FEATURES/BENEFITS:

- Polymer fortified no need for job site mixing of latex additives
- Economical saves time and money
- High strength formula
- Exceeds ASTM C270 compressive strength requirements
- Use as a scratch or finish coat in place of Type S or Type N mortar
- Premixed no job site blending of powders required
- Pumpable for large scale veneer projects

PACKAGING:

60 lb (27.3 kg) bag; 56 bags per pallet

Approximate Coverage Per 60 lb (27.2 kg) bag

12 ft² at 1/2" (1.1 m² at 12 mm)

6 ft² at 1" thickness (0.56 m² at 25 mm)

3 ft² at 2" (0.3 m² at 50 mm)

LATAPOXY® 310 CORDLESS MIXER **AND NOZZLES**

Refer to Data Sheet 683.0 RT8480310 RT8480500



This dual-component mixer quickly dispenses LATAPOXY® 310 Stone Adhesive onto tile, porcelain, and stone veneers.

LATAPOXY® 310 STONE ADHESIVE

Refer to Data Sheets 679.0 and 679.3 S-310AB-NC-08 S-310AB-NC-08-1 S-310AB-NC-10 S-310AB-NC-10-1 S-310AB-CC-10 S-310AB-CC-10-1

See page 50 for futher details



A strong, two-component epoxy adhesive for spot-bonding large format tile and stone on vertical surfaces. Easier and faster than traditional methods of veneer installation.





