

### Product Description

TREMDrain® 2000 is a three-layer drainage mat including a nonwoven, needle-punched, polypropylene fabric, polystyrene core and polymeric film.

### Basic Uses

The TREMDrain Series of mats are used with TREMproof® and Paraseal® waterproofing membranes serving both as a protection course and replacement for traditional pipe and stone drainage systems.

### Features and Benefits

- TREMDrain Series Drainage and Protection Boards replace or eliminate the need for a separate protection course.
- Provide an uninterrupted flow plane and eliminate the opportunity for hydrostatic pressure to form against a wall.
- Lightweight and easy to install compared to conventional pipe and stone drainage.

### Availability

Immediately available from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

### Packaging

4' x 50' (1.22 M x 15.8 M)

### Storage

Store out of direct sunlight. Vertical storage recommended.

### Limitations

- Not for use beneath sand-set vehicular pavers.
- Not to be used as an exposed or wearing surface. Limit UV exposure to a maximum of 14 days.

### Installation

Refer to TREMDrain Series Application Instructions for specific application details. The techniques included may require modification to adjust to job-site conditions. Consult your local Tremco Sales Representative or Tremco Technical Service for specific design requirements.

### Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Product proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

**TREMDrain® 2000NW**

Multi-Composite Drainage and Protection Boards

**TYPICAL PHYSICAL PROPERTIES**

PROPERTY	TEST METHOD	VALUES US	VALUES SI
Typical Applications		Split Slab, Planters	
Roll Length		50'	15.24 M
Roll Width		4'	1.22 M
Roll Weight		54 lb	20.86 kg
Recycled Content		>60%	
<b>Fabric</b>			
Material		Nonwoven Needle-punched Polypropylene	
Weight	ASTM D3776	6 oz/yd <sup>2</sup>	203.43 g/M <sup>2</sup>
Grab Tensile Strength	ASTM D4632	205 lb	1090 N
CBR Puncture	ASTM D6241	580 lbs	2580 N
Grab Elongation	ASTM D4632	60%	
AOS	ASTM D4751	80 sieve	0.180 mm
Permittivity	ASTM D4491	1.8 sec <sup>-1</sup>	
Water Flow Rate	ASTM D4491	135 gpm/ft <sup>2</sup>	5501 Lpm/M <sup>2</sup>
Root Barrier Fabric		None	
UV Resistance	ASTM D4355	70% / 500 Hrs	70% / 500 Hrs
<b>Core</b>			
Material		Polystyrene	
Thickness	ASTM D1777	0.44 in	11 mm
Compressive Strength	ASTM D1621	18,000 lb /ft <sup>2</sup>	862 kPa
	ASTM D6364	18,000 lb /ft <sup>2</sup>	862 kPa
Backing Film		Yes	
In-Plane Flow Rate	ASTM D4716	18 gpm/ft	224 Lpm/m

**1119/TD2000NWDS-BG****Tremco Commercial Sealants & Waterproofing**

3735 Green Rd  
 Beachwood OH 44122  
 216.292.5000 / 800.321.7906

1451 Jacobson Ave  
 Ashland OH 44805  
 419.289.2050 / 800.321.6357

220 Wicksteed Ave  
 Toronto ON M4H1G7  
 416.421.3300 / 800.363.3213

1445 Rue de Coulomb  
 Boucherville QC J4B 7L8  
 514.521.9555

