

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Date of Issue: 04/05/2018

SECTION 1: IDENTIFICATION

Product Identifier 1.1.

Product Form: Mixture Product Name: SPARTACOTE™ Moisture Vapor Barrier Part A

1.2. **Intended Use of the Product**

Use of the Substance/Mixture: Vapor Reduction Membrane. For professional use only

1.3. Name, Address, and Telephone of the Responsible Party

Company LATICRETE International 1 Laticrete Park, N Bethany, CT 06524

T (203)-393-0010

www.laticrete.com

1.4. **Emergency Telephone Number**

Emergency Number

: For Chemical Emergency Call CHEMTREC day or night Within USA and Canada: 1.800.424.9300 Mexico: 1.800.681.9531 Outside USA and Canada: 1.703.527.3887 (collect calls accepted)

S

SECTION 2: HAZARDS IDENT	IFICATION
2.1. Classification of the Su	
GHS-US Classification	
Skin Corr. 1B H3:	14
Eye Dam. 1 H3	18
Skin Sens. 1 H3	
Repr. 2 H3	
Aquatic Acute 3 H40	
Aquatic Chronic 1 H4	10
Full text of hazard classes and H-s	statements : see section 16
2.2. Label Elements	
GHS-US Labeling	
Hazard Pictograms (GHS-US)	
	GHS05 GHS07 GHS08 GHS09
Signal Word (GHS-US)	: Danger
Hazard Statements (GHS-US)	: H314 - Causes severe skin burns and eye damage.
	H317 - May cause an allergic skin reaction.
	H318 - Causes serious eye damage.
	H361 - Suspected of damaging fertility or the unborn child.
	H402 - Harmful to aquatic life.
Precautionary Statements (GHS	H410 - Very toxic to aquatic life with long lasting effects.S-US) : P201 - Obtain special instructions before use.
Precautionary Statements (GHS	P202 - Do not handle until all safety precautions have been read and understood.
	P260 - Do not breathe vapors, mist, or spray.
	P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
	P272 - Contaminated work clothing must not be allowed out of the workplace.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves, protective clothing, and eye protection.
	P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
	P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated
	clothing. Rinse skin with water/shower.
	P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position
	comfortable for breathing.
	P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes.

Version: 1.0

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P391 - Collect spillage.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	GHS-US classification
2-Propenenitrile, reaction products with ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine and triethylenetetramine, hydrogenated	(CAS-No.) 1173092-74-4	18 - 74	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
1,3-Benzenedimethanamine	(CAS-No.) 1477-55-0	< 8.75	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Acute 3, H402
4-tert-Butylphenol	(CAS-No.) 98-54-4	< 7.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361 Aquatic Acute 2, H401 Aquatic Chronic 1, H410
1,6-Hexanediamine, 2,2,4-trimethyl-	(CAS-No.) 3236-53-1	< 2.5	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Urea, N,N'-bis[3-(dimethylamino)propyl]-	(CAS-No.) 52338-87-1	< 2.5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200]. Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

First-aid Measures After Skin Contact: Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

First-aid Measures After Eye Contact: Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Causes severe skin burns and eye damage. Skin sensitization. Suspected of damaging fertility or the unborn child.

Symptoms/Injuries After Inhalation: May be corrosive to the respiratory tract.

Symptoms/Injuries After Skin Contact: Causes severe irritation which will progress to chemical burns. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. **Chronic Symptoms:** Suspected of damaging fertility or the unborn child.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products:** Carbon oxides (CO, CO₂). Ammonia. Nitrogen oxides. Aldehydes. Low molecular weight hydrocarbon fragments.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Cautiously neutralize spilled liquid. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. May release corrosive vapors.

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, spray. Do not get in eyes, on skin, or on clothing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Handle empty containers with care because they may still present a hazard.

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container.

Incompatible Materials: Acids. Strong oxidizers. Reactive metals. Mineral acids. Peroxides. Materials reactive with hydroxyl compounds.

7.3. Specific End Use(s)

Vapor Reduction Membrane. For professional use only

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. **Control Parameters**

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

1,3-Benzenedimethanamine (1477-55-0)		
USA ACGIH	ACGIH Ceiling (mg/m ³)	0.1 mg/m ³
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	0.1 mg/m³

8.2. **Exposure Controls**

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

: Gloves. Protective clothing. Protective goggles. Face shield. Insufficient ventilation:

Personal Protective Equipment

- wear respiratory protection.
- : Chemically resistant materials and fabrics. Corrosion-proof clothing. **Materials for Protective Clothing** Hand Protection : Wear protective gloves. : Chemical safety goggles and face shield. **Eve and Face Protection Skin and Body Protection** : Wear suitable protective clothing. **Respiratory Protection**
 - : If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information	. When using, do not eat, drink or smoke.	
SECTION 9: PHYSICAL AND CHEM	IICAL PROPERTIES	
9.1. Information on Basic Physic	cal and Chemical Properties	
Physical State	: Liquid	
Appearance	: Yellow	
Odor	: Ammoniacal	
Odor Threshold	: No data available	
рН	: No data available	
Evaporation Rate	: No data available	
Melting Point	: No data available	
Freezing Point	: No data available	
Boiling Point	: No data available	
Flash Point	: > 212 °F (100 °C)	
Auto-ignition Temperature	: No data available	
Decomposition Temperature	: No data available	
Flammability (solid, gas)	: Not applicable	
Vapor Pressure	: No data available	
Relative Vapor Density at 20°C	: No data available	
Relative Density	: No data available	
Specific Gravity	: 1.04	
04/05/2018	EN (English US)	4

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility: Soluble in waterPartition Coefficient: N-Octanol/Water: No data availableViscosity: 680 cP

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials: Acids. Strong oxidizers. Reactive metals. Mineral acids. Peroxides. Materials reactive with hydroxyl compounds.

10.6. Hazardous Decomposition Products: Thermal decomposition generates: Ammonia gas. Corrosive vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity: Not classified

4-tert-Butylphenol (98-54-4)	
LD50 Oral Rat	4000 mg/kg
LD50 Dermal Rabbit	2318 mg/kg
1,3-Benzenedimethanamine (1477-55-0)	
LD50 Oral Rat	1090 mg/kg (Species: Wistar)
LD50 Dermal Rabbit	2 g/kg
LC50 Inhalation Rat	350 ppm/4h
LC50 Inhalation Rat	1.34 mg/l/4h (Species: Wistar)
1,6-Hexanediamine, 2,2,4-trimethyl- (3236-53-1)	
ATE (Oral)	500.00 mg/kg body weight

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May be corrosive to the respiratory tract.

Symptoms/Injuries After Skin Contact: Causes severe irritation which will progress to chemical burns. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. **Chronic Symptoms:** Suspected of damaging fertility or the unborn child.

SECTION 12: ECOLOGICAL INFORMATION

Ecology - General	: Harmful to aquatic life. Very toxic to aquatic life with long lasting effects.	
4-tert-Butylphenol (98-54-4)		
LC50 Fish 1	4.71 - 5.62 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	3.9 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 Fish 2	6.9 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])	
EC50 Daphnia 2	3.4 - 4.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
NOEC Chronic Fish	0.1 mg/l (Species: Pimephales promelas)	
NOEC Chronic Algae	0.32 mg/l	
1,3-Benzenedimethanamine (1477-55-0)		
LC50 Fish 1	75 mg/l	
EC50 Daphnia 1	15 mg/l	
NOEC Chronic Crustacea	4.7 mg/l	

SPARTACOTE™ Moisture Vapor Barrier Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

According to rederal Register / Vol. 77, No. 58	/ Monday, March 26, 2012 / Rules and Regulations
12.2. Persistence and De	gradability
SPARTACOTE [™] Moisture Vap	or Barrier Part A
Persistence and Degradability	May cause long-term adverse effects in the environment.
12.3. Bioaccumulative Po	otential
SPARTACOTE [™] Moisture Vap	or Barrier Part A
Bioaccumulative Potential	Not established.
4-tert-Butylphenol (98-54-4)	
BCF Fish 1	34 - 240
Log Pow	2.44
	additional information available
12.5. Other Adverse Effe	
Other Information	: Avoid release to the environment.
SECTION 13: DISPOSAL CO	
13.1. Waste Treatment N	
	tions: Dispose of contents/container in accordance with local, regional, national, and international
regulations.	ainer may remain hazardous when empty. Continue to observe all precautions.
	void release to the environment. This material is hazardous to the aquatic environment. Keep out
of sewers and waterways.	The release to the environment. This material is hazardous to the aquatic environment. Reep out
SECTION 14: TRANSPORT I	ΝΕΟΡΜΑΤΙΟΝ
	ed herein were prepared in accordance with certain assumptions at the time the SDS was n a number of variables that may or may not have been known at the time the SDS was issued.
14.1. In Accordance with	
Proper Shipping Name	: AMINES, LIQUID, CORROSIVE, N.O.S. (2-Propenenitrile, reaction products with
	ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine
Hazard Class	and triethylenetetramine, hydrogenated) : 8
Identification Number	: 0 : UN2735
Label Codes	
Packing Group	
Marine Pollutant	: Marine pollutant
ERG Number	: 153
14.2. In Accordance with	
Proper Shipping Name	: AMINES, LIQUID, CORROSIVE, N.O.S. (2-Propenenitrile, reaction products with
Toper Shipping Rune	ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine
	and triethylenetetramine, hydrogenated)
Hazard Class	: 8
Identification Number	: UN2735
Packing Group	:
Label Codes	: 8
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-B
Marine Pollutant	: Marine pollutant
14.3. In Accordance with	ΙΑΤΑ
Proper Shipping Name	: AMINES, LIQUID, CORROSIVE, N.O.S. (2-Propenenitrile, reaction products with
	ethylenediamine, hydrogenated, reaction products with benzaldehyde, diethylenetriamine
	and triethylenetetramine, hydrogenated)
Packing Group	: 11
Identification Number	: UN2735
Hazard Class	: 8
Label Codes	: 8
ERG Code (IATA)	: 8L

SPARTACOTE™ Moisture Vapor Barrier Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: REGULATORY INFORMATIO	N		
15.1. US Federal Regulations			
SPARTACOTE™ Moisture Vapor Barrier Part A			
SARA Section 311/312 Hazard Classes	Health hazard - Reproductive toxicity		
	Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation		
	Health hazard - Serious eye damage of eye initiation Health hazard - Skin corrosion or Irritation		
Urea, N,N'-bis[3-(dimethylamino)propyl]- (523			
Listed on the United States TSCA (Toxic Substar			
4-tert-Butylphenol (98-54-4)			
Listed on the United States TSCA (Toxic Substar	nces Control Act) inventory		
1,3-Benzenedimethanamine (1477-55-0)			
Listed on the United States TSCA (Toxic Substar	nces Control Act) inventorv		
1,6-Hexanediamine, 2,2,4-trimethyl- (3236-53-			
Listed on the United States TSCA (Toxic Substar	•		
15.2. US State Regulations			
1,3-Benzenedimethanamine (1477-55-0)			
U.S Massachusetts - Right To Know List			
U.S New Jersey - Right to Know Hazardous Su	ibstance List		
U.S Pennsylvania - RTK (Right to Know) List			
SECTION 16: OTHER INFORMATION, INC	LUDING DATE OF PREPARATION OR LAST REVISION		
•	: 04/05/2018		
Other Information :	: This document has been prepared in accordance with the SDS requirements of		
	the OSHA Hazard Communication Standard 29 CFR 1910.1200		
GHS Full Text Phrases:			
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4		
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4		
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4		
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2		
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3		
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1		
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3		
Eye Dam. 1	Serious eye damage/eye irritation Category 1		
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A		
Repr. 2	Reproductive toxicity Category 2		
Skin Corr. 1A	Skin corrosion/irritation Category 1A		
Skin Corr. 1B	Skin corrosion/irritation Category 1B		
Skin Irrit. 2	Skin corrosion/irritation Category 2		
Skin Sens. 1	Skin sensitization, Category 1		
Skin Sens. 1B	Skin sensitization, category 1B		
H302	Harmful if swallowed		
H312	Harmful in contact with skin		
H314	Causes severe skin burns and eye damage		
H315	Causes skin irritation		
H317	May cause an allergic skin reaction		
H318	Causes serious eye damage		
H319	Causes serious eye irritation		
H332	Harmful if inhaled		
H361	Suspected of damaging fertility or the unborn child		
H401	Toxic to aquatic life		
H402	Harmful to aquatic life		

H410

Very toxic to aquatic life with long lasting effects

SPARTACOTE™ Moisture Vapor Barrier Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H412 Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)