

## Rolled Mastic Sealants

### Foil-Grip 1402

Foil-Grip 1402 is a pressure sensitive, 40-year cycle, duct joint and general purpose rolled mastic sealant. It provides an instant water resistant grip to most surfaces including sheet metal, duct board, flex duct, PVC coated duct, and duct wrap vapor barriers. Foil-Grip 1402 is suitable for subgrade application on PVC coated duct and is ideal for replacement applications



- 40-Year cycle indoor/outdoor
- Instant water-resistant grip
- UL Classified
- Pressure sensitive
- Suitable for subgrade application on PVC coated duct
- Passes SCAQMD Rule 1168
- True Zero-VOC
- Zero Dry Time
- Leed Compliant
- City of Los Angeles Approval

### Foil-Grip 1404

Foil-Grip 1404-181BFX is a UL 181B-FX listed pressures sensitive rolled mastic sealant. The Foil-Grip 1404-181BFX has superior tack for instant grab strength to galvanized metal, flex duct, PVC coated pipe, and PVC coated ductwork for an immediate airtight bond. The foil facer/butyl adhesive composite provides excellent UV resistance coupled with outstanding water resistance. The easy tear provides a fast installation for airtight seals on above and below grade ductwork applications.



- Code Approved
- Ideal for replacement applications
- Zero dry time
- True zero VOC
- Immediate air-tight bond
- Approved for indoor/outdoor use
- Easy tear
- 17-Mil Thickness

### All-Purpose 1602

All-Purpose is a pressure sensitive, 30-year cycle, duct joint and general purpose rolled sealant. All-Purpose provides an instant aggressive grip to most surfaces including sheet metal, duct board, and flex duct for indoor applications. The Gray Matter™ butyl adhesive/sealant is a 100% solids sealant, which stays flexible and does not release from the substrate.



- 30 year life cycle
- All-purpose, pressure sensitive rolled sealant aggressively grips to most surfaces
- DuPont Sontara® polyester backing allows for easy painting or coating
- Passes SCAQMD Rule 1168

### AFT-701

Aluma-Grip AFT-701 is a heavy-duty, pressure-sensitive, 40-year-cycle, duct joint rolled sealant. AFT-701 provides an aggressive water-resistant grip to most surfaces including sheet metal, duct board, flex duct, PVC-coated duct, and duct wrap vapor barriers. AFT-701 is suitable for subgrade application on PVC-coated duct.



- 40-Year cycle indoor/outdoor
- Heavy-duty, pressure-sensitive
- Immediate sealing on contact
- Long-term adhesion
- Passes SCAQMD Rule 1168
- True Zero-VOC
- Zero Dry Time
- LEED Compliant
- Passes 2,000 hours QUV
- 30-Mil Thickness



## Construction/Flashing Tapes

### TGM-3300

TGM-3300 is a butyl-based material between two release liners capable of bonding a variety of items together. TGM-3300 offers an aggressive grip, superior long-term bonding and stays flexible during application, assuring immediate adhesion on contact. Perfect for metal, plastics and some fabrics, TGM-3300's pressure sensitive properties allow a fast, clean and easy application.



- Double sided butyl tape, capable of bonding a variety of items together
- Aggressive grip
- Superior long term bonding
- Excellent water resistance

### BRT-801

BRT-801 is a black, water resistant, hip and ridge sealant for use under tile and roof applications. BRT-801 has an aggressive grip, superior long-term adhesion and stays flexible during application, assuring immediate sealing on contact. Providing leak-proof results, this butyl adhesive/sealant is asphalt and solvent free. BRT-801 is also reverse-rolled for easy, fast application.



- Reverse-rolled for easy, fast application
- Superior long-term adhesion
- U.V. Resistant
- Ideal for Hip & Ridge sealing
- Immediate water tight bond
- Asphalt and solvent free
- High Density Polyethylene

### TPO-2265

TPO-2265 is a UV and weather resistant white wrap with the Gray Matter™ enhanced formula butyl sealant. The TPO membrane is a proven roofing membrane that provides excellent UV protection and an impact resistance surface.



- Excellent for seams
- Aggressive grip & adhesion
- Immediate leak proof results
- Stays flexible
- Easy, fast application
- UV Resistant
- Thermoplastic Polyolefin (TPO) Rubber Backing

### RMR-6325

RMR-6325 is a white, surface and shape adapting rubber membrane for flashing and sealing unusual roofing needs, including fasteners on metal roof installations. RMR-6325 has an aggressive grip, superior long-term adhesion and stays flexible during application, assuring immediate sealing on contact. RMR-6325's pressure sensitive properties allow a fast, clean and easy application.



- Superior water resistance
- Aggressive grip
- Adaptable rubber membrane makes it ideal for flashings and sealing unusual roofing needs
- Pressure sensitive
- Backing is a white Carlisle EPDM Roofing Membrane
- Superior long-term adhesion

