



## PROTECTO LWM200™ VAPOR PERMEABLE LIQUID WATERPROOFING MEMBRANE

A non hazardous, environmentally friendly, elastomeric polymer dispersion waterproofing membrane. This water-based, non-bituminous, aqueous polymer dispersion is specifically designed for the demanding requirements of waterproofing window, door and CMU openings.

- Meets or exceeds standards set by FMA/AAMA 200-12 and requirements for AAMA 714-15
- Great for rough openings in masonry construction and replacement installations
- Single component product/no additives needed and water-based for easy cleanup
- One step application/no primer needed
- Excellent adhesion/bonds to multiple surfaces
- Can be used as a capillary break coating to keep ground moisture from wicking into foundation walls
- Meets requirements of the Florida Building Code
- Available in 1 and 5 gallon containers



## PROTECTO CMU100™ VAPOR PERMEABLE WATER RESISTANT COATING

A water resistant liquid membrane coating for application to concrete and masonry. It is an advanced hybrid acrylic polymer blended coating that is both flexible and breathable and can be applied with a brush, roller or airless sprayer. The coating is odorless, dries tan and can be painted any color.

- Meets or exceeds ICC-ES AC29 requirements
- Great for rough openings in masonry construction and replacement installations
- Single component product/no additives needed
- One step application/no primer needed
- Excellent adhesion/bonds to multiple surfaces
- Water-based for easy cleanup
- Available in 1 and 5 gallon containers



## PROTECTO SEAL 45™ ALUMINUM FACED WATERPROOFING MEMBRANE

Made with a rubberized asphalt, our all purpose, exposable waterproofing membrane withstands weather elements and is UV resistant, making it excellent for use around skylights, gutters, HVAC units, commercial window flashing and low pitched and porch roofs.

- Rubberized asphalt adhesive
- UV rated for long term exposure
- Aluminum foil facer film for added sealant adhesion
- Puncture and abrasion resistant
- Forms a positive air/vapor barrier
- Available in mill finish only
- IAPMO ER #362
- Roll sizes available: 4", 6", 9", 12", 36" x 50' • High temperature: 240°F



## PROTECTO SEAL 45 BUTYL™ ALUMINUM FACED WATERPROOFING MEMBRANE

Our butyl alternative to Protecto Seal 45. An all purpose, exposable waterproofing membrane withstands weather elements and is UV resistant, making it excellent for use around skylights, gutters, HVAC units, commercial window flashing and low pitched and porch roofs.

- Proprietary recycled 100% butyl adhesive
- UV rated for long term exposure
- Aluminum foil facer film for added sealant adhesion
- Fully adhered system
- Puncture and abrasion resistant
- Forms a positive air/vapor barrier
- Available in mill finish only
- Roll sizes available: 4", 6", 9", 12" x 50' • High temperature: 300°F