



COLPHENE FLAM 180 FR GR

COLPHENE Flam 180 FR GR is an SBS-modified bitumen cap ply for use in approved multi-ply waterproofing assemblies. COLPHENE Flam 180 FR GR is composed of a proprietary formulation of elastomeric styrene-butadiene-styrene (SBS) polymer modified bitumen and is reinforced with a tough, dimensionally stable non-woven polyester mat. The topside is surfaced with ceramic coated granules and underside is surfaced with polyolefin burn-off film to optimize heat welding.

PRODUCT CODE: 01226

DIMENSIONS: 32.8 ft (10.0 m) x 39.4 in (1.0m)

THICKNESS: 157 mils (4.0 mm)



COLPHENE 250 FR GR

COLPHENE 250 FR GR is an SBS-modified bitumen cap ply for use in approved multi-ply waterproofing assemblies. COLPHENE 250 FR GR is composed of a proprietary formulation of elastomeric styrene-butadiene-styrene (SBS) polymer modified bitumen and is reinforced with a tough, dimensionally stable non-woven polyester mat. The topside is surfaced with ceramic coated granules and the underside is surfaced with fine mineral aggregate to facilitate cold adhesive and hot asphalt applications.

PRODUCT CODE: 01225

DIMENSIONS: 32.8 ft (10.0 m) x 39.4 in (1.0m)

THICKNESS: 157 mils (4.0 mm)



COLPHENE FLAM 250 FR GR

COLPHENE Flam 250 FR GR is an SBS-modified bitumen cap ply for use in approved multi-ply waterproofing assemblies. COLPHENE Flam 250 FR GR is composed of a proprietary formulation of elastomeric styrene-butadiene-styrene (SBS) polymer modified bitumen and is reinforced with a tough, dimensionally stable non-woven polyester mat. The topside is surfaced with ceramic coated granules and underside is surfaced with polyolefin burn-off film to optimize heat welding.

PRODUCT CODE: 01223

DIMENSIONS: 32.8 ft (10.0 m) x 39.4 in (1.0m)

THICKNESS: 157 mils (4.0 mm)